

BIOPTICAL HOLOGRAPHIC LASER SCANNING SYSTEM

Inventors:

Frank Check  
LeRoy Dickson  
John Groot  
Timothy Good

RELATED CASES

This is a Continuation-in-Part of U.S. Application No. 09/551,887 filed April 18, 2000; copending Application Serial No. 08/949,915 filed October 14, 1997; copending Application Serial No. 08/726,522 filed October 7, 1996; which is a Continuation of Application Serial No. 08/573,949 filed December 18, 1995, now abandoned; which is a Continuation-in-Part of Application Serial Nos. 08/615,054 filed March 12, 1996; 08/476,069 filed June 7, 1995, now U.S. Letters Patent 5,591,953; 08/561,479 filed November 20, 1995, now U.S. Letters Patent No. 5,661,292; which is a Continuation of 08/293,695 filed August 19, 1994, now U.S. Letters Patent 5,468,951; 08/293,493 filed August 19, 1994, now U.S. Letters Patent 5,525,789; 08/475,376 filed June 7, 1995, now U.S. Letters Patent 5,637,852; 08/439,224 filed May 11, 1995, now U.S. Letters Patent 5,627,359; and 08/292,237 filed August 17, 1994, each commonly owned by Assignee, Metrologic Instruments, Inc., of Blackwood, New Jersey, and is incorporated herein by reference as if fully set forth herein.

BACKGROUND OF THE INVENTION

Field of Invention

The present invention relates generally to holographic laser scanners of ultra-compact design capable of reading bar code symbols in point-of-sale (POS) and other demanding scanning environments.

Brief Description of the Prior Art

The use of bar code symbols for product and article identification is well known in the art.

Presently, various types of bar code symbol scanners have been developed. In general, these bar code symbol readers can be classified into two distinct classes.

The first class of bar code symbol reader simultaneously illuminates all of the bars and spaces of a bar code symbol with light of a specific wavelength(s) in order to capture an image

1 thereof for recognition and decoding purposes. Such scanners are commonly known as CCD  
2 scanners because they use CCD image detectors to detect images of the bar code symbols being  
3 read.

4 The second class of bar code symbol reader uses a focused light beam, typically a  
5 focused laser beam, to sequentially scan the bars and spaces of a bar code symbol to be read.  
6 This type of bar code symbol scanner is commonly called a "flying spot" scanner as the focused  
7 laser beam appears as "a spot of light that flies" across the bar code symbol being read. In  
8 general, laser bar code symbol scanners are subclassified further by the type of mechanism used  
9 to focus and scan the laser beam across bar code symbols.

10 Polygon-based laser scanning systems employ lenses and moving (i.e. rotating or  
11 oscillating) polygon mirrors and/or other optical elements in order to focus and scan laser beams  
12 across bar code symbols during code symbol reading operations. Examples of such polygon-  
13 based laser scanning systems is described in U.S. Patents No. 4,006,343; 4,093,865; 4,960,985;  
14 5,073,702; 5,229,588; and JP-54-33740, each incorporated herein by reference in its entirety.

15 Holographic-based laser scanning systems employ lenses and moving (i.e. rotating)  
16 holographic elements and/or other optical elements in order to focus and scan laser beams across  
17 bar code symbols during code symbol reading operations. Examples of such holographic-based  
18 laser scanning systems is described in US Patent Nos. 4,415,224; 4,758,058; 4,748,316;  
19 4,591,242; 4,548,463; 4,652,732; 4,794,237; 4,647,143; 5,331,445; 5,416,505; 5,475,207;  
20 5,705,802; 5,837,988; and JP64-48017, each incorporated herein by reference in its entirety.

21 In demanding retail scanning environments, it is common to employ polygon-based laser  
22 scanning systems that have both bottom and side scanning windows to enable highly aggressive  
23 scanner performance, whereby the cashier need only drag a bar coded product past these  
24 scanning windows for the bar code thereon to be automatically read with minimal assistance of  
25 the cashier or checkout personal. Such dual scanning window systems are typically referred to  
26 as "bioptical" laser scanning systems as such systems employ two sets of optics disposed behind  
27 the bottom and side scanning windows thereof. Examples of polygon-based bioptical laser  
28 scanning systems are disclosed in US Patent Nos. 5,206,491; 5,229,588; 5,684,289; 5,705,802;  
29 5,801,370; and 5,886,336, each incorporated herein by reference in its entirety.

30 In general, prior art bioptical laser scanning systems are generally more aggressive than  
31 conventional single scanning window systems. For this reason, bioptical scanning systems are  
32 often deployed in demanding retail environments, such as supermarkets and high-volume  
33 department stores, where high check-out throughput is critical to achieving store profitability and  
34 customer satisfaction.

35 While prior art bioptical scanning systems represent a technological advance over most  
36 single scanning window systems, prior art bioptical scanning systems in general suffered from  
37 various shortcomings and drawbacks.

38 In particular, by virtue of the dual scanning windows and supporting optics required by  
39 prior art bioptical laser scanning systems, such scanning systems have been physically larger  
40 than many retail environments would otherwise desire, as space near the point-of-sale is the most  
41 valuable space within the retail environment. Also, the laser scanning patterns of prior art  
42 bioptical laser scanning systems are not optimized in terms of scanning coverage and

performance, and are generally expensive to manufacture by virtue of the large number of optical components presently required to constructed such laser scanning systems.

Thus, there is a great need in the art for an improved bioptical-type laser scanning bar code symbol reading system, while avoiding the shortcomings and drawbacks of prior art laser scanning systems and methodologies.

### OBJECTS AND SUMMARY OF THE PRESENT INVENTION

Accordingly, a primary object of the present invention is to provide a novel bioptical-type holographic laser scanning system which is free of the shortcomings and drawbacks of prior art bioptical laser scanning systems and methodologies.

Another object of the present invention is to provide a bioptical holographic laser scanning system, wherein a plurality of pairs of quasi-orthogonal laser scanning planes are projected within predetermined regions of space contained within a 3-D scanning volume defined between the bottom and side scanning windows of the system.

Another object of the present invention is to provide a novel bioptical holographic laser scanning system, wherein the plurality of pairs of quasi-orthogonal laser scanning planes are produced using a holographic scanning disc having holographic scanning facets that have high and low elevation angle characteristics as well as left, right and zero skew angle characteristics.

Another object of the present invention is to provide a bioptical holographic laser scanning system, wherein the each pair of quasi-orthogonal laser scanning planes comprises a plurality of substantially-vertical laser scanning planes for reading bar code symbols having bar code elements (i.e. ladder-type bar code symbols) that are oriented substantially horizontal with respect to the bottom scanning window, and a plurality of substantially-horizontal laser scanning planes for reading bar code symbols having bar code elements (i.e. picket-fence type bar code symbols) that are oriented substantially vertical with respect to the bottom scanning window.

Another object of the present invention is to provide a bioptical holographic laser scanning system comprising a plurality of laser scanning stations, each of which produces a plurality of pairs of quasi-orthogonal laser scanning planes are projected within predetermined regions of space contained within a 3-D scanning volume defined between the bottom and side scanning windows of the system.

Another object of the present invention is to provide a bioptical holographic laser scanning system, wherein the plurality of pairs of quasi-orthogonal laser scanning planes are produced using a holographic scanning disc supporting holographic scanning facets having high and low elevation angle characteristics and left, right and zero skew angle characteristics.

Another object of the present invention is to provide a bioptical holographic laser scanning system, wherein each laser scanning station produces a plurality of pairs of quasi-orthogonal laser scanning planes which can read bar code symbol that is orientated with bar code elements arranged in either a substantially vertical (i.e. picket-fence) or substantially horizontal (i.e. ladder) configuration with respect to the horizontal scanning window of the system.

Another object of the present invention is to provide such a bioptical holographic laser scanning system employing four laser scanning systems, wherein the first and third laser

1 scanning stations employ mirror groups and scanning facets having only high elevation  
2 characteristics and left and right skew angle characteristics so as to produce from each station a  
3 plurality of pairs of quasi-orthogonal laser scanning planes capable of reading bar code symbol  
4 orientated with bar code elements arranged in either a substantially vertical (i.e. picket-fence) or  
5 substantially horizontal (i.e. ladder) configuration with respect to the horizontal scanning  
6 window of the system.

7 Another object of the present invention is to provide such a bioptical holographic laser  
8 scanning system, wherein the second laser scanning station employs mirror groups and scanning  
9 facets having only low elevation characteristics and zero skew angle characteristics so as to  
10 produce from each station a plurality of pairs of quasi-orthogonal laser scanning planes capable  
11 of reading bar code symbol orientated with bar code elements arranged in either a substantially  
12 vertical (i.e. picket-fence) or substantially horizontal (i.e. ladder) configuration with respect to  
13 the horizontal scanning window of the system.

14 Another object of the present invention is to provide such a bioptical holographic laser  
15 scanning system, wherein the fourth laser scanning station employs mirror groups and scanning  
16 facets having only high elevation characteristics and zero skew angle characteristics so as to  
17 produce from each station a plurality of laser scanning planes capable of reading bar code  
18 symbol orientated with bar code elements arranged in either a substantially vertical (i.e. picket-  
19 fence) configuration with respect to the horizontal scanning window of the system.

20 Another object of the present invention is to provide a bioptical holographic laser  
21 scanning system, wherein the plurality of pairs of quasi-orthogonal laser scanning planes are  
22 produced using S-polarized laser beams directed incident the holographic scanning disc.

23 Another object of the present invention is to provide a bioptical holographic laser  
24 scanning system, wherein four symmetrically placed visible laser diodes (VLDs) are used to  
25 create the plurality of pairs of quasi-orthogonal laser scanning planes.

26 Another object of the present invention is to provide a bioptical holographic laser  
27 scanning system, wherein a single VLD is used to create the vertical window scan pattern,  
28 thereby minimizing crosstalk.

29 Another object of the present invention is to provide a bioptical holographic laser  
30 scanning system, wherein the sizes of the laser beam folding mirrors employed at each laser  
31 scanning station of the present invention are minimized.

32 Another object of the present invention is to provide a bioptical holographic laser  
33 scanning system, wherein blocking of light return paths by the laser beam folding mirrors has  
34 been eliminated.

35 Another object of the present invention is to provide a bioptical holographic laser  
36 scanning system, wherein mechanical interference between individual laser beam folding mirrors  
37 within the system has been eliminated.

38 Another object of the present invention is to provide a bioptical holographic laser  
39 scanning system, wherein the angles of incidence of the laser scanning beams at the horizontal  
40 scanning window have been optimized.

41 Another object of the present invention is to provide a bioptical holographic laser  
42 scanning system which generates a laser scanning pattern providing 360 degrees of scan



1 coverage at a POS station, while the internal mirror-space volume of the scanning system has  
2 been minimized.

3 Another object of the present invention is to provide such a bioptical holographic laser  
4 scanning system, wherein the "sweet spot" of the 360 laser scanning pattern is located at and  
5 above the center of the horizontal (i.e. bottom) scanning window, regardless of the item  
6 orientation or location of the bar code on the item.

7 Another object of the present invention is to provide such a bioptical holographic laser  
8 scanning system, wherein the center of all groups of laser scanning planes generated by the  
9 system is directed toward the center of the horizontal scanning window, or to a line normal to the  
10 horizontal scanning window at the center thereof, thereby enhancing operator productivity by  
11 providing the feedback "beep" at substantially the same location above the horizontal scanning  
12 window for each and every item being scanned.

13 Another object of the present invention is to provide a bioptical holographic laser  
14 scanning system, wherein the size of the scan data collecting photodetector at each laser  
15 scanning station is minimized.

16 Another object of the present invention is to provide a bioptical holographic laser  
17 scanning system, wherein the location of the scan data collecting photodetector at each laser  
18 scanning station is determined using a novel spreadsheet-based design process that minimizes the  
19 vertical space required for placement of the parabolic light collection mirror beneath the  
20 scanning disc.

21 Another object of the present invention is to provide a bioptical holographic laser  
22 scanning system, wherein the size, shape and orientation of the scan data collecting  
23 photodetector at each laser scanning station is designed so that the lateral shift of the reflected  
24 beam image across the light sensitive surface of the photo detector, as a scanned item moves  
25 through the depth of field of the scanning region of the scanning station, which results in a  
26 relatively uniform light level reaching the light sensitive surface of the photodetector.

27 Another object of the present invention is to provide a bioptical holographic laser  
28 scanning system, wherein the shift of the collected light across the data detector (as the item  
29 moves through the depth of field of the scanning region) minimizes variation in signal.

30 Another object of the present invention is to provide a bioptical holographic laser  
31 scanning system comprising a holographic scanning disc with multiple facets which  
32 simultaneously focus multiple scanning beams to overlapping regions in the 3-D scanning  
33 volume at varying focal distances (preferably, less than 2 inches or less difference in focal  
34 distance), which minimizes the effects of paper noise.

35 Another object of the present invention is to provide a bioptical holographic laser  
36 scanning system, which allows the same facets to be used for both the horizontal and vertical  
37 windows even though the distances to the items to be scanned is different for the two windows.

38 Another object of the present invention is to provide a bioptical holographic laser  
39 scanning system, wherein use of a 12 facet disk design to increase the signal level for a 6 inch  
40 disk, necessary for POS scanners, which must provide lower laser power levels at the scan  
41 windows.

1 Another object of the present invention is to provide a bioptical holographic laser  
2 scanning system, wherein use of an S-polarized beam at the disk to maximize signal and provide  
3 better resolution throughout the DOF  
4 region.

5 Another object of the present invention is to provide a bioptical holographic laser  
6 scanning system, wherein use of skew facets with symmetric Left/Right skew, which allows the  
7 same scan pattern to be produced by both the fore and aft scanning stations.

8 Another object of the present invention is to provide a bioptical holographic laser  
9 scanning system, wherein the vertical-window horizontal scan lines and the operator-side-station  
10 horizontal scan lines are split and tilted for enhanced scan coverage.

11 Another object of the present invention is to provide a bioptical holographic laser  
12 scanning system, wherein recessing selected portions of the scanner base plate allow reduction of  
13 the box height.

14 Another object of the present invention is to provide a bioptical holographic laser  
15 scanning system, wherein parabolic mirror with modified, non-sector-shaped, cross-section  
16 maximize light collection efficiency.

17 Another object of the present invention is to provide a bioptical holographic laser  
18 scanning system, wherein use of optimum skew angle for each of the skew facets provides  
19 maximum scan coverage while minimizing the mirror-space volume.

20 Another object of the present invention is to provide a bioptical holographic laser  
21 scanning system, wherein diffraction angles are selected to provide maximum scan coverage  
22 while still allowing complete blockage of the facet from undesired ambient light.

23 Another object of the present invention is to provide a bioptical holographic laser  
24 scanning system, wherein a fixed beam blocker with optimum shape prohibits ambient light from  
25 entering the facets at the zero order beam angle, which light would otherwise be directed to the  
26 data detector by the parabolic mirror thereby increasing the noise level.

27 Another object of the present invention is to provide a bioptical holographic laser  
28 scanning system, wherein undercut box design allows for a smaller scanner footprint in both the  
29 X-dimension and the Y-dimension.

30 Another object of the present invention is to provide a bioptical holographic laser  
31 scanning system, wherein turning the VLD off when the scan line is no longer in the window,  
32 thereby eliminating unwanted internal scattering of the laser light and extends the life of the  
33 laser.

34 Another object of the present invention is to provide a bioptical holographic laser  
35 scanning system capable of generating a complex of pairs of quasi-orthogonal laser scanning  
36 planes, each composed by a plurality of substantially-vertical laser scanning planes for reading  
37 bar code symbols having bar code elements (i.e. ladder-type bar code symbols) that are oriented  
38 substantially horizontal with respect to the bottom scanning window, and a plurality of  
39 substantially-horizontal laser scanning planes for reading bar code symbols having bar code  
40 elements (i.e. picket-fence type bar code symbols) that are oriented substantially vertical with  
41 respect to the bottom scanning window.

1 Another object of the present invention is to provide a bioptical holographic laser  
2 scanning system, wherein each scan data collecting photodetector is positioned behind a beam  
3 folding mirror having a small hole formed therethrough to allow the return light from a parabolic  
4 mirror beneath the scanning disc to reach the photodetector, thereby enabling optimum  
5 placement of the photodetector and nearly maximum use of the surface of the beam folding  
6 mirror for light collection while providing a light shield for the data detector.

7 Another object of the present invention is to provide a bioptical holographic laser  
8 scanning system, wherein the light collection efficiency of each scanning facet is optimized in  
9 order to compensate for variations in facet collection area during laser scanning operations.

10 Another object of the present invention is to provide a bioptical holographic laser  
11 scanning system, wherein a beam deflecting mirror is supported on the back side of each  
12 parabolic collection mirror, beneath a notch formed therein, to allow an incident laser beam,  
13 produced beyond the scanning disc, to be directed through the light collection mirror and onto  
14 the point of incidence of the scanning disc during scanning operation.

15 Another object of the present invention is to provide a bioptical holographic laser  
16 scanning system, wherein a single beam folding mirror is used as the last outgoing mirror to  
17 produce a plurality of different laser scanning planes that are projected out through the vertical  
18 scanning window, thereby allowing greater light collection for a given amount of space (or  
19 potentially less space).

20 Another object of the present invention is to provide a bioptical holographic laser  
21 scanning system, wherein a light pipe or other light guiding structure can be used to conduct  
22 collected light at a point of collection within the system, and guiding such light to a  
23 photodetector located at a convenient location within the system.

24 Another object of the present invention is to provide a bioptical holographic laser  
25 scanning system, wherein a light-collection cone can be used to reduce the size of the  
26 photodetector.

27 Another object of the present invention is to provide a bioptical holographic laser  
28 scanning system which produces a three-dimensional laser scanning volume that is substantially  
29 greater than the volume of the housing of the holographic laser scanner itself, and provides full  
30 omni-directional scanning within the laser scanning volume.

31 A further object of the present invention is to provide such a bioptical holographic laser  
32 scanning system, in which the three-dimensional laser scanning volume has multiple focal planes  
33 and a highly confined geometry extending about a projection axis extending from the scanning  
34 windows of the holographic scanning system.

35 A further object of the present invention is to provide such a bioptical holographic laser  
36 scanning system, in which laser light produced from a particular holographic optical element  
37 reflects off a bar code symbol, passes through the same holographic optical element, and is  
38 thereafter collimated for light intensity detection.

39 A further object of the present invention is to provide such a bioptical holographic laser  
40 scanning system, in which a plurality of lasers simultaneously produce a plurality of laser beams  
41 which are focused and scanned through the scanning volume by a rotating disc that supports a  
42 plurality of holographic facets.

1 A further object of the present invention is to provide such a bioptical holographic laser  
2 scanning system, in which the holographic optical elements on the rotating disc maximize the  
3 use of the disk space for light collection, while minimizing the laser beam velocity at the focal  
4 planes of each of the laser scan patterns, in order to minimize the electronic bandwidth required  
5 by the light detection and signal processing circuitry.

6 A further object of the present invention is to provide a compact bioptical holographic  
7 laser scanning system, in which substantially all of the available light collecting surface area on  
8 the scanning disc is utilized and the light collection efficiency of each holographic facet on the  
9 holographic scanning disc is substantially equal, thereby allowing the holographic laser scanner  
10 to use a holographic scanning disc having the smallest possible disc diameter.

11 A further object of the present invention is to provide such a bioptical holographic laser  
12 scanning system, in which laser beam astigmatism caused by the inherent astigmatic difference  
13 in each visible laser diode is effectively eliminated prior to the passage of the laser beam through  
14 the holographic optical elements on the rotating scanning disc.

15 A further object of the present invention is to provide such a bioptical holographic laser  
16 scanning system, in which the dispersion of the relatively broad spectral output of each visible  
17 laser diode by the holographic optical elements on the scanning disc is effectively automatically  
18 compensated for as the laser beam propagates from the visible laser diode, through an integrated  
19 optics assembly, and through the holographic optical elements on the rotating disc of the  
20 holographic laser scanner.

21 A further object of the present invention is to provide such a bioptical holographic laser  
22 scanning system, in which a conventional visible laser diode is used to produce a laser scanning  
23 beam, and a simple and inexpensive arrangement is provided for eliminating or minimizing the  
24 effects of the dispersion caused by the holographic disc of the laser scanner.

25 A further object of the present invention is to provide such a bioptical holographic laser  
26 scanning system, in which the inherent astigmatic difference in each visible laser diode is  
27 effectively eliminated prior to the laser beam passing through the holographic optical elements  
28 on the rotating disc.

29 A further object of the present invention is to provide such a bioptical holographic laser  
30 scanning system, in which the laser beam produced from each laser diode is processed by a  
31 single, ultra-compact optics module in order to circularize the laser beam produced by the laser  
32 diode, eliminate the inherent astigmatic difference therein, as well as compensate for  
33 wavelength-dependent variations in the spectral output of each visible laser diode, such as  
34 superluminescence, multi-mode lasing, and laser mode hopping, thereby allowing the use of the  
35 resulting laser beam in holographic scanning applications demanding large depths of field.

36 A further object of the present invention is to provide such a bioptical holographic laser  
37 scanning system, in which an independent light collection/detection subsystem is provided for  
38 each laser diode employed within the holographic laser scanner.

39 A further object of the present invention is to provide such a bioptical holographic laser  
40 scanning system, in which an independent signal processing channel is provided for each laser  
41 diode and light collection/detection subsystem in order to improve the signal processing speed of  
42 the system.

1 A further object of the present invention is to provide such a bioptical holographic laser  
2 scanning system, in which a plurality of signal processors are used for simultaneously processing  
3 the scan data signals produced from each of the photodetectors within the holographic laser  
4 scanner.

5 A further object of the present invention is to provide such a bioptical holographic laser  
6 scanning system, in which each facet on the holographic disc has an identification code which is  
7 encoded by the zero-th diffraction order of the outgoing laser beam and detected so as to  
8 determine which scanning planes are to be selectively filtered during the symbol decoding  
9 operations.

10 A further object of the present invention is to provide such a bioptical holographic laser  
11 scanning system, in which the zero-th diffractive order of the laser beam which passes directly  
12 through the respective holographic optical elements on the rotating disc is used to produce a  
13 start/home pulse for use with stitching-type decoding processes carried out within the scanner.

14 These and other objects of the present invention will become apparent hereinafter and in  
15 the Claims to Invention.

#### 16 BRIEF DESCRIPTION OF THE DRAWINGS

17  
18  
19 In order to more fully understand the Objects of the Present Invention, the following  
20 Detailed Description of the Illustrative Embodiments should be read in conjunction with the  
21 accompanying Figure Drawings in which:

22 Fig. 1A1 is a perspective view of the bioptical holographic laser scanning system of the  
23 present invention showing its bottom and side scanning windows formed with its compact  
24 scanner housing;

25 Fig. 1A2 is an elevated side view of the bioptical holographic laser scanning system of  
26 Fig. 1A;

27 Fig. 1B1 is a perspective view of the bioptical holographic laser scanning system of the  
28 present invention shown installed in a Point-Of-Sale (POS) retail environment

29 Fig. 1B2 is an exploded perspective view of the bioptical holographic laser scanning  
30 system of the present invention shown installed in a Point-Of-Sale (POS) retail environment

31 Fig. 1C is a perspective view of the bioptical holographic laser scanning system of the  
32 present invention shown installed above a work surface (e.g. a conveyor belt structure)  
33 employed, for example, in manual sortation operations or the like;

34 Fig. 1D is a perspective view of the bioptical holographic scanning system of the  
35 illustrative embodiment of the present invention, shown with the top panels of its housing  
36 removed in order to reveal the holographic scanning disc mounted on its optical bench, and the  
37 first, second, third and fourth laser scanning stations disposed thereabout, wherein each laser  
38 scanning station comprises a laser beam production module, a set of laser beam folding mirrors,  
39 a light collecting/focusing mirror disposed beneath the scanning disc, a photodetector disposed  
40 above the scanning disc, and pair of analog/digital signal processing boards associated with the  
41 laser scanning station;

1 Fig. 1D2 is a perspective view of a wire-frame graphics model of the bioptical  
2 holographic scanning system of Fig. 1D, wherein the components thereof are shown using wire-  
3 frame modeling and the bottom and side scanning windows are indicated in dotted lines;

4 Fig. 1E is a plane view of the bioptical holographic scanning system shown in Fig. 1D;

5 Fig. 1F is a perspective view of the scanner housing employed in the bioptical  
6 holographic scanning system of Fig. 1E, show with its top cover panels removed therefrom;

7 Fig. 1G is a perspective view of the optical bench employed in the bioptical holographic  
8 scanning system of Fig. 1D;

9 Fig. 1H is a perspective view of the optical bench employed in the bioptical holographic  
10 scanning system of Fig. 1D;

11 Fig. 2A1 is a perspective view of the bioptical holographic scanning system of the  
12 illustrative embodiment of the present invention, shown with its housing removed in order to  
13 reveal the holographic scanning disc rotatably mounted on its optical bench, and the first,  
14 second, third and fourth laser scanning stations disposed thereabout, wherein each laser scanning  
15 station comprises a laser beam production module, a set of laser beam folding mirrors, a light  
16 collecting/focusing mirror disposed beneath the scanning disc, a photodetector disposed above  
17 the scanning disc, and pair of analog/digital signal processing boards associated with the laser  
18 scanning station;

19 Fig. 2A2 is a perspective view of the bioptical holographic scanning system shown in  
20 Fig. 2A1, wherein the components thereof are shown using wire-frame graphics modeling and  
21 the bottom and side scanning windows are indicated in dotted lines;

22 Fig. 2B1 is a plan view of the bioptical holographic scanning system of the illustrative  
23 embodiment shown in Fig. 2A1;

24 Fig. 2B2 is a plan view of graphics the bioptical holographic scanning system shown in  
25 Fig. 2A1, wherein the components thereof are shown using wire-frame graphics modeling and  
26 the bottom and side scanning windows are indicated in dotted lines;

27 Fig. 2C1 is a first elevated side view of the bioptical holographic scanning system of Fig.  
28 2A1, taken along the longitudinally extending reference plane passing through the axis of  
29 rotation of the scanning disc axis and disposed normal to the bottom scanning window indicated  
30 in dotted lines, wherein the components thereof are shown using solid modeling while the side  
31 scanning window is not shown;

32 Fig. 2C2 is a first elevated side view of the bioptical holographic scanning system shown  
33 in Fig. 2C1, wherein the components thereof are shown using wire-frame graphics modeling and  
34 the bottom and side scanning windows are indicated in dotted lines;

35 Fig. 2D1 is a second elevated side view of the bioptical holographic scanning system of  
36 Fig. 2A1, taken along the longitudinally extending reference plane passing through the axis of  
37 rotation of the scanning disc axis and disposed normal to the bottom scanning window indicated  
38 in dotted lines, wherein the components thereof are shown using solid modeling while the side  
39 scanning window is not shown;

40 Fig. 2D2 is a second elevated side view of the bioptical holographic scanning system  
41 shown in Fig. 2D1, wherein the components thereof are shown using wire-frame graphics  
42 modeling and the bottom and side scanning windows are indicated in dotted lines;

1 Fig. 2E1 is a third elevated side view of the bioptical holographic scanning system of Fig.  
2 2A1, taken along the longitudinally extending reference plane passing through the axis of  
3 rotation of the scanning disc axis and disposed normal to the bottom scanning window indicated  
4 in dotted lines, wherein the components thereof are shown using solid modeling while the side  
5 scanning window is not shown;

6 Fig 2E2 is a third elevated side view of the bioptical holographic scanning system shown  
7 in Fig. 2E1, wherein the components thereof are shown using wire-frame graphics modeling and  
8 the bottom and side scanning windows are indicated in dotted lines;

9 Fig. 2F1 is a perspective view of a subassembly from the bioptical holographic scanning  
10 system of the illustrative embodiment, comprising the optical bench of the system, the  
11 holographic scanning disc mounted thereon, the first, second, third and fourth laser beam  
12 production modules mounted about the perimeter of the holographic scanning disc, and the first,  
13 second, third and fourth associated parabolic light collection mirror structures mounted beneath  
14 the holographic scanning disc, adjacent the respective laser beam production modules;

15 Fig. 2F2 is a plan view of the subassembly of Fig. 2F2, showing the subcomponents  
16 thereof using wire-frame modeling;

17 Fig. 2G1 is a perspective view of the laser beam production module employed in each of  
18 the laser scanning stations in the biopticals holographic laser scanning system of Fig. 1A,  
19 wherein the components thereof are shown using solid graphics modeling techniques;

20 Fig. 2G2 is cross-sectional view of the laser beam production module depicted in Fig.  
21 2G1, showing its subcomponents using wire-frame modeling techniques, as well as the  
22 propagation of the laser beam from its visible laser diode source, through its multi-function light  
23 diffractive grating, and reflected off its light reflective mirror, out towards the laser beam  
24 deflecting mirror adjacent the holographic scanning disc;

25 Fig. 2H1 is a perspective view of the laser beam deflection module employed in each of  
26 the laser scanning stations in the biopticals holographic laser scanning system of Fig. 1A,  
27 wherein the components thereof are shown using solid graphics modeling techniques;

28 Fig. 2H2 is a perspective view of the laser beam deflection module employed in each of  
29 the laser scanning stations in the biopticals holographic laser scanning system of Fig. 1A, using  
30 wire-frame graphics modeling techniques to show the spatial location of the subcomponents  
31 thereof within the laser beam reflection module;

32 Fig. 2I1 is an elevated side view of the holographic laser scanning disc and laser scanning  
33 stations associated with the bioptical holographic laser scanning system depicted in Fig. 1A,  
34 using wire-frame modeling techniques to show the position of the photodetector directly above  
35 the point of incidence of the laser beam on each holographic scanning disc in each laser scanning  
36 station thereof;

37 Fig. 2I2 is an elevated side view of the holographic laser scanning disc, a light blocking  
38 element, and laser scanning stations of the bioptical holographic laser scanning system depicted  
39 in Fig. 1A, using wire-frame modeling techniques to show the position of the light blocking  
40 element with respect to the holographic scanning disc, the bottom window, and the  
41 photodetectors in each laser scanning station thereof;

1 Fig. 2I3 is a perspective view of a wire frame model of the holographic laser scanning  
2 disc and light blocking element of Fig. 2I2;

3 Fig. 2J1 is a plan view of the holographic laser scanning disc and laser scanning stations  
4 associated with the bioptical holographic laser scanning system depicted in Fig. 1A, using solid  
5 graphics modeling techniques to show the position of the photodetector directly above the point  
6 of incidence of the laser beam on the holographic scanning disc in each laser scanning station  
7 thereof;

8 Fig. 2J2 is a plan view of the holographic laser scanning disc and laser scanning stations  
9 associated with the bioptical holographic laser scanning system depicted in Fig. 1A, using wire-  
10 frame graphics modeling techniques to show the position of the photodetector directly above the  
11 point of incidence of the laser beam on the holographic scanning disc in each laser scanning  
12 station thereof;

13 Fig. 2K is a perspective view of the first laser scanning station (ST1) in the bioptical  
14 holographic laser scanning system of the present invention, showing solid models of its laser  
15 beam production and direction modules disposed about the edge of the holographic laser  
16 scanning disc, and associated first, second and third groups of laser beam folding mirrors,  
17 wherein the laser beam folding mirrors associated with the first group ( $M_{i,j,k}$  where the group  
18 index  $j$  is  $i=1$ ) cooperate with laser beams generated from scanning facets having high elevation  
19 angle and positive (i.e. left) skew angle characteristics, the laser beam folding mirrors associated  
20 with the second group ( $M_{i,j,k}$  where the group index  $j$  is  $j=2$ ) cooperate with laser beams  
21 generated from scanning facets having high elevation angle and negative (i.e. right) skew angle  
22 characteristics, and the laser beam folding mirrors associated with the first group ( $M_{i,j,k}$  where the  
23 group index  $j$  is  $j=3$ ) cooperate with laser beams generated from scanning facets having low  
24 elevation angle and zero (i.e. no) skew angle characteristics;

25 Fig. 2L is a perspective view of the second laser scanning station (ST2) in the bioptical  
26 holographic laser scanning system of the present invention, showing solid models of its laser  
27 beam production and direction modules disposed about the edge of the holographic laser  
28 scanning disc, and associated group of laser beam folding mirrors, wherein the laser beam  
29 folding mirrors associated the group ( $M_{i,j,k}$  where the group index  $j$  is  $j=3$ ) cooperate with laser  
30 beams generated from scanning facets having low elevation angle and zero (i.e. no) skew angle  
31 characteristics;

32 Fig. 2M is a perspective view of the third laser scanning station (ST3) in the bioptical  
33 holographic laser scanning system of the present invention, showing solid models of its laser  
34 beam production and direction modules disposed about the edge of the holographic laser  
35 scanning disc, and associated first, second and third groups of laser beam folding mirrors,  
36 wherein the laser beam folding mirrors associated with the first group ( $M_{i,j,k}$  where the group  
37 index  $j$  is  $i=1$ ) cooperate with laser beams generated from scanning facets having high elevation  
38 angle and positive (i.e. left) skew angle characteristics, the laser beam folding mirrors associated  
39 with the second group ( $M_{i,j,k}$  where the group index  $j$  is  $j=2$ ) cooperate with laser beams  
40 generated from scanning facets having high elevation angle and negative (i.e. right) skew angle  
41 characteristics, and the laser beam folding mirrors associated with the first group ( $M_{i,j,k}$  where the



group index  $j$  is  $j=3$ ) cooperate with laser beams generated from scanning facets having low elevation angle and zero (i.e. no) skew angle characteristics;

Fig. 2N is an elevated side view of the first and third laser scanning stations (ST1 and ST3) in the bioptical holographic laser scanning system of the present invention, showing solid models of its laser beam production and direction modules disposed about the edge of the holographic laser scanning disc, and associated first, second and third groups of laser beam folding mirrors;

Fig. 2O is a perspective view of the first and third laser scanning stations (ST1 and ST3) in the bioptical holographic laser scanning system of the present invention, showing solid models of its laser beam production and direction modules disposed about the edge of the holographic laser scanning disc, and associated first, second and third groups of laser beam folding mirrors;

Fig. 2P is a perspective view of the fourth laser scanning station (ST4) in the bioptical holographic laser scanning system of the present invention, showing solid models of its laser beam production and direction modules disposed about the edge of the holographic laser scanning disc, and associated first, second and third groups of laser beam folding mirrors, wherein the laser beam folding mirrors associated with the first group ( $M_{i,j,k}$  where the group index  $j$  is  $i=1$ ) cooperate with laser beams generated from scanning facets having high elevation angle and positive (i.e. left) skew angle characteristics, the laser beam folding mirrors associated with the second group ( $M_{i,j,k}$  where the group index  $j$  is  $j=2$ ) cooperate with laser beams generated from scanning facets having high elevation angle and negative (i.e. right) skew angle characteristics, and the laser beam folding mirrors associated with the first group ( $M_{i,j,k}$  where the group index  $j$  is  $j=3$ ) cooperate with laser beams generated from scanning facets having low elevation angle and zero (i.e. no) skew angle characteristics;

Fig. 2Q is an elevated side view of the fourth laser scanning stations (ST4) in the bioptical holographic laser scanning system of the present invention, showing solid models of its laser beam production and direction modules disposed about the edge of the holographic laser scanning disc, and associated first, second and third groups of laser beam folding mirrors;

Fig. 3A1 is a plan view of the holographic scanning disc of the illustrative embodiment of the present invention, showing the boundaries of each  $i$ -th holographic optical facet mounted thereon about its axis of rotation, with the assigned facet number and selected disc design parameters imposed thereon for illustrative purposes;

Fig. 3A2 is a geometrical optics model of the process of producing the  $P(i,j)$ -th laser scanning plane of the system by directing the output laser beam from the  $j$ -th laser beam production module through  $i$ -th holographic scanning facet supported upon the holographic scanning disc as it rotates about its axis, wherein various parameters employed in the model, including diffraction angle, beam elevation angle and scan angle, are schematically defined;

Fig. 3A3 is a plan view of the geometrical optics model of Fig. 3A2, defining the skew angle of the scanning facet, also employed therein;

Fig. 3A4 is a table categorizing the twelve facets on the holographic scanning disc of the illustrative embodiment as either having (i) high elevation angle characteristics and left (i.e. positive) skew angle characteristics, (ii) high elevation angle characteristics and right (i.e.

negative) skew angle characteristics and (iii) low elevation angle characteristics and no (i.e. zero) skew angle characteristics;

Figs. 3B1 and 3B2, taken together, collectively provide a vector-based specification of the vertices of each laser beam folding mirrors employed in the first laser scanning station (ST1) of the bioptical holographic scanning system using position vectors defined with respect to local coordinate reference system  $R_{local\ 1}$  symbolically embedded within the holographic scanning disc, as shown in Fig. 2A1;

Figs. 3C1 through 3C2, taken together, collectively provide a vector-based specification of the vertices of each laser beam folding mirrors employed in the second laser scanning station (ST2) of the bioptical holographic scanning system using position vectors defined with respect to local coordinate reference system  $R_{local\ 2}$  symbolically embedded within the holographic scanning disc, as shown in Fig. 2A1 ;

Figs. 3D1 through 3D2, taken together, collectively provide a vector-based specification of the vertices of each laser beam folding mirrors employed in the third laser scanning station (ST3) of the bioptical holographic scanning system using position vectors defined with respect to local coordinate reference system  $R_{local\ 3}$  symbolically embedded within the holographic scanning disc, as shown in Fig. 2A;

Figs. 3E1 through 3E2, taken together, collectively provide a vector-based specification of the vertices of each laser beam folding mirrors employed in the fourth laser scanning station (ST4) of the bioptical holographic scanning system using position vectors defined with respect to local coordinate reference system  $R_{local\ 4}$  symbolically embedded within the holographic scanning disc, as shown in Fig. 2A1;

Fig. 3F is a table setting forth major physical, optical and electrical parameters which can be used to characterize to the bioptical holographic laser scanning system of the illustrative embodiment of the present invention;

Figs. 3G1 and 3G2, taken collectively, provide a table setting forth various physical and optical parameters characteristic of the holographic laser scanning disc employed in the illustrative embodiment of the bioptical holographic laser scanning system of the present invention;

Fig. 3H provides a table setting forth the holographic exposure/recording angles (i.e. facet construction parameters) for mastering at 488 nanometers the holographic laser scanning disc employed in the illustrative embodiment of the bioptical holographic laser scanning system of the present invention;

Fig. 3I provides a table setting forth the "modified" holographic exposure/recording angles (i.e. facet construction parameters) for mastering at 488 nanometers the holographic laser scanning disc employed in the illustrative embodiment, while correcting/compensating for post-processing residual gelatin swell associated with the holographic recording medium;

Fig. 3J provides a table setting forth parameters used to analyze the focus shift and out-of-focus spot size for a converging laser reference beam;

Fig. 3K is a table setting forth the focal distances of each scanning facet on the holographic scanning disc of the illustrative embodiment of the present invention, as well as

1 optical distances from each facet to the horizontal and vertical windows of the bioptical  
2 holographic scanning system of the illustrative embodiment;

3 Figs. 3L1 and 3L2, taken together, provides a table setting forth CDRH/IEC calculations  
4 which verify that the bioptical holographic laser scanning system of the illustrative embodiment  
5 satisfies Laser Class requirements;

6 Figs. 4A, 4B and 4C set forth a block functional diagram of bioptical holographic laser  
7 scanning system of the illustrative embodiment of the present invention, showing the major  
8 components of the system and their relation to each other;

9 Fig. 5A1 is a perspective view of the bioptical holographic laser scanning system of the  
10 illustrative embodiment of the present invention, schematically illustrating the projection of each  
11 and every  $P(i,j)$ -th laser scanning plane generated within the three-dimensional scanning volume  
12 extending between the bottom and side scanning windows of the system during each complete  
13 revolution of the holographic laser scanning disc, wherein the prespecified depth of focus (DOF)  
14 and laser beam cross-section characteristics of each such laser scanning plane are specified by  
15 the holographic scanning facet generating the laser scanning plane;

16 Fig. 5A2 is an elevated side view of the bioptical holographic laser scanning system of  
17 the illustrative embodiment of the present invention, schematically illustrating the projection of  
18 each and every  $P(i,j)$ -th laser scanning plane generated within the three-dimensional scanning  
19 volume extending between the bottom and side scanning windows of the system during each  
20 complete revolution of the holographic laser scanning disc, wherein the prespecified depth of  
21 focus (DOF) and laser beam cross-section characteristics of each such laser scanning plane are  
22 specified by the holographic scanning facet generating the laser scanning plane;

23 Fig. 5A3 is a plan view of the bioptical holographic laser scanning system of the  
24 illustrative embodiment of the present invention, schematically illustrating the projection of each  
25 and every  $P(i,j)$ -th laser scanning plane generated within the three-dimensional scanning volume  
26 extending between the bottom and side scanning windows of the system during each complete  
27 revolution of the holographic laser scanning disc, wherein the prespecified depth of focus (DOF)  
28 and laser beam cross-section characteristics of each such laser scanning plane are specified by  
29 the holographic scanning facet generating the laser scanning plane;

30 Fig. 5A4 is an elevated side end view of the bioptical holographic laser scanning system  
31 of the illustrative embodiment of the present invention, schematically illustrating the projection  
32 of each and every  $P(i,j)$ -th laser scanning plane generated within the three-dimensional scanning  
33 volume extending between the bottom and side scanning windows of the system during each  
34 complete revolution of the holographic laser scanning disc, wherein the prespecified depth of  
35 focus (DOF) and laser beam cross-section characteristics of each such laser scanning plane are  
36 specified by the holographic scanning facet generating the laser scanning plane;

37 Fig. 5B1 is a perspective view of the bioptical holographic laser scanning system of the  
38 illustrative embodiment of the present invention, schematically illustrating the projection of  
39 substantially vertically-disposed laser scanning planes through the bottom scanning window for  
40 reading horizontally-oriented (i.e. ladder-type) bar code symbols, when scanning facets (Nos. 7,  
41 9 and 11) having high elevation angle characteristics and left (i.e. positive) skew angle  
42 characteristics pass through the first laser scanning station (ST1) and generate laser scanning

1 beams that reflect off the first group of beam folding mirrors (MG1@ST1) associated therewith  
2 during system operation;

3 Fig. 5B2 is a side view of the bioptical holographic laser scanning system of the  
4 illustrative embodiment of the present invention, schematically illustrating the projection of  
5 substantially vertically-disposed laser scanning planes through the bottom scanning window for  
6 reading horizontally-oriented (i.e. ladder-type) bar code symbols, when scanning facets (Nos. 7,  
7 9 and 11) having high elevation angle characteristics and left (i.e. positive) skew angle  
8 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
9 beams that reflect off the first group of beam folding mirrors (MG1@ST1) associated therewith  
10 during system operation;

11 Fig. 5B3 is a plan view of the bioptical holographic laser scanning system of the  
12 illustrative embodiment of the present invention, schematically illustrating the projection of  
13 substantially vertically-disposed laser scanning planes through the bottom scanning window for  
14 reading horizontally-oriented (i.e. ladder-type) bar code symbols, when scanning facets (Nos. 7,  
15 9 and 11) having high elevation angle characteristics and left (i.e. positive) skew angle  
16 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
17 beams that reflect off the first group of beam folding mirrors (MG1@ST1) associated therewith  
18 during system operation;

19 Fig. 5B4 is an elevated end view of the bioptical holographic laser scanning system of the  
20 illustrative embodiment of the present invention, schematically illustrating the projection of  
21 substantially vertically-disposed laser scanning planes through the bottom scanning window for  
22 reading horizontally-oriented (i.e. ladder-type) bar code symbols, when scanning facets (Nos. 7,  
23 9 and 11) having high elevation angle characteristics and left (i.e. positive) skew angle  
24 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
25 beams that reflect off the first group of beam folding mirrors (MG1@ST1) associated therewith  
26 during system operation;

27 Fig. 5C1 is a perspective view of a wire-frame model of the laser scanning platform  
28 within the bioptical holographic laser scanning system of the illustrative embodiment,  
29 schematically illustrating the projection of substantially vertically-disposed laser scanning planes  
30 through the bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code  
31 symbols, when scanning facets (Nos. 7, 9 and 11) having high elevation angle characteristics and  
32 left (i.e. positive) skew angle characteristics pass through the first laser scanning station (ST1)  
33 and generate laser scanning beams that reflect off the first group of beam folding mirrors  
34 (MG1@ST1) associated therewith during system operation;

35 Fig. 5C2 is a plan view of a wire-frame model of the laser scanning platform within the  
36 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
37 illustrating the projection of substantially vertically-disposed laser scanning planes through the  
38 bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code symbols,  
39 when scanning facets (Nos. 7, 9 and 11) having high elevation angle characteristics and left (i.e.  
40 positive) skew angle characteristics pass through the first laser scanning station (ST1) and  
41 generate laser scanning beams that reflect off the first group of beam folding mirrors  
42 (MG1@ST1) associated therewith during system operation;

1 Fig. 5C3 is an elevated end view of a wire-frame model of the laser scanning platform  
2 within the bioptical holographic laser scanning system of the illustrative embodiment,  
3 schematically illustrating the projection of substantially vertically-disposed laser scanning planes  
4 through the bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code  
5 symbols, when scanning facets (Nos. 7, 9 and 11) having high elevation angle characteristics and  
6 left (i.e. positive) skew angle characteristics pass through the first laser scanning station (ST1)  
7 and generate laser scanning beams that reflect off the first group of beam folding mirrors  
8 (MG1@ST1) associated therewith during system operation;

9 Fig. 5C4 is a first elevated side view of a wire-frame model of the laser scanning  
10 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
11 schematically illustrating the projection of substantially vertically-disposed laser scanning planes  
12 through the bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code  
13 symbols, when scanning facets (Nos. 7, 9 and 11) having high elevation angle characteristics and  
14 left (i.e. positive) skew angle characteristics pass through the first laser scanning station (ST1)  
15 and generate laser scanning beams that reflect off the first group of beam folding mirrors  
16 (MG1@ST1) associated therewith during system operation;

17 Fig. 5C5 is a second elevated side view of a wire-frame model of the laser scanning  
18 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
19 schematically illustrating the projection of substantially vertically-disposed laser scanning planes  
20 through the bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code  
21 symbols, when scanning facets (Nos. 7, 9 and 11) having high elevation angle characteristics  
22 and left (i.e. positive) skew angle characteristics pass through the first laser scanning station  
23 (ST1) and generate laser scanning beams that reflect off the first group of beam folding mirrors  
24 (MG1@ST1) associated therewith during system operation;

25 Fig. 5D1 is a perspective view of the bioptical holographic laser scanning system of the  
26 illustrative embodiment of the present invention, schematically illustrating the projection of  
27 substantially vertically-disposed laser scanning planes through the bottom scanning window for  
28 reading horizontally-oriented (i.e. ladder-type) bar code symbols, when scanning facets (Nos. 8,  
29 10 and 12) having high elevation angle characteristics and right (i.e. negative) skew angle  
30 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
31 beams that reflect off the second group of beam folding mirrors (MG2@ST1) associated  
32 therewith during system operation;

33 Fig. 5D2 is a side view of the bioptical holographic laser scanning system of the  
34 illustrative embodiment of the present invention, schematically illustrating the projection of  
35 substantially vertically-disposed laser scanning planes through the bottom scanning window for  
36 reading horizontally-oriented (i.e. ladder-type) bar code symbols, when scanning facets (Nos. 8,  
37 10 and 12) having high elevation angle characteristics and right (i.e. negative) skew angle  
38 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
39 beams that reflect off the second group of beam folding mirrors (MG2@ST1) associated  
40 therewith during system operation;

41 Fig. 5D3 is a plan view of the bioptical holographic laser scanning system of the  
42 illustrative embodiment of the present invention, schematically illustrating the projection of

1 substantially vertically-disposed laser scanning planes through the bottom scanning window for  
2 reading horizontally-oriented (i.e. ladder-type) bar code symbols, when scanning facets (Nos. 8,  
3 10 and 12) having high elevation angle characteristics and right (i.e. negative) skew angle  
4 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
5 beams that reflect off the second group of beam folding mirrors (MG2@ST1) associated  
6 therewith during system operation;

7 Fig. 5D4 is an elevated end view of the bioptical holographic laser scanning system of the  
8 illustrative embodiment of the present invention, schematically illustrating the projection of  
9 substantially vertically-disposed laser scanning planes through the bottom scanning window for  
10 reading horizontally-oriented (i.e. ladder-type) bar code symbols, when scanning facets (Nos. 8,  
11 10 and 12) having high elevation angle characteristics and right (i.e. negative) skew angle  
12 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
13 beams that reflect off the second group of beam folding mirrors (MG2@ST1) associated  
14 therewith during system operation;

15 Fig. 5E1 is a perspective view of a wire-frame model of the laser scanning platform  
16 within the bioptical holographic laser scanning system of the illustrative embodiment,  
17 schematically illustrating the projection of substantially vertically-disposed laser scanning planes  
18 through the bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code  
19 symbols, when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics  
20 and right (i.e. negative) skew angle characteristics pass through the first laser scanning station  
21 (ST1) and generate laser scanning beams that reflect off the second group of beam folding  
22 mirrors (MG2@ST1) associated therewith during system operation;

23 Fig. 5E2 is a plan view of a wire-frame model of the laser scanning platform within the  
24 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
25 illustrating the projection of substantially vertically-disposed laser scanning planes through the  
26 bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code symbols,  
27 when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics and right  
28 (i.e. negative) skew angle characteristics pass through the first laser scanning station (ST1) and  
29 generate laser scanning beams that reflect off the second group of beam folding mirrors  
30 (MG2@ST1) associated therewith during system operation;

31 Fig. 5E3 is an elevated end view of a wire-frame model of the laser scanning platform  
32 within the bioptical holographic laser scanning system of the illustrative embodiment,  
33 schematically illustrating the projection of substantially vertically-disposed laser scanning planes  
34 through the bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code  
35 symbols, when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics  
36 and right (i.e. negative) skew angle characteristics pass through the first laser scanning station  
37 (ST1) and generate laser scanning beams that reflect off the second group of beam folding  
38 mirrors (MG2@ST1) associated therewith during system operation;

39 Fig. 5E4 is a first elevated side view of a wire-frame model of the laser scanning platform  
40 within the bioptical holographic laser scanning system of the illustrative embodiment,  
41 schematically illustrating the projection of substantially vertically-disposed laser scanning planes  
42 through the bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code

1 symbols, when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics  
2 and right (i.e. negative) skew angle characteristics pass through the first laser scanning station  
3 (ST1) and generate laser scanning beams that reflect off the second group of beam folding  
4 mirrors (MG2@ST1) associated therewith during system operation;

5 Fig. 5E5 is a second elevated side view of a wire-frame model of the laser scanning  
6 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
7 schematically illustrating the projection of substantially vertically-disposed laser scanning planes  
8 through the bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code  
9 symbols, when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics  
10 and right (i.e. negative) skew angle characteristics pass through the first laser scanning station  
11 (ST1) and generate laser scanning beams that reflect off the second group of beam folding  
12 mirrors (MG2@ST1) associated therewith during system operation;

13 Fig. 5F1 is a perspective view of the bioptical holographic laser scanning system of the  
14 illustrative embodiment of the present invention, schematically illustrating the projection of  
15 substantially horizontally-disposed laser scanning planes through the bottom scanning window  
16 for reading vertically-oriented (i.e. picket-fence type) bar code symbols, when scanning facets  
17 (Nos. 1 through 4) having low elevation angle characteristics and no (i.e. zero) skew angle  
18 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
19 beams that reflect off the third group of beam folding mirrors (MG3@ST1) associated therewith  
20 during system operation;

21 Fig. 5F2 is a plan view of the bioptical holographic laser scanning system of the  
22 illustrative embodiment of the present invention, schematically illustrating the projection of  
23 substantially horizontally-disposed laser scanning planes through the bottom scanning window  
24 for reading vertically-oriented (i.e. picket-fence -type) bar code symbols, when scanning facets  
25 (Nos. 1 through 4) having low elevation angle characteristics and no (i.e. zero) skew angle  
26 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
27 beams that reflect off the third group of beam folding mirrors (MG3@ST1) associated therewith  
28 during system operation;

29 Fig. 5F3 is an end view of the bioptical holographic laser scanning system of the  
30 illustrative embodiment of the present invention, schematically illustrating the projection of  
31 substantially horizontally-disposed laser scanning planes through the bottom scanning window  
32 for reading vertically-oriented (i.e. picket-fence type) bar code symbols, when scanning facets  
33 (Nos. 1 through 4) having low elevation angle characteristics and no (i.e. zero) skew angle  
34 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
35 beams that reflect off the third group of beam folding mirrors (MG3@ST1) associated therewith  
36 during system operation;

37 Fig. 5F4 is a first side view of the bioptical holographic laser scanning system of the  
38 illustrative embodiment of the present invention, schematically illustrating the projection of  
39 substantially horizontally-disposed laser scanning planes through the bottom scanning window  
40 for reading vertically-oriented (i.e. picket-fence type) bar code symbols, when scanning facets  
41 having low elevation angle characteristics and no (i.e. zero) skew angle characteristics pass  
42 through the first laser scanning station (ST1) and generate laser scanning beams that reflect off

1 the third group of beam folding mirrors (MG3@ST1) associated therewith during system  
2 operation;

3 Fig. 5F5 is a second side view of the bioptical holographic laser scanning system of the  
4 illustrative embodiment of the present invention, schematically illustrating the projection of  
5 substantially horizontally-disposed laser scanning planes through the bottom scanning window  
6 for reading vertically-oriented (i.e. picket-fence type) bar code symbols, when scanning facets  
7 (Nos. 1 through 4) having low elevation angle characteristics and no (i.e. zero) skew angle  
8 characteristics pass through the first laser scanning station (ST1) and generate laser scanning  
9 beams that reflect off the third group of beam folding mirrors (MG3@ST1) associated therewith  
10 during system operation;

11 Fig. 5G1 is a perspective view of a wire-frame model of the laser scanning platform  
12 within the bioptical holographic laser scanning system of the illustrative embodiment,  
13 schematically illustrating the projection of substantially horizontally disposed laser scanning  
14 planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence  
15 type) bar code symbols, when scanning facets (Nos. 1-4) pass through the first laser scanning  
16 station (ST1) and generate laser scanning beams that reflect off the third group of beam folding  
17 mirrors (MG3@ST1) associated therewith during system operation;

18 Fig. 5G2 is a plan view of a wire-frame model of the laser scanning platform within the  
19 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
20 illustrating the projection of substantially horizontally disposed laser scanning planes through the  
21 bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code  
22 symbols, when scanning facets (Nos. 1-4) pass through the first laser scanning station (ST1) and  
23 generate laser scanning beams that reflect off the third group of beam folding mirrors  
24 (MG3@ST1) associated therewith during system operation;

25 Fig. 5G3 is an elevated end view of a wire-frame model of the laser scanning platform  
26 within the bioptical holographic laser scanning system of the illustrative embodiment,  
27 schematically illustrating the projection of substantially horizontally disposed laser scanning  
28 planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence  
29 type) bar code symbols, when scanning facets (Nos. 1-4) pass through the first laser scanning  
30 station (ST1) and generate laser scanning beams that reflect off the third group of beam folding  
31 mirrors (MG3@ST1) associated therewith during system operation;

32 Fig. 5G4 is a first elevated side view of a wire-frame model of the laser scanning  
33 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
34 schematically illustrating the projection of substantially horizontally disposed laser scanning  
35 planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence  
36 type) bar code symbols, when scanning facets (Nos. 1-4) pass through the first laser scanning  
37 station (ST1) and generate laser scanning beams that reflect off the third group of beam folding  
38 mirrors (MG3@ST1) associated therewith during system operation;

39 Fig. 5G5 is a second elevated side view of a wire-frame model of the laser scanning  
40 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
41 schematically illustrating the projection of substantially horizontally disposed laser scanning  
42 planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence



1 type) bar code symbols, when scanning facets (Nos. 1-4) pass through the first laser scanning  
2 station (ST1) and generate laser scanning beams that reflect off the third group of beam folding  
3 mirrors (MG3@ST1) associated therewith during system operation;

4 Fig. 5H1 is a perspective view of a wire-frame model of the laser scanning platform  
5 within the bioptical holographic laser scanning system of the illustrative embodiment,  
6 schematically illustrating the projection of both substantially horizontally and vertically disposed  
7 laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e.  
8 picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code  
9 symbols, respectively, when scanning facets (Nos. 1-4 and 7-12) pass through the first laser  
10 scanning station (ST1) and generate laser scanning beams that reflect off the first, second and  
11 third groups of beam folding mirrors (MG1@ST1, MG2@ST1 and MG3@ST1) associated  
12 therewith during system operation;

13 Fig. 5H2 is a plan view of a wire-frame model of the laser scanning platform within the  
14 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
15 illustrating the projection of both substantially horizontally and vertically disposed laser  
16 scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-  
17 fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols,  
18 respectively, when scanning facets (Nos. 1-4 and 7-12) pass through the first laser scanning  
19 station (ST1) and generate laser scanning beams that reflect off the first, second and third groups  
20 of beam folding mirrors (MG1@ST1, MG2@ST1 and MG3@ST1) associated therewith during  
21 system operation;

22 Fig. 5H3 is an elevated end view of a wire-frame model of the laser scanning platform  
23 within the bioptical holographic laser scanning system of the illustrative embodiment,  
24 schematically illustrating the projection of both substantially horizontally and vertically disposed  
25 laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e.  
26 picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code  
27 symbols, respectively, when scanning facets (Nos. 1-4 and 7-12) pass through the first laser  
28 scanning station (ST1) and generate laser scanning beams that reflect off the first, second and  
29 third groups of beam folding mirrors (MG1@ST1, MG2@ST1 and MG3@ST1) associated  
30 therewith during system operation;

31 Fig. 5H4 is a first elevated side view of a wire-frame model of the laser scanning  
32 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
33 schematically illustrating the projection of both substantially horizontally and vertically disposed  
34 laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e.  
35 picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code  
36 symbols, respectively, when scanning facets (Nos. 1-4 and 7-12) pass through the first laser  
37 scanning station (ST1) and generate laser scanning beams that reflect off the first, second and  
38 third groups of beam folding mirrors (MG1@ST1, MG2@ST1 and MG@ST1) associated  
39 therewith during system operation;

40 Fig. 5H5 is a second elevated side view of a wire-frame model of the laser scanning  
41 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
42 schematically illustrating the projection of both substantially horizontally and vertically disposed

1 laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e.  
2 picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code  
3 symbols, respectively, when scanning facets (Nos. 1-4 and 7-12) pass through the first laser  
4 scanning station (ST1) and generate laser scanning beams that reflect off the first, second and  
5 third groups of beam folding mirrors (MG1@ST1, MG2@ST1 and MG3@ST1) associated  
6 therewith during system operation;

7 Fig. 5H6 is a perspective view of the bioptical holographic laser scanning system of the  
8 illustrative embodiment of the present invention, schematically illustrating the projection of both  
9 substantially horizontally and vertically disposed laser scanning planes through the bottom  
10 scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
11 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
12 (Nos. 1-4 and 7-12) pass through the first laser scanning station (ST1) and generate laser  
13 scanning beams that reflect off the first, second and third groups of beam folding mirrors  
14 (MG1@ST1, MG2@ST1 and MG3@ST1) associated therewith during system operation;

15 Fig. 5H7 is a plan view of the bioptical holographic laser scanning system of the  
16 illustrative embodiment of the present invention, schematically illustrating the projection of both  
17 substantially horizontally and vertically disposed laser scanning planes through the bottom  
18 scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
19 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
20 (Nos. 1-4 and 7-12) pass through the first laser scanning station (ST1) and generate laser  
21 scanning beams that reflect off the first, second and third groups of beam folding mirrors  
22 (MG1@ST1, MG2@ST1 and MG3@ST1) associated therewith during system operation;

23 Fig. 5H8 is an elevated end view of the bioptical holographic laser scanning system of the  
24 illustrative embodiment of the present invention, schematically illustrating the projection of both  
25 substantially horizontally and vertically disposed laser scanning planes through the bottom  
26 scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
27 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
28 (Nos. 1-4 and 7-12) disc pass through the first laser scanning station (ST1) and generate laser  
29 scanning beams that reflect off the first, second and third groups of beam folding mirrors  
30 (MG1@ST1, MG2@ST1 and MG3@ST1) associated therewith during system operation;

31 Fig. 5H9 is a first elevated side view of the bioptical holographic laser scanning system  
32 of the illustrative embodiment of the present invention, schematically illustrating the projection  
33 of both substantially horizontally and vertically disposed laser scanning planes through the  
34 bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols  
35 and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
36 (Nos. 1-4 and 7-12) disc pass through the first laser scanning station (ST1) and generate laser  
37 scanning beams that reflect off the first, second and third groups of beam folding mirrors  
38 (MG1@ST1, MG2@ST1 and MG3@ST1) associated therewith during system operation;

39 Fig. 5H10 is a second elevated side view of the bioptical holographic laser scanning  
40 system of the illustrative embodiment of the present invention, schematically illustrating the  
41 projection of both substantially horizontally and vertically disposed laser scanning planes  
42 through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar

code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets (Nos. 1-4 and 7-12) disc pass through the first laser scanning station (ST1) and generate laser scanning beams that reflect off the first, second and third groups of beam folding mirrors (MG1@ST1, MG2@ST1 and MG3@ST1) associated therewith during system operation;

Fig. 5I1 is a perspective view of a wire-frame model of the laser scanning platform within the bioptical holographic laser scanning system of the illustrative embodiment, schematically illustrating the projection of substantially horizontally disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics pass through the second laser scanning station (ST2) and generate laser scanning beams that reflect off the group of beam folding mirrors (MG3@ST2) associated therewith during system operation;

Fig. 5I2 is a plan view of a wire-frame model of the laser scanning platform within the bioptical holographic laser scanning system of the illustrative embodiment, schematically illustrating the projection of substantially horizontally disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics pass through the second laser scanning station (ST2) and generate laser scanning beams that reflect off the group of beam folding mirrors (MG3@ST2) associated therewith during system operation;

Fig. 5I3 is an elevated end view of a wire-frame model of the laser scanning platform within the bioptical holographic laser scanning system of the illustrative embodiment, schematically illustrating the projection of substantially horizontally disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics pass through the second laser scanning station (ST2) and generate laser scanning beams that reflect off the group of beam folding mirrors (MG3@ST2) associated therewith during system operation;

Fig. 5I4 is a first elevated side view of a wire-frame model of the laser scanning platform within the bioptical holographic laser scanning system of the illustrative embodiment, schematically illustrating the projection of substantially horizontally disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics pass through the second laser scanning station (ST2) and generate laser scanning beams that reflect off the group of beam folding mirrors (MG3@ST2) associated therewith during system operation;

Fig. 5I5 is a second elevated side view of a wire-frame model of the laser scanning platform within the bioptical holographic laser scanning system of the illustrative embodiment, schematically illustrating the projection of substantially horizontally disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics pass through the second laser

1 scanning station (ST2) and generate laser scanning beams that reflect off the group of beam  
2 folding mirrors (MG3@ST2) associated therewith during system operation;

3 Fig. 5J1 is a perspective view of the bioptical holographic laser scanning system of the  
4 illustrative embodiment of the present invention, schematically illustrating the projection of  
5 substantially horizontally disposed laser scanning planes through the bottom scanning window  
6 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
7 (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle  
8 characteristics pass through the second laser scanning station (ST2) and generate laser scanning  
9 beams that reflect off the group of beam folding mirrors (MG3@ST2) associated therewith  
10 during system operation;

11 Fig. 5J2 is a side view of the bioptical holographic laser scanning system of the  
12 illustrative embodiment of the present invention, schematically illustrating the projection of  
13 substantially horizontally disposed laser scanning planes through the bottom scanning window  
14 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
15 (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle  
16 characteristics pass through the second laser scanning station (ST2) and generate laser scanning  
17 beams that reflect off the group of beam folding mirrors (MG3@ST2) associated therewith  
18 during system operation;

19 Fig. 5J3 is a plan view of the bioptical holographic laser scanning system of the  
20 illustrative embodiment of the present invention, schematically illustrating the projection of  
21 substantially horizontally disposed laser scanning planes through the bottom scanning window  
22 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
23 (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle  
24 characteristics pass through the second laser scanning station (ST2) and generate laser scanning  
25 beams that reflect off the group of beam folding mirrors (MG3@ST2) associated therewith  
26 during system operation;

27 Fig. 5J4 is a first elevated end view of the bioptical holographic laser scanning system of  
28 the illustrative embodiment of the present invention, schematically illustrating the projection of  
29 substantially horizontally disposed laser scanning planes through the bottom scanning window  
30 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
31 (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle  
32 characteristics pass through the second laser scanning station (ST2) and generate laser scanning  
33 beams that reflect off the group of beam folding mirrors (MG3@ST2) associated therewith  
34 during system operation ;

35 Fig. 5J5 is a second elevated end view of the bioptical holographic laser scanning system  
36 of the illustrative embodiment of the present invention, schematically illustrating the projection  
37 of substantially horizontally disposed laser scanning planes through the bottom scanning window  
38 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
39 (Nos. 1 through 6) having low elevation angle characteristics and no (i.e. zero) skew angle  
40 characteristics pass through the second laser scanning station (ST2) and generate laser scanning  
41 beams that reflect off the group of beam folding mirrors (MG3@ST2) associated therewith  
42 during system operation;

1 Fig. 5K1 is a perspective view of a wire-frame model of the laser scanning platform  
2 within the bioptical holographic laser scanning system of the illustrative embodiment,  
3 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
4 through the bottom scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
5 symbols when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics  
6 and right (i.e. negative) skew angle characteristics pass through the third laser scanning station  
7 (ST3) and generate laser scanning beams that reflect off the first group of beam folding mirrors  
8 (MG1@ST3) associated therewith during system operation;

9 Fig. 5K2 is a plan view of a wire-frame model of the laser scanning platform within the  
10 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
11 illustrating the projection of substantially vertically disposed laser scanning planes through the  
12 bottom scanning window for reading horizontally-oriented (i.e. ladder type) bar code symbols  
13 when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics and right  
14 (i.e. negative) skew angle characteristics pass through the third laser scanning station (ST3) and  
15 generate laser scanning beams that reflect off the first group of beam folding mirrors  
16 (MG1@ST3) associated therewith during system operation;

17 Fig. 5K3 is an elevated end view of a wire-frame model of the laser scanning platform  
18 within the bioptical holographic laser scanning system of the illustrative embodiment,  
19 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
20 through the bottom scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
21 symbols when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics  
22 and right (i.e. negative) skew angle characteristics pass through the third laser scanning station  
23 (ST3) and generate laser scanning beams that reflect off the first group of beam folding mirrors  
24 (MG1@ST3) associated therewith during system operation;

25 Fig. 5K4 is a first elevated side view of a wire-frame model of the laser scanning  
26 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
27 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
28 through the bottom scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
29 symbols when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics  
30 and right (i.e. negative) skew angle characteristics pass through the third laser scanning station  
31 (ST3) and generate laser scanning beams that reflect off the first group of beam folding mirrors  
32 (MG1@ST3) associated therewith during system operation;

33 Fig. 5K5 is a second elevated side view of a wire-frame model of the laser scanning  
34 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
35 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
36 through the bottom scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
37 symbols when scanning facets (Nos. 8, 10 and 12) having high elevation angle characteristics  
38 and right (i.e. negative) skew angle characteristics pass through the third laser scanning station  
39 (ST3) and generate laser scanning beams that reflect off the first group of beam folding mirrors  
40 (MG1@ST3) associated therewith during system operation;

41 Fig. 5L1 is a perspective view of the bioptical holographic laser scanning system of the  
42 illustrative embodiment of the present invention, schematically illustrating the projection of

1 substantially vertically disposed laser scanning planes through the bottom scanning window for  
2 reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning facets (Nos. 8,  
3 10 and 12) having high elevation angle characteristics and right (i.e. negative) skew angle  
4 characteristics pass through the third laser scanning station (ST3) and generate laser scanning  
5 beams that reflect off the first group of beam folding mirrors (MG1@ST3) associated therewith  
6 during system operation;

7 Fig. 5L2 is a plan view of the bioptical holographic laser scanning system of the  
8 illustrative embodiment of the present invention, schematically illustrating the projection of  
9 substantially vertically disposed laser scanning planes through the bottom scanning window for  
10 reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning facets (Nos. 8,  
11 10 and 12) having high elevation angle characteristics and right (i.e. negative) skew angle  
12 characteristics pass through the third laser scanning station (ST3) and generate laser scanning  
13 beams that reflect off the group of beam folding mirrors (MG1@ST3) associated therewith  
14 during system operation;

15 Fig. 5L3 is an end view of the bioptical holographic laser scanning system of the  
16 illustrative embodiment of the present invention, schematically illustrating the projection of  
17 substantially vertically disposed laser scanning planes through the bottom scanning window for  
18 reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning facets (Nos. 8,  
19 10 and 12) having high elevation angle characteristics and right (i.e. negative) skew angle  
20 characteristics pass through the third laser scanning station (ST3) and generate laser scanning  
21 beams that reflect off the first group of beam folding mirrors (MG1@ST3) associated therewith  
22 during system operation;

23 Fig. 5L4 is a first side view of the bioptical holographic laser scanning system of the  
24 illustrative embodiment of the present invention, schematically illustrating the projection of  
25 substantially vertically disposed laser scanning planes through the bottom scanning window for  
26 reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning facets (Nos. 8,  
27 10 and 12) having high elevation angle characteristics and right (i.e. negative) skew angle  
28 characteristics pass through the third laser scanning station (ST3) and generate laser scanning  
29 beams that reflect off the group of beam folding mirrors (MG1@ST3) associated therewith  
30 during system operation;

31 Fig. 5L5 is a second side view of the bioptical holographic laser scanning system of the  
32 illustrative embodiment of the present invention, schematically illustrating the projection of  
33 substantially vertically disposed laser scanning planes through the bottom scanning window for  
34 reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning facets (Nos. 8,  
35 10 and 12) having high elevation angle characteristics and right (i.e. negative) skew angle  
36 characteristics pass through the third laser scanning station (ST3) and generate laser scanning  
37 beams that reflect off the first group of beam folding mirrors (MG1@ST3) associated therewith  
38 during system operation;

39 Fig. 5M1 is a perspective view of a wire-frame model of the laser scanning platform  
40 within the bioptical holographic laser scanning system of the illustrative embodiment,  
41 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
42 through the bottom scanning window for reading horizontally-oriented (i.e. ladder type) bar code

1 symbols when scanning facets (Nos. 7, 9 and 11) having high elevation angle characteristics and  
2 left (i.e. positive) skew angle characteristics pass through the third laser scanning station (ST3)  
3 and generate laser scanning beams that reflect off the second group of beam folding mirrors  
4 (MG2@ST3) associated therewith during system operation;

5 Fig. 5M2 is a plan view of a wire-frame model of the laser scanning platform within the  
6 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
7 illustrating the projection of substantially vertically disposed laser scanning planes through the  
8 bottom scanning window for reading horizontally-oriented (i.e. ladder type) bar code symbols  
9 when scanning facets (Nos. 7, 9 and 11) having high elevation angle characteristics and left (i.e.  
10 positive) skew angle characteristics pass through the third laser scanning station (ST3) and  
11 generate laser scanning beams that reflect off the second group of beam folding mirrors  
12 (MG2@ST3) associated therewith during system operation;

13 Fig. 5M3 is an elevated end view of a wire-frame model of the laser scanning platform  
14 within the bioptical holographic laser scanning system of the illustrative embodiment,  
15 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
16 through the bottom scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
17 symbols when scanning facets (Nos. 7, 9 and 11) having high elevation angle characteristics and  
18 left (i.e. positive) skew angle characteristics pass through the third laser scanning station (ST3)  
19 and generate laser scanning beams that reflect off the second group of beam folding mirrors  
20 (MG2@ST3) associated therewith during system operation;

21 Fig. 5M4 is a first elevated side view of a wire-frame model of the laser scanning  
22 platform within the bioptical holographic laser scanning system of the illustrative embodiment;

23 Fig. 5M5 is a second elevated side view of a wire-frame model of the laser scanning  
24 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
25 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
26 through the bottom scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
27 symbols when scanning facets (Nos. 7, 9 and 11) having high elevation angle characteristics and  
28 left (i.e. positive) skew angle characteristics pass through the third laser scanning station (ST3)  
29 and generate laser scanning beams that reflect off the second group of beam folding mirrors  
30 (MG2@ST3) associated therewith during system operation;

31 Fig. 5N1 is a perspective view of the bioptical holographic laser scanning system of the  
32 illustrative embodiment of the present invention, schematically illustrating the projection of  
33 substantially vertically disposed laser scanning planes through the bottom scanning window for  
34 reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning facets (Nos. 7, 9  
35 and 11) having high elevation angle characteristics and left (i.e. positive) skew angle  
36 characteristics pass through the third laser scanning station (ST3) and generate laser scanning  
37 beams that reflect off the second group of beam folding mirrors (MG2@ST3) associated  
38 therewith during system operation;

39 Fig. 5N2 is a plan view of the bioptical holographic laser scanning system of the  
40 illustrative embodiment of the present invention, schematically illustrating the projection of  
41 substantially vertically disposed laser scanning planes through the bottom scanning window for  
42 reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning facets (Nos. 7, 9

1 and 11) having high elevation angle characteristics and left (i.e. positive) skew angle  
2 characteristics pass through the third laser scanning station (ST3) and generate laser scanning  
3 beams that reflect off the second group of beam folding mirrors (MG2@ST3) associated  
4 therewith during system operation;

5 Fig. 5N3 is an elevated end view of the bioptical holographic laser scanning system of the  
6 illustrative embodiment of the present invention, schematically illustrating the projection of  
7 substantially vertically disposed laser scanning planes through the bottom scanning window for  
8 reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning facets (Nos. 7, 9  
9 and 11) having high elevation angle characteristics and left (i.e. positive) skew angle  
10 characteristics pass through the third laser scanning station (ST3) and generate laser scanning  
11 beams that reflect off the second group of beam folding mirrors (MG2@ST3) associated  
12 therewith during system operation;

13 Fig. 5N4 is a first elevated side view of the bioptical holographic laser scanning system  
14 of the illustrative embodiment of the present invention, schematically illustrating the projection  
15 of substantially vertically disposed laser scanning planes through the bottom scanning window  
16 for reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning facets (Nos.  
17 7, 9 and 11) having high elevation angle characteristics and left (i.e. positive) skew angle  
18 characteristics pass through the third laser scanning station (ST3) and generate laser scanning  
19 beams that reflect off the second group of beam folding mirrors (MG2@ST3) associated  
20 therewith during system operation;

21 Fig. 5N5 is a second elevated side view of the bioptical holographic laser scanning  
22 system of the illustrative embodiment of the present invention, schematically illustrating the  
23 projection of substantially vertically disposed laser scanning planes through the bottom scanning  
24 window for reading horizontally-oriented (i.e. ladder type) bar code symbols when scanning  
25 facets (Nos. 7, 9 and 11) having high elevation angle characteristics and left (i.e. positive) skew  
26 angle characteristics pass through the third laser scanning station (ST3) and generate laser  
27 scanning beams that reflect off the second group of beam folding mirrors (MG2@ST3)  
28 associated therewith during system operation;

29 Fig. 5O1 is a perspective view of a wire-frame model of the laser scanning platform  
30 within the bioptical holographic laser scanning system of the illustrative embodiment,  
31 schematically illustrating the projection of substantially horizontally disposed laser scanning  
32 planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence  
33 type) bar code symbols when scanning facets (Nos. 1-4) having low elevation angle  
34 characteristics and no (i.e. zero) skew angle characteristics pass through the third laser scanning  
35 station (ST3) and generate laser scanning beams that reflect off the third group of beam folding  
36 mirrors (MG3@ST3) associated therewith during system operation;

37 Fig. 5O2 is a plan view of a wire-frame model of the laser scanning platform within the  
38 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
39 illustrating the projection of substantially horizontally disposed laser scanning planes through the  
40 bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols  
41 when scanning facets (Nos. 1-4) having low elevation angle characteristics and no (i.e. zero)  
42 skew angle characteristics pass through the third laser scanning station (ST3) and generate laser



1 scanning beams that reflect off the third group of beam folding mirrors (MG3@ST3) associated  
2 therewith during system operation;

3 Fig. 5O3 is an elevated end view of a wire-frame model of the laser scanning platform  
4 within the bioptical holographic laser scanning system of the illustrative embodiment,  
5 schematically illustrating the projection of substantially horizontally disposed laser scanning  
6 planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence  
7 type) bar code symbols when scanning facets (Nos. 1-4) having low elevation angle  
8 characteristics and no (i.e. zero) skew angle characteristics pass through the third laser scanning  
9 station (ST3) and generate laser scanning beams that reflect off the third group of beam folding  
10 mirrors (MG3@ST3) associated therewith during system operation;

11 Fig. 5O4 is a first elevated side view of a wire-frame model of the laser scanning  
12 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
13 schematically illustrating the projection of substantially horizontally disposed laser scanning  
14 planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence  
15 type) bar code symbols when scanning facets (Nos. 1-4) having low elevation angle  
16 characteristics and no (i.e. zero) skew angle characteristics pass through the third laser scanning  
17 station (ST3) and generate laser scanning beams that reflect off the third group of beam folding  
18 mirrors (MG3@ST3) associated therewith during system operation;

19 Fig. 5O5 is a second elevated side view of a wire-frame model of the laser scanning  
20 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
21 schematically illustrating the projection of substantially horizontally disposed laser scanning  
22 planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence  
23 type) bar code symbols when scanning facets (Nos. 1-4) having low elevation angle  
24 characteristics and no (i.e. zero) skew angle characteristics pass through the third laser scanning  
25 station (ST3) and generate laser scanning beams that reflect off the third group of beam folding  
26 mirrors (MG3@ST3) associated therewith during system operation;

27 Fig. 5H1 is a perspective view of the bioptical holographic laser scanning system of the  
28 illustrative embodiment of the present invention, schematically illustrating the projection of  
29 substantially horizontally disposed laser scanning planes through the bottom scanning window  
30 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
31 (Nos. 1-4) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics  
32 pass through the third laser scanning station (ST3) and generate laser scanning beams that reflect  
33 off the third group of beam folding mirrors (MG3@ST3) associated therewith during system  
34 operation;

35 Fig. 5P2 is a plan view of the bioptical holographic laser scanning system of the  
36 illustrative embodiment of the present invention, schematically illustrating the projection of  
37 substantially horizontally disposed laser scanning planes through the bottom scanning window  
38 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
39 (Nos. 1-4) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics  
40 pass through the third laser scanning station (ST3) and generate laser scanning beams that reflect  
41 off the third group of beam folding mirrors (MG3@ST3) associated therewith during system  
42 operation;

1 Fig. 5P3 is an elevated end view of the bioptical holographic laser scanning system of the  
2 illustrative embodiment of the present invention, schematically illustrating the projection of  
3 substantially horizontally disposed laser scanning planes through the bottom scanning window  
4 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
5 (Nos. 1-4) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics  
6 pass through the third laser scanning station (ST3) and generate laser scanning beams that reflect  
7 off the third group of beam folding mirrors (MG3@ST3) associated therewith during system  
8 operation;

9 Fig. 5P4 is a first elevated side view of the bioptical holographic laser scanning system of  
10 the illustrative embodiment of the present invention, schematically illustrating the projection of  
11 substantially horizontally disposed laser scanning planes through the bottom scanning window  
12 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
13 (Nos. 1-4) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics  
14 pass through the third laser scanning station (ST3) and generate laser scanning beams that reflect  
15 off the third group of beam folding mirrors (MG3@ST3) associated therewith during system  
16 operation;

17 Fig. 5P5 is a second elevated side view of the bioptical holographic laser scanning system  
18 of the illustrative embodiment of the present invention, schematically illustrating the projection  
19 of substantially horizontally disposed laser scanning planes through the bottom scanning window  
20 for reading vertically-oriented (i.e. picket-fence type) bar code symbols when scanning facets  
21 (Nos. 1-4) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics  
22 pass through the third laser scanning station (ST3) and generate laser scanning beams that reflect  
23 off the third group of beam folding mirrors (MG3@ST3) associated therewith during system  
24 operation;

25 Fig. 5Q1 is a perspective view of a wire-frame model of the laser scanning platform  
26 within the bioptical holographic laser scanning system of the illustrative embodiment,  
27 schematically illustrating the projection of both substantially horizontally and vertically disposed  
28 laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e.  
29 picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code  
30 symbols, respectively, when scanning facets (Nos. 1-4 and 7-12) pass through the third laser  
31 scanning station (ST3) and generate laser scanning beams that reflect off the first, second and  
32 third groups of beam folding mirrors (MG1@ST3, MG2@ST3 and MG3@ST3) associated  
33 therewith during system operation;

34 Fig. 5Q2 is a plan view of a wire-frame model of the laser scanning platform within the  
35 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
36 illustrating the projection of both substantially horizontally and vertically disposed laser  
37 scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-  
38 fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols,  
39 respectively, when scanning facets (Nos. 1-4 and 7-12) pass through the third laser scanning  
40 station (ST3) and generate laser scanning beams that reflect off the first, second and third groups  
41 of beam folding mirrors (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during  
42 system operation;

1 scanning beams that reflect off the first, second and third groups of beam folding mirrors  
2 (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

3 Fig. 5R3 is an elevated end view of the bioptical holographic laser scanning system of the  
4 illustrative embodiment of the present invention, schematically illustrating the projection of both  
5 substantially horizontally and vertically disposed laser scanning planes through the bottom  
6 scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
7 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
8 (Nos. 1-4 and 7-12) disc pass through the third laser scanning station (ST3) and generate laser  
9 scanning beams that reflect off the first, second and third groups of beam folding mirrors  
10 (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

11 Fig. 5R4 is a first elevated side view of the bioptical holographic laser scanning system of  
12 the illustrative embodiment of the present invention, schematically illustrating the projection of  
13 both substantially horizontally and vertically disposed laser scanning planes through the bottom  
14 scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
15 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
16 (Nos. 1-4 and 7-12) disc pass through the third laser scanning station (ST3) and generate laser  
17 scanning beams that reflect off the first, second and third groups of beam folding mirrors  
18 (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

19 Fig. 5R5 is a second elevated side view of the bioptical holographic laser scanning  
20 system of the illustrative embodiment of the present invention, schematically illustrating the  
21 projection of both substantially horizontally and vertically disposed laser scanning planes  
22 through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar  
23 code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when  
24 scanning facets (Nos. 1-4 and 7-12) disc pass through the third laser scanning station (ST3) and  
25 generate laser scanning beams that reflect off the first, second and third groups of beam folding  
26 mirrors (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

27 Fig. 5S1 is a perspective view of a wire-frame model of the laser scanning platform  
28 within the bioptical holographic laser scanning system of the illustrative embodiment,  
29 schematically illustrating the projection of both substantially horizontally and vertically disposed  
30 laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e.  
31 picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code  
32 symbols, respectively, when scanning facets (Nos. 1-12) pass through the first, second and third  
33 laser scanning stations (ST3, ST2 and ST3) and generate laser scanning beams that reflect off the  
34 groups of beam folding mirrors (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2,  
35 (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

36 Fig. 5S2 is a plan view of a wire-frame model of the laser scanning platform within the  
37 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
38 illustrating the projection of both substantially horizontally and vertically disposed laser  
39 scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-  
40 fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols,  
41 respectively, when scanning facets (Nos. 1-12) pass through the first, second and third laser  
42 scanning stations (ST3, ST2 and ST3) and generate laser scanning beams that reflect off the

groups of beam folding mirrors (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

Fig. 5S3 is an elevated end view of a wire-frame model of the laser scanning platform within the bioptical holographic laser scanning system of the illustrative embodiment, schematically illustrating the projection of both substantially horizontally and vertically disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets (Nos. 1-12) pass through the first, second and third laser scanning stations (ST3, ST2 and ST3) and generate laser scanning beams that reflect off the groups of beam folding mirrors (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

Fig. 5S4 is a first elevated side view of a wire-frame model of the laser scanning platform within the bioptical holographic laser scanning system of the illustrative embodiment, schematically illustrating the projection of both substantially horizontally and vertically disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets (Nos. 1-12) pass through the first, second and third laser scanning stations (ST3, ST2 and ST3) and generate laser scanning beams that reflect off the groups of beam folding mirrors (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

Fig. 5S5 is a second elevated side view of a wire-frame model of the laser scanning platform within the bioptical holographic laser scanning system of the illustrative embodiment, schematically illustrating the projection of both substantially horizontally and vertically disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets (Nos. 1-12) pass through the first, second and third laser scanning stations (ST3, ST2 and ST3) and generate laser scanning beams that reflect off the groups of beam folding mirrors (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

Fig. 5T1 is a perspective view of the bioptical holographic laser scanning system of the illustrative embodiment of the present invention, schematically illustrating the projection of both substantially horizontally and vertically disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets (Nos. 1-12) pass through the first, second and third laser scanning stations (ST3, ST2 and ST3) and generate laser scanning beams that reflect off the groups of beam folding mirrors (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation;

Fig. 5T2 is a plan view of the bioptical holographic laser scanning system of the illustrative embodiment of the present invention, schematically illustrating the projection of both substantially horizontally and vertically disposed laser scanning planes through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and

1 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
2 (Nos. 1-12) pass through the first, second and third laser scanning stations (ST3, ST2 and ST3)  
3 and generate laser scanning beams that reflect off the groups of beam folding mirrors  
4 (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and MG3@ST3)  
5 associated therewith during system operation;

6 Fig. 5T3 is an elevated end view of the bioptical holographic laser scanning system of the  
7 illustrative embodiment of the present invention, schematically illustrating the projection of both  
8 substantially horizontally and vertically disposed laser scanning planes through the bottom  
9 scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
10 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
11 (Nos. 1-12) pass through the first, second and third laser scanning stations (ST3, ST2 and ST3)  
12 and generate laser scanning beams that reflect off the groups of beam folding mirrors  
13 (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and MG3@ST3)  
14 associated therewith during system operation;

15 Fig. 5T4 is a first elevated side view of the bioptical holographic laser scanning system of  
16 the illustrative embodiment of the present invention, schematically illustrating the projection of  
17 both substantially horizontally and vertically disposed laser scanning planes through the bottom  
18 scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
19 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
20 (Nos. 1-12) pass through the first, second and third laser scanning stations (ST3, ST2 and ST3)  
21 and generate laser scanning beams that reflect off the groups of beam folding mirrors  
22 (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and MG3@ST3)  
23 associated therewith during system operation;

24 Fig. 5T5 is a second elevated side view of the bioptical holographic laser scanning  
25 system of the illustrative embodiment of the present invention, schematically illustrating the  
26 projection of both substantially horizontally and vertically disposed laser scanning planes  
27 through the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar  
28 code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when  
29 scanning facets (Nos. 1-12) pass through the first, second and third laser scanning stations (ST3,  
30 ST2 and ST3) and generate laser scanning beams that reflect off the groups of beam folding  
31 mirrors (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and  
32 MG3@ST3) associated therewith during system operation;

33 Fig. 5U1 is a perspective view of a wire-frame model of the laser scanning platform  
34 within the bioptical holographic laser scanning system of the illustrative embodiment,  
35 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
36 through the side scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
37 symbols, when scanning facets (Nos. 7-12) pass through the fourth laser scanning station (ST4)  
38 and generate laser scanning beams that reflect off the groups of beam folding mirrors  
39 (MG1@ST4 and MG2@ST4) associated therewith during system operation;

40 Fig. 5U2 is a plan view of a wire-frame model of the laser scanning platform within the  
41 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
42 illustrating the projection of substantially vertically disposed laser scanning planes through the

1 side scanning window for reading horizontally-oriented (i.e. ladder type) bar code symbols,  
2 when scanning facets (Nos. 7-12) pass through the fourth laser scanning station (ST4) and  
3 generate laser scanning beams that reflect off the first and second groups of beam folding mirrors  
4 (MG1@ST4 and MG2@ST4) associated therewith during system operation;

5 Fig. 5U3 is an elevated end view of a wire-frame model of the laser scanning platform  
6 within the bioptical holographic laser scanning system of the illustrative embodiment,  
7 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
8 through the side scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
9 symbols, when scanning facets (Nos. 7-12) pass through the fourth laser scanning station (ST4)  
10 and generate laser scanning beams that reflect off the first and second groups of beam folding  
11 mirrors (MG1@ST4 and MG2@ST4) associated therewith during system operation;

12 Fig. 5U4 is a first elevated side view of a wire-frame model of the laser scanning  
13 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
14 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
15 through the side scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
16 symbols, when scanning facets (Nos. 7-12) pass through the fourth laser scanning station (ST4)  
17 and generate laser scanning beams that reflect off the first and second groups of beam folding  
18 mirrors (MG1@ST4 and MG2@ST4) associated therewith during system operation;

19 Fig. 5U5 is a second elevated side view of a wire-frame model of the laser scanning  
20 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
21 schematically illustrating the projection of substantially vertically disposed laser scanning planes  
22 through the side scanning window for reading horizontally-oriented (i.e. ladder type) bar code  
23 symbols, when scanning facets (Nos. 7-12) pass through the fourth laser scanning station (ST4)  
24 and generate laser scanning beams that reflect off the first and second groups of beam folding  
25 mirrors (MG1@ST4 and MG2@ST4) associated therewith during system operation;

26 Fig. 5V1 is a perspective view of the bioptical holographic laser scanning system of the  
27 illustrative embodiment of the present invention, schematically illustrating the projection of  
28 substantially vertically disposed laser scanning planes through the side scanning window for  
29 reading horizontally-oriented (i.e. ladder type) bar code symbols, when scanning facets (Nos. 7-  
30 12) pass through the fourth laser scanning station (ST4) and generate laser scanning beams that  
31 reflect off the first and second groups of beam folding mirrors (MG1@ST4 and MG2@ST4)  
32 associated therewith during system operation;

33 Fig. 5V3 is an elevated end view of the bioptical holographic laser scanning system of the  
34 illustrative embodiment of the present invention, schematically illustrating the projection of  
35 substantially vertically disposed laser scanning planes through the side scanning window for  
36 reading horizontally-oriented (i.e. ladder type) bar code symbols, when scanning facets (Nos. 7-  
37 12) pass through the fourth laser scanning station (ST4) and generate laser scanning beams that  
38 reflect off the first and second groups of beam folding mirrors (MG1@ST4 and MG2@ST4)  
39 associated therewith during system operation;

40 Fig. 5V4 is a first elevated side view of the bioptical holographic laser scanning system  
41 of the illustrative embodiment of the present invention, schematically illustrating the projection  
42 of substantially vertically disposed laser scanning planes through the side scanning window for

1 reading horizontally-oriented (i.e. ladder type) bar code symbols, when scanning facets (Nos. 7-  
2 12) pass through the fourth laser scanning station (ST4) and generate laser scanning beams that  
3 reflect off the first and second groups of beam folding mirrors (MG1@ST4 and MG2@ST4)  
4 associated therewith during system operation;

5 Fig. 5V5 is a second elevated side view of the bioptical holographic laser scanning  
6 system of the illustrative embodiment of the present invention, schematically illustrating the  
7 projection of substantially vertically disposed laser scanning planes through the side scanning  
8 window for reading horizontally-oriented (i.e. ladder type) bar code symbols, when scanning  
9 facets (Nos. 7-12) pass through the fourth laser scanning station (ST4) and generate laser  
10 scanning beams that reflect off the first and second groups of beam folding mirrors (MG1@ST4  
11 and MG2@ST4) associated therewith during system operation;

12 Fig. 5W1 is a perspective view of a wire-frame model of the laser scanning platform  
13 within the bioptical holographic laser scanning system of the illustrative embodiment,  
14 schematically illustrating the projection of substantially horizontally disposed laser scanning  
15 planes through the side scanning window for reading vertically-oriented (i.e. picket-fence type)  
16 bar code symbols, when scanning facets (Nos. 1-6) pass through the fourth laser scanning station  
17 (ST4) and generate laser scanning beams that reflect off the third group of beam folding mirrors  
18 (MG3@ST4) associated therewith during system operation;

19 Fig. 5W2 is a plan view of a wire-frame model of the laser scanning platform within the  
20 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
21 illustrating the projection of substantially horizontally disposed laser scanning planes through the  
22 side scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols,  
23 when scanning facets (Nos. 1-6) pass through the fourth laser scanning station (ST4) and  
24 generate laser scanning beams that reflect off the third group of beam folding mirrors  
25 (MG3@ST4) associated therewith during system operation;

26 Fig. 5W4 is a first elevated side view of a wire-frame model of the laser scanning  
27 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
28 schematically illustrating the projection of substantially horizontally disposed laser scanning  
29 planes through the side scanning window for reading vertically-oriented (i.e. picket-fence type)  
30 bar code symbols, when scanning facets (Nos. 1-6) pass through the fourth laser scanning station  
31 (ST4) and generate laser scanning beams that reflect off the third group of beam folding mirrors  
32 (MG3@ST4) associated therewith during system operation;

33 Fig. 5W5 is a second elevated side view of a wire-frame model of the laser scanning  
34 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
35 schematically illustrating the projection of substantially horizontally disposed laser scanning  
36 planes through the side scanning window for reading vertically-oriented (i.e. picket-fence type)  
37 bar code symbols, when scanning facets (Nos. 1-6) pass through the fourth laser scanning station  
38 (ST4) and generate laser scanning beams that reflect off the third group of beam folding mirrors  
39 (MG3@ST4) associated therewith during system operation;

40 Fig. 5X1 is a perspective view of the bioptical holographic laser scanning system of the  
41 illustrative embodiment of the present invention, schematically illustrating the projection of  
42 substantially horizontally disposed laser scanning planes through the side scanning window for

1 reading vertically-oriented (i.e. picket-fence type) bar code symbols, when scanning facets (Nos.  
2 1-6) pass through the fourth laser scanning station (ST4) and generate laser scanning beams that  
3 reflect off the third group of beam folding mirrors (MG3@ST4) associated therewith during  
4 system operation;

5 Fig. 5X2 is a plan view of the bioptical holographic laser scanning system of the  
6 illustrative embodiment of the present invention, schematically illustrating the projection of  
7 substantially horizontally disposed laser scanning planes through the side scanning window for  
8 reading vertically-oriented (i.e. picket-fence type) bar code symbols, when scanning facets (Nos.  
9 1-6) pass through the fourth laser scanning station (ST4) and generate laser scanning beams that  
10 reflect off the third group of beam folding mirrors (MG3@ST4) associated therewith during  
11 system operation;

12 Fig. 5X3 is an elevated end view of the bioptical holographic laser scanning system of the  
13 illustrative embodiment of the present invention, schematically illustrating the projection of  
14 substantially horizontally disposed laser scanning planes through the side scanning window for  
15 reading vertically-oriented (i.e. picket-fence type) bar code symbols, when scanning facets (Nos.  
16 1-6) pass through the fourth laser scanning station (ST4) and generate laser scanning beams that  
17 reflect off the third group of beam folding mirrors (MG3@ST4) associated therewith during  
18 system operation;

19 Fig. 5X4 is a first elevated side view of the bioptical holographic laser scanning system  
20 of the illustrative embodiment of the present invention, schematically illustrating the projection  
21 of substantially horizontally disposed laser scanning planes through the side scanning window  
22 for reading vertically-oriented (i.e. picket-fence type) bar code symbols, when scanning facets  
23 (Nos. 1-6) pass through the fourth laser scanning station (ST4) and generate laser scanning  
24 beams that reflect off the third group of beam folding mirrors (MG3@ST4) associated therewith  
25 during system operation;

26 Fig. 5X5 is a second elevated side view of the bioptical holographic laser scanning  
27 system of the illustrative embodiment of the present invention, schematically illustrating the  
28 projection of substantially horizontally disposed laser scanning planes through the side scanning  
29 window for reading vertically-oriented (i.e. picket-fence type) bar code symbols, when scanning  
30 facets (Nos. 1-6) pass through the fourth laser scanning station (ST4) and generate laser scanning  
31 beams that reflect off the third group of beam folding mirrors (MG3@ST4) associated therewith  
32 during system operation;

33 Fig. 5Y1 is a perspective view of a wire-frame model of the laser scanning platform  
34 within the bioptical holographic laser scanning system of the illustrative embodiment,  
35 schematically illustrating the projection of both substantially horizontally and vertically disposed  
36 laser scanning planes through the side scanning window for reading vertically-oriented (i.e.  
37 picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code  
38 symbols, respectively, when scanning facets (Nos. 1-12) pass through the fourth laser scanning  
39 station (ST4) and generate laser scanning beams that reflect off the first, second and third groups  
40 of beam folding mirrors (MG1@ST4, MG2@ST4 and MG3@ST4) associated therewith during  
41 system operation;



1 Fig. 5Y2 is a plan view of a wire-frame model of the laser scanning platform within the  
2 bioptical holographic laser scanning system of the illustrative embodiment, schematically  
3 illustrating the projection of both substantially horizontally and vertically disposed laser  
4 scanning planes through the side scanning window for reading vertically-oriented (i.e. picket-  
5 fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols,  
6 respectively, when scanning facets (Nos. 1-12) pass through the fourth laser scanning station  
7 (ST4) and generate laser scanning beams that reflect off the first, second and third groups of  
8 beam folding mirrors (MG1@ST4, MG2@ST4 and MG3@ST4) associated therewith during  
9 system operation;

10 Fig. 5Y4 is a first elevated side view of a wire-frame model of the laser scanning  
11 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
12 schematically illustrating the projection of both substantially horizontally and vertically disposed  
13 laser scanning planes through the side scanning window for reading vertically-oriented (i.e.  
14 picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code  
15 symbols, respectively, when scanning facets (Nos. 1-12) pass through the fourth laser scanning  
16 station (ST4) and generate laser scanning beams that reflect off the first, second and third groups  
17 of beam folding mirrors (MG1@ST4, MG2@ST4 and MG3@ST4) associated therewith during  
18 system operation;

19 Fig. 5Y5 is a second elevated side view of a wire-frame model of the laser scanning  
20 platform within the bioptical holographic laser scanning system of the illustrative embodiment,  
21 schematically illustrating the projection of both substantially horizontally and vertically disposed  
22 laser scanning planes through the side scanning window for reading vertically-oriented (i.e.  
23 picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code  
24 symbols, respectively, when scanning facets (Nos. 1-12) pass through the fourth laser scanning  
25 station (ST4) and generate laser scanning beams that reflect off the first, second and third groups  
26 of beam folding mirrors (MG1@ST4, MG2@ST4 and MG3@ST4) associated therewith during  
27 system operation;

28 Fig. 5Z1 is a perspective view of the bioptical holographic laser scanning system of the  
29 illustrative embodiment of the present invention, schematically illustrating the projection of both  
30 substantially horizontally and vertically disposed laser scanning planes through the side scanning  
31 window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
32 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
33 (Nos. 1-12) pass through the fourth laser scanning station (ST4) and generate laser scanning  
34 beams that reflect off the first, second and third groups of beam folding mirrors (MG1@ST4,  
35 MG2@ST4 and MG3@ST4) associated therewith during system operation;

36 Fig. 5Z2 is a plan view of the bioptical holographic laser scanning system of the  
37 illustrative embodiment of the present invention, schematically illustrating the projection of both  
38 substantially horizontally and vertically disposed laser scanning planes through the side scanning  
39 window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
40 horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets  
41 (Nos. 1-12) pass through the fourth laser scanning station (ST4) and generate laser scanning

beams that reflect off the first, second and third groups of beam folding mirrors (MG1@ST4, MG2@ST4 and MG3@ST4) associated therewith during system operation;

Fig. 5Z3 is an elevated end view of the bioptical holographic laser scanning system of the illustrative embodiment of the present invention, schematically illustrating the projection of both substantially horizontally and vertically disposed laser scanning planes through the side scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets (Nos. 1-12) pass through the fourth laser scanning station (ST4) and generate laser scanning beams that reflect off the first, second and third groups of beam folding mirrors (MG1@ST4, MG2@ST4 and MG3@ST4) associated therewith during system operation;

Fig. 5Z4 is a first elevated side view of the bioptical holographic laser scanning system of the illustrative embodiment of the present invention, schematically illustrating the projection of both substantially horizontally and vertically disposed laser scanning planes through the side scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets (Nos. 1-12) pass through the fourth laser scanning station (ST4) and generate laser scanning beams that reflect off the first, second and third groups of beam folding mirrors (MG1@ST4, MG2@ST4 and MG3@ST4) associated therewith during system operation;

Fig. 5Z5 is a second elevated side view of the bioptical holographic laser scanning system of the illustrative embodiment of the present invention, schematically illustrating the projection of both substantially horizontally and vertically disposed laser scanning planes through the side scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder type) bar code symbols, respectively, when scanning facets (Nos. 1-12) pass through the fourth laser scanning station (ST4) and generate laser scanning beams that reflect off the first, second and third groups of beam folding mirrors (MG1@ST4, MG2@ST4 and MG3@ST4) associated therewith during system operation;

Fig. 6A1 is a perspective view of a solid model of the first laser scanning station (ST1) and holographic scanning disc in the bioptical holographic laser scanning system of the illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced by a scanning facet (i.e. Facet Nos. 7, 9 and 11) having high elevation angle characteristics and positive (i.e. left) skew angle characteristics, causing the laser beam to be reflected off the first group of beam folding mirrors (MG1@ST1) associated with the first laser scanning station (ST1) and projected out the bottom scanning window of the system;

Fig. 6A2 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the first local coordinate reference system R1, the direction of the laser beam incident the scanning disc at laser scanning station ST1, and (ii) four sets of x,y,z coordinates specifying, relative to the first local coordinate reference system R1, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST1 is diffracted by rotating scanning facet No. 7, reflected off the two beam folding mirrors in group MG1@ST1 thereof, and ultimately projected through

the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5B1 through 5C5;

Fig. 6A3 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the first local coordinate reference system R1, the direction of the laser beam incident the scanning disc at laser scanning station ST1, and (ii) four sets of x,y,z coordinates specifying, relative to the first local coordinate reference system R1, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST1 is diffracted by rotating scanning facet No. 9, reflected off the two beam folding mirrors in group MG1@ST1 thereof, and ultimately projected through the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5B1 through 5C5;

Fig. 6A4 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the first local coordinate reference system R1, the direction of the laser beam incident the scanning disc at laser scanning station ST1, and (ii) four sets of x,y,z coordinates specifying, relative to the first local coordinate reference system R1, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST1 is diffracted by rotating scanning facet No. 11, reflected off the two beam folding mirrors in group MG1@ST1 thereof, and ultimately projected through the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5B1 through 5C5;

Fig. 6B1 is a perspective view of a solid model of the first laser scanning station (ST1) and holographic scanning disc in the bioptical holographic laser scanning system of the illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced by a scanning facet (i.e. Facet Nos. 8, 10 and 12) having high elevation angle characteristics and negative (i.e. right) skew angle characteristics, causing the laser beam to be reflected off the second group of beam folding mirrors (MG2@ST1) associated with the first laser scanning station (ST1) and projected out the bottom scanning window of the system;

Fig. 6B2 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the first local coordinate reference system R1, the direction of the laser beam incident the scanning disc at laser scanning station ST1, and (ii) three sets of x,y,z coordinates specifying, relative to the first local coordinate reference system R1, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST1 is diffracted by scanning facet No. 8, reflected off the three beam folding mirrors in group MG2@ST1 thereof, and ultimately projected through the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5D1 through 5E5;

Fig. 6B3 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the first local coordinate reference system R1, the direction of the laser beam incident the scanning disc at laser scanning station ST1, and (ii) three sets of x,y,z coordinates specifying, relative to the first local coordinate reference system R1, the outgoing optical paths of three

1 different laser scanning beams defining the beginning, middle and end portions of a substantially  
2 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
3 station ST1 is diffracted by scanning facet No. 10, reflected off the three beam folding mirrors in  
4 group MG2@ST1 thereof, and ultimately projected through the bottom scanning window of the  
5 system towards the focal point of the scanning facet, as illustrated in Figs. 5D1 through 5E5;

6 Fig. 6B4 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
7 relative to the first local coordinate reference system R1, the direction of the laser beam incident  
8 the scanning disc at laser scanning station ST1, and (ii) three sets of x,y,z coordinates specifying,  
9 relative to the first local coordinate reference system R1, the outgoing optical paths of three  
10 different laser scanning beams defining the beginning, middle and end portions of a substantially  
11 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
12 station ST1 is diffracted by scanning facet No. 12, reflected off the three beam folding mirrors in  
13 group MG2@ST1 thereof, and ultimately projected through the bottom scanning window of the  
14 system towards the focal point of the scanning facet, as illustrated in Figs. 5D1 through 5E5;

15 Fig. 6C1 is a perspective view of a solid model of the first laser scanning station (ST1)  
16 and holographic scanning disc in the bioptical holographic laser scanning system of the  
17 illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced  
18 by a scanning facet (i.e. Facet Nos. 1-4) having low elevation angle characteristics and no (i.e.  
19 zero) skew angle characteristics, causing the laser beam to be reflected off the third group of  
20 beam folding mirrors (MG3@ST1) associated with the first laser scanning station (ST1) and  
21 projected out the bottom scanning window of the system;

22 Fig. 6C2 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
23 relative to the first local coordinate reference system R1, the direction of the laser beam incident  
24 the scanning disc at laser scanning station ST1, and (ii) three sets of x,y,z coordinates specifying,  
25 relative to the first local coordinate reference system R1, the outgoing optical paths of three  
26 different laser scanning beams defining the beginning, middle and end portions of a substantially  
27 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
28 station ST1 is diffracted by scanning facet No. 1, reflected off the two beam folding mirrors in  
29 group MG3@ST1 thereof, and ultimately projected through the bottom scanning window of the  
30 system towards the focal point of the scanning facet, as illustrated in Figs. 5F1 through 5G5;

31 Fig. 6C3 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
32 relative to the first local coordinate reference system R1, the direction of the laser beam incident  
33 the scanning disc at laser scanning station ST1, and (ii) three sets of x,y,z coordinates specifying,  
34 relative to the first local coordinate reference system R1, the outgoing optical paths of three  
35 different laser scanning beams defining the beginning, middle and end portions of a substantially  
36 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
37 station ST1 is diffracted by scanning facet No. 2, reflected off the two beam folding mirrors in  
38 group MG3@ST1 thereof, and ultimately projected through the bottom scanning window of the  
39 system towards the focal point of the scanning facet, as illustrated in Figs. 5F1 through 5G5;

40 Fig. 6C4 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
41 relative to the first local coordinate reference system R1, the direction of the laser beam incident  
42 the scanning disc at laser scanning station ST1, and (ii) three sets of x,y,z coordinates specifying,

1 relative to the first local coordinate reference system R1, the outgoing optical paths of three  
2 different laser scanning beams defining the beginning, middle and end portions of a substantially  
3 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
4 station ST1 is diffracted by scanning facet No. 3, reflected off the two beam folding mirrors in  
5 group MG3@ST1 thereof, and ultimately projected through the bottom scanning window of the  
6 system towards the focal point of the scanning facet, as illustrated in Figs. 5F1 through 5G5;

7 Fig. 6C5 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
8 relative to the first local coordinate reference system R1, the direction of the laser beam incident  
9 the scanning disc at laser scanning station ST1, and (ii) three sets of x,y,z coordinates specifying,  
10 relative to the first local coordinate reference system R1, the outgoing optical paths of three  
11 different laser scanning beams defining the beginning, middle and end portions of a substantially  
12 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
13 station ST1 is diffracted by scanning facet No. 4, reflected off the two beam folding mirrors in  
14 group MG3@ST1 thereof, and ultimately projected through the bottom scanning window of the  
15 system towards the focal point of the scanning facet, as illustrated in Figs. 5F1 through 5G5;

16 Fig. 6D1 is a perspective view of a solid model of the second laser scanning station (ST2)  
17 and holographic scanning disc in the bioptical holographic laser scanning system of the  
18 illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced  
19 by a scanning facet (i.e. Facet Nos. 1-6) having low elevation angle characteristics and no (i.e.  
20 zero) skew angle characteristics, causing the laser beam to be reflected off the group of beam  
21 folding mirrors (MG3@ST2) associated with the first laser scanning station (ST2) and projected  
22 out the bottom scanning window of the system;

23 Fig. 6D2 is a spreadsheet-type information table listing (i) the unit coordinates  
24 specifying, relative to the second local coordinate reference system R2, the direction of the laser  
25 beam incident the scanning disc at laser scanning station ST2, and (ii) three sets of x,y,z  
26 coordinates specifying, relative to the second local coordinate reference system R2, the outgoing  
27 optical paths of three different laser scanning beams defining the beginning, middle and end  
28 portions of a substantially planar laser scanning plane that is produced when the incident laser  
29 scanning beam at scanning station ST2 is diffracted by scanning facet No. 1, reflected off the  
30 three beam folding mirrors in group MG3@ST2 thereof, and ultimately projected through the  
31 bottom scanning window of the system towards the focal point of the scanning facet, as  
32 illustrated in Figs. 5I1 through 5J5;

33 Fig. 6D3 is a spreadsheet-type information table listing (i) the unit coordinates  
34 specifying, relative to the second local coordinate reference system R2, the direction of the laser  
35 beam incident the scanning disc at laser scanning station ST2, and (ii) three sets of x,y,z  
36 coordinates specifying, relative to the second local coordinate reference system R2, the outgoing  
37 optical paths of three different laser scanning beams defining the beginning, middle and end  
38 portions of a substantially planar laser scanning plane that is produced when the incident laser  
39 scanning beam at scanning station ST2 is diffracted by scanning facet No. 2, reflected off the  
40 three beam folding mirrors in group MG3@ST2 thereof, and ultimately projected through the  
41 bottom scanning window of the system towards the focal point of the scanning facet, as  
42 illustrated in Figs. 5I1 through 5J5;

1 Fig. 6D4 is a spreadsheet-type information table listing (i) the unit coordinates  
2 specifying, relative to the second local coordinate reference system R2, the direction of the laser  
3 beam incident the scanning disc at laser scanning station ST2, and (ii) three sets of x,y,z  
4 coordinates specifying, relative to the second local coordinate reference system R2, the outgoing  
5 optical paths of three different laser scanning beams defining the beginning, middle and end  
6 portions of a substantially planar laser scanning plane that is produced when the incident laser  
7 scanning beam at scanning station ST2 is diffracted by scanning facet No. 3, reflected off the  
8 three beam folding mirrors in group MG3@ST2 thereof, and ultimately projected through the  
9 bottom scanning window of the system towards the focal point of the scanning facet, as  
10 illustrated in Figs. 5I1 through 5J5;

11 Fig. 6D5 is a spreadsheet-type information table listing (i) the unit coordinates  
12 specifying, relative to the second local coordinate reference system R2, the direction of the laser  
13 beam incident the scanning disc at laser scanning station ST2, and (ii) three sets of x,y,z  
14 coordinates specifying, relative to the second local coordinate reference system R2, the outgoing  
15 optical paths of three different laser scanning beams defining the beginning, middle and end  
16 portions of a substantially planar laser scanning plane that is produced when the incident laser  
17 scanning beam at scanning station ST2 is diffracted by scanning facet No. 4, reflected off the  
18 three beam folding mirrors in group MG3@ST2 thereof, and ultimately projected through the  
19 bottom scanning window of the system towards the focal point of the scanning facet, as  
20 illustrated in Figs. 5I1 through 5J5;

21 Fig. 6D6 is a spreadsheet-type information table listing (i) the unit coordinates  
22 specifying, relative to the second local coordinate reference system R2, the direction of the laser  
23 beam incident the scanning disc at laser scanning station ST2, and (ii) three sets of x,y,z  
24 coordinates specifying, relative to the second local coordinate reference system R2, the outgoing  
25 optical paths of three different laser scanning beams defining the beginning, middle and end  
26 portions of a substantially planar laser scanning plane that is produced when the incident laser  
27 scanning beam at scanning station ST2 is diffracted by scanning facet No. 5, reflected off the  
28 three beam folding mirrors in group MG3@ST2 thereof, and ultimately projected through the  
29 bottom scanning window of the system towards the focal point of the scanning facet, as  
30 illustrated in Figs. 5I1 through 5J5;

31 Fig. 6D7 is a spreadsheet-type information table listing (i) the unit coordinates  
32 specifying, relative to the second local coordinate reference system R2, the direction of the laser  
33 beam incident the scanning disc at laser scanning station ST2, and (ii) three sets of x,y,z  
34 coordinates specifying, relative to the second local coordinate reference system R2, the outgoing  
35 optical paths of three different laser scanning beams defining the beginning, middle and end  
36 portions of a substantially planar laser scanning plane that is produced when the incident laser  
37 scanning beam at scanning station ST2 is diffracted by scanning facet No. 6, reflected off the  
38 three beam folding mirrors in group MG3@ST2 thereof, and ultimately projected through the  
39 bottom scanning window of the system towards the focal point of the scanning facet, as  
40 illustrated in Figs. 5I1 through 5J5;

41 Fig. 6E1 is a perspective view of a solid model of the third laser scanning station (ST3)  
42 and holographic scanning disc in the bioptical holographic laser scanning system of the

1 illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced  
2 by a scanning facet (i.e. Facet Nos. 7, 9 and 11) having high elevation angle characteristics and  
3 positive (i.e. left) skew angle characteristics, causing the laser beam to be reflected off the first  
4 group of beam folding mirrors (MG1@ST3) associated with the third laser scanning station  
5 (ST3) and projected out the bottom scanning window of the system;

6 Fig. 6E2 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
7 relative to the third local coordinate reference system R3, the direction of the laser beam incident  
8 the scanning disc at laser scanning station ST3, and (ii) three sets of x,y,z coordinates specifying,  
9 relative to the third local coordinate reference system R3, the outgoing optical paths of three  
10 different laser scanning beams defining the beginning, middle and end portions of a substantially  
11 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
12 station ST3 is diffracted by scanning facet No. 7, reflected off the three beam folding mirrors in  
13 group MG1@ST3 thereof, and ultimately projected through the bottom scanning window of the  
14 system towards the focal point of the scanning facet, as illustrated in Figs. 5M1 through 5N5;

15 Fig. 6E3 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
16 relative to the third local coordinate reference system R3, the direction of the laser beam incident  
17 the scanning disc at laser scanning station ST3, and (ii) three sets of x,y,z coordinates specifying,  
18 relative to the third local coordinate reference system R3, the outgoing optical paths of three  
19 different laser scanning beams defining the beginning, middle and end portions of a substantially  
20 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
21 station ST3 is diffracted by scanning facet No. 9, reflected off the three beam folding mirrors in  
22 group MG1@ST3 thereof, and ultimately projected through the bottom scanning window of the  
23 system towards the focal point of the scanning facet, as illustrated in Figs. 5M1 through 5N5;

24 Fig. 6E4 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
25 relative to the third local coordinate reference system R3, the direction of the laser beam incident  
26 the scanning disc at laser scanning station ST3, and (ii) three sets of x,y,z coordinates specifying,  
27 relative to the third local coordinate reference system R3, the outgoing optical paths of three  
28 different laser scanning beams defining the beginning, middle and end portions of a substantially  
29 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
30 station ST3 is diffracted by scanning facet No. 11, reflected off the three beam folding mirrors in  
31 group MG1@ST3 thereof, and ultimately projected through the bottom scanning window of the  
32 system towards the focal point of the scanning facet, as illustrated in Figs. 5K1 through 5L5;

33 Fig. 6F1 is a perspective view of a solid model of the third laser scanning station (ST3)  
34 and holographic scanning disc in the bioptical holographic laser scanning system of the  
35 illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced  
36 by a scanning facet (i.e. Facet Nos. 8, 10 and 12) having high elevation angle characteristics and  
37 positive (i.e. left) skew angle characteristics, causing the laser beam to be reflected off the  
38 second group of beam folding mirrors (MG2) associated with the third laser scanning station  
39 (ST3) and projected out the bottom scanning window of the system;

40 Fig. 6F2 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
41 relative to the third local coordinate reference system R3, the direction of the laser beam incident  
42 the scanning disc at laser scanning station ST3, and (ii) four sets of x,y,z coordinates specifying,

1 relative to the third local coordinate reference system R3, the outgoing optical paths of three  
2 different laser scanning beams defining the beginning, middle and end portions of a substantially  
3 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
4 station ST3 is diffracted by scanning facet No. 8, reflected off the two beam folding mirrors in  
5 group MG2@ST3 thereof, and ultimately projected through the bottom scanning window of the  
6 system towards the focal point of the scanning facet, as illustrated in Figs. 5M1 through 5N5;

7 Fig. 6F3 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
8 relative to the third local coordinate reference system R3, the direction of the laser beam incident  
9 the scanning disc at laser scanning station ST3, and (ii) four sets of x,y,z coordinates specifying,  
10 relative to the third local coordinate reference system R3, the outgoing optical paths of three  
11 different laser scanning beams defining the beginning, middle and end portions of a substantially  
12 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
13 station ST3 is diffracted by scanning facet No. 10, reflected off the two beam folding mirrors in  
14 group MG2@ST3 thereof, and ultimately projected through the bottom scanning window of the  
15 system towards the focal point of the scanning facet, as illustrated in Figs. 5M1 through 5N5;

16 Fig. 6F4 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
17 relative to the third local coordinate reference system R3, the direction of the laser beam incident  
18 the scanning disc at laser scanning station ST3, and (ii) four sets of x,y,z coordinates specifying,  
19 relative to the third local coordinate reference system R3, the outgoing optical paths of three  
20 different laser scanning beams defining the beginning, middle and end portions of a substantially  
21 planar laser scanning plane that is produced when the incident laser scanning beam at scanning  
22 station ST3 is diffracted by scanning facet No. 12, reflected off the two beam folding mirrors in  
23 group MG2@ST3 thereof, and ultimately projected through the bottom scanning window of the  
24 system towards the focal point of the scanning facet, as illustrated in Figs. 5M1 through 5N5;

25 Fig. 6G1 is a perspective view of a solid model of the third laser scanning station (ST3)  
26 and holographic scanning disc in the bioptical holographic laser scanning system of the  
27 illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced  
28 by a scanning facet (i.e. Facet Nos. 1-4) having low elevation angle characteristics and no (i.e.  
29 zero) skew angle characteristics, causing the laser beam to be reflected off the third group of  
30 beam folding mirrors (MG3@ST3) associated with the third laser scanning station (ST3) and  
31 projected out the bottom scanning window of the system;

32 Fig. 6G2 is a spreadsheet-type information table listing (i) the unit coordinates  
33 specifying, relative to the third local coordinate reference system R3, the direction of the laser  
34 beam incident the scanning disc at laser scanning station ST3, and (ii) three sets of x,y,z  
35 coordinates specifying, relative to the third local coordinate reference system R3, the outgoing  
36 optical paths of three different laser scanning beams defining the beginning, middle and end  
37 portions of a substantially planar laser scanning plane that is produced when the incident laser  
38 scanning beam at scanning station ST3 is diffracted by scanning facet No. 1, reflected off two  
39 beam folding mirrors in group MG3@ST3 thereof, and ultimately projected through the bottom  
40 scanning window of the system towards the focal point of the scanning facet, as illustrated in  
41 Figs. 5O1 through 5P5;



Fig. 6G3 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the third local coordinate reference system R3, the direction of the laser beam incident the scanning disc at laser scanning station ST3, and (ii) three sets of x,y,z coordinates specifying, relative to the third local coordinate reference system R3, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST3 is diffracted by scanning facet No. 2, reflected off two beam folding mirrors in group MG3@ST3 thereof, and ultimately projected through the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5O1 through 5P5;

Fig. 6G4 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the third local coordinate reference system R3, the direction of the laser beam incident the scanning disc at laser scanning station ST3, and (ii) three sets of x,y,z coordinates specifying, relative to the third local coordinate reference system R3, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST3 is diffracted by scanning facet No. 3, reflected off two beam folding mirrors in group MG3@ST3 thereof, and ultimately projected through the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5O1 through 5P5;

Fig. 6G5 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the third local coordinate reference system R3, the direction of the laser beam incident the scanning disc at laser scanning station ST3, and (ii) three sets of x,y,z coordinates specifying, relative to the third local coordinate reference system R3, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST3 is diffracted by scanning facet No. 4, reflected off two beam folding mirrors in group MG3@ST3 thereof, and ultimately projected through the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5O1 through 5P5;

Fig. 6H1 is a perspective view of a solid model of the fourth laser scanning station (ST4) and holographic scanning disc in the bioptical holographic laser scanning system of the illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced by a scanning facet (i.e. Facet Nos. 7, 9 and 11) having high elevation angle characteristics and positive (i.e. left) skew angle characteristics, causing the laser beam to be reflected off the first group of beam folding mirrors (MG1@ST4) associated with the third laser scanning station (ST4) and projected out the bottom scanning window of the system;

Fig. 6H2 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the fourth local coordinate reference system R4, the direction of the laser beam incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end

1 portions of a substantially planar laser scanning plane that is produced when the incident laser  
2 scanning beam at scanning station ST4 is diffracted by scanning facet No. 7, reflected off the two  
3 beam folding mirrors in group MG1@ST4 thereof, and ultimately projected through the bottom  
4 scanning window of the system towards the focal point of the scanning facet, as illustrated in  
5 Figs. 5U1 through 5V5;

6 Fig. 6H3 is a spreadsheet-type information table listing (i) the unit coordinates  
7 specifying, relative to the fourth local coordinate reference system R4, the direction of the laser  
8 beam incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z  
9 coordinates specifying, relative to the fourth local coordinate reference system R4, the outgoing  
10 optical paths of three different laser scanning beams defining the beginning, middle and end  
11 portions of a substantially planar laser scanning plane that is produced when the incident laser  
12 scanning beam at scanning station ST4 is diffracted by scanning facet No. 9, reflected off the two  
13 beam folding mirrors in group MG1@ST4 thereof, and ultimately projected through the bottom  
14 scanning window of the system towards the focal point of the scanning facet, as illustrated in  
15 Figs. 5U1 through 5V5;

16 Fig. 6H4 is a spreadsheet-type information table listing (i) the unit coordinates  
17 specifying, relative to the fourth local coordinate reference system R4, the direction of the laser  
18 beam incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z  
19 coordinates specifying, relative to the fourth local coordinate reference system R4, the outgoing  
20 optical paths of three different laser scanning beams defining the beginning, middle and end  
21 portions of a substantially planar laser scanning plane that is produced when the incident laser  
22 scanning beam at scanning station ST4 is diffracted by scanning facet No. 11, reflected off the  
23 two beam folding mirrors in group MG1@ST4 thereof, and ultimately projected through the  
24 bottom scanning window of the system towards the focal point of the scanning facet, as  
25 illustrated in Figs. 5U1 through 5V5;

26 Fig. 6I1 is a perspective view of a solid model of the fourth laser scanning station (ST4)  
27 and holographic scanning disc in the bioptical holographic laser scanning system of the  
28 illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced  
29 by a scanning facet (i.e. Facet Nos. 8, 10 and 12) having high elevation angle characteristics and  
30 negative (i.e. right) skew angle characteristics, causing the laser beam to be reflected off the  
31 second group of beam folding mirrors (MG2@ST4) associated with the fourth laser scanning  
32 station (ST4) and projected out the bottom scanning window of the system;

33 Fig. 6I2 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
34 relative to the fourth local coordinate reference system R4, the direction of the laser beam  
35 incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates  
36 specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths  
37 of three different laser scanning beams defining the beginning, middle and end portions of a  
38 substantially planar laser scanning plane that is produced when the incident laser scanning beam  
39 at scanning station ST4 is diffracted by scanning facet No. 8, reflected off the two beam folding  
40 mirrors in group MG2@ST4 thereof, and ultimately projected through the bottom scanning  
41 window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5U1  
42 through 5V5;

Fig. 6I3 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the fourth local coordinate reference system R4, the direction of the laser beam incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST4 is diffracted by scanning facet No. 10, reflected off the two beam folding mirrors in group MG2@ST4 thereof, and ultimately projected through the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5U1 through 5V5;

Fig. 6I4 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the fourth local coordinate reference system R4, the direction of the laser beam incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST4 is diffracted by scanning facet No. 12, reflected off the two beam folding mirrors in group MG2@ST4 thereof, and ultimately projected through the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5U1 through 5V5;

Fig. 6J1 is a perspective view of a solid model of the fourth laser scanning station (ST4) and holographic scanning disc in the bioptical holographic laser scanning system of the illustrative embodiment, showing the generalized outgoing optical path of a laser beam produced by a scanning facet (i.e. Facet Nos. 1-6) having low elevation angle characteristics and no (i.e. zero) skew angle characteristics, causing the laser beam to be reflected off the third group of beam folding mirrors (MG3@ST4) associated with the fourth laser scanning station (ST4) and projected out the bottom scanning window of the system;

Fig. 6J2 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the fourth local coordinate reference system R4, the direction of the laser beam incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam at scanning station ST4 is diffracted by scanning facet No. 1, reflected off one beam folding mirror in group MG3@ST4, and ultimately projected through the bottom scanning window of the system towards the focal point of the scanning facet, as illustrated in Figs. 5W1 through 5V5;

Fig. 6J3 is a spreadsheet-type information table listing (i) the unit coordinates specifying, relative to the fourth local coordinate reference system R4, the direction of the laser beam incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths of three different laser scanning beams defining the beginning, middle and end portions of a substantially planar laser scanning plane that is produced when the incident laser scanning beam

1 at scanning station ST4 is diffracted by scanning facet No. 2, reflected off one beam folding  
2 mirror in group MG3@ST4, and ultimately projected through the bottom scanning window of  
3 the system towards the focal point of the scanning facet, as illustrated in Figs. 5W1 through 5V5;

4 Fig. 6J4 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
5 relative to the fourth local coordinate reference system R4, the direction of the laser beam  
6 incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates  
7 specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths  
8 of three different laser scanning beams defining the beginning, middle and end portions of a  
9 substantially planar laser scanning plane that is produced when the incident laser scanning beam  
10 at scanning station ST4 is diffracted by scanning facet No. 3, reflected off one beam folding  
11 mirror in group MG3@ST4, and ultimately projected through the bottom scanning window of  
12 the system towards the focal point of the scanning facet, as illustrated in Figs. 5W1 through 5V5;

13 Fig. 6J5 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
14 relative to the fourth local coordinate reference system R4, the direction of the laser beam  
15 incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates  
16 specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths  
17 of three different laser scanning beams defining the beginning, middle and end portions of a  
18 substantially planar laser scanning plane that is produced when the incident laser scanning beam  
19 at scanning station ST4 is diffracted by scanning facet No. 4, reflected off one beam folding  
20 mirror in group MG3@ST4, and ultimately projected through the bottom scanning window of  
21 the system towards the focal point of the scanning facet, as illustrated in Figs. 5W1 through 5V5;

22 Fig. 6J6 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
23 relative to the fourth local coordinate reference system R4, the direction of the laser beam  
24 incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates  
25 specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths  
26 of three different laser scanning beams defining the beginning, middle and end portions of a  
27 substantially planar laser scanning plane that is produced when the incident laser scanning beam  
28 at scanning station ST4 is diffracted by scanning facet No. 5, reflected off one beam folding  
29 mirror in group MG3@ST4, and ultimately projected through the bottom scanning window of  
30 the system towards the focal point of the scanning facet, as illustrated in Figs. 5W1 through 5V5;

31 Fig. 6J7 is a spreadsheet-type information table listing (i) the unit coordinates specifying,  
32 relative to the fourth local coordinate reference system R4, the direction of the laser beam  
33 incident the scanning disc at laser scanning station ST4, and (ii) three sets of x,y,z coordinates  
34 specifying, relative to the fourth local coordinate reference system R4, the outgoing optical paths  
35 of three different laser scanning beams defining the beginning, middle and end portions of a  
36 substantially planar laser scanning plane that is produced when the incident laser scanning beam  
37 at scanning station ST4 is diffracted by scanning facet No. 6, reflected off one beam folding  
38 mirror in group MG3@ST4, and ultimately projected through the bottom scanning window of  
39 the system towards the focal point of the scanning facet, as illustrated in Figs. 5W1 through 5V5;  
40 and

41 Fig. 6K is a schematic representation indicating the time sequential order in which each  
42 laser scanning facet is used to generate a laser scanning planes from each of the laser scanning

stations employed within the bioptical holographic laser scanning system of the illustrative embodiment, wherein each scanning facet is indexed by facet index  $i$  and each laser scanning station is indexed by station index  $j$ .

Figs. 7A through 7R, taken collectively, set forth the steps carried out in a preferred method of designing and constructing the bioptical holographic laser scanning system of the illustrative embodiment;

Fig. 8A is a schematic diagram of the holographic scanning disc of the illustrative embodiment designed and constructed according to the method of the present invention, and indicating the various geometrical parameters used to specify the geometrical optical characteristics of each  $i$ -th holographic scanning facet thereof;

Fig. 8B is a perspective view of a geometrical optics model of the process of producing the  $P(i,j)$ -th laser scanning plane of the system by directing the output laser beam from the  $j$ -th laser beam production module through  $i$ -th holographic scanning facet supported upon the holographic scanning disc as it rotates about its axis of rotation, wherein various parameters employed in the model, including the beam angle of incidence, beam diffraction angle, beam elevation angle, beam scan angle, and beam skew angle are schematically defined;

Fig. 8C is a plan view of the geometrical optics model of Fig. 8B, defining, in greater detail, the skew angle and angle of rotation of the scanning facet with respect to the local coordinate reference system symbolically embedded within the exemplary laser scanning station of the present invention;

Figs. 8D1 and 8D2, collectively, show a table listing parameters used to construct the vector-based geometrical optics model shown in Figs. 8A, 8B and 8C;

Fig. 8E is a table listing mathematical equations used to describe structural and functional relationships among particular parameters in the geometrical optics model of Figs. 8A and 8D;

Fig. 8F1 is a vector-based model of the light diffraction process carried out when a substantially collimated laser scanning beam (indicated by  $R_x$ ) is transmitted from its laser beam production model, through an arbitrary point ( $x$ ) along the center portion of a holographic scanning facet during scanning operations, and diffracted along an outgoing scanning direction specified by vector  $O_x$ , towards the focal point of the scanning facet, as shown in Figs. 8A through 8C;

Fig. 8F2 is a vector-based model of the light diffraction process carried out when a substantially collimated laser scanning beam (indicated by  $R_x$ ) is transmitted from its laser beam production model, through an arbitrary point ( $x$ ) along the center portion of a holographic scanning facet during scanning operations, and diffracted along a prespecified outgoing scanning direction specified by vector  $O_x$ , towards the focal point of the scanning facet, as shown in Figs. 8A through 8C;

Figs. 8F3 and 8F4 set forth a vector-based model of the outgoing laser beam diffracted by an exemplary scanning facet, showing the components of the outgoing laser beam expressed in terms of the focal length, beam elevation angle, beam rotation angle, and beam skew angle characteristics of the scanning facet;

Fig. 8F5 is a table setting forth mathematical expressions defining relationships between the vector components in the models of Figs. 8F3;

1 Fig. 9 is a spreadsheet-type information table listing calculated parameters used to  
2 analyze the light transmission efficiency of the laser scanning beam and calculate the optical  
3 power of the laser scanning beam at the data photodetector and the resulting signal levels, for  
4 targets located at the local planes and targets located at the maximum depth of field limits of  
5 each laser scanning facets;

6 Fig. 10A1 is a geometrical optics model illustrating the path traveled by the light rays  
7 associated with an incident laser beam being initially diffracted by a rotating holographic facet  
8 towards a bar code symbol, then returning light rays reflected therefrom (according to Lambert's  
9 law) being diffracted again by the same holographic facet towards a light focusing parabolic  
10 mirror disposed beneath the scanning disc, and finally the focused light rays being transmitted  
11 through the same holographic facet without diffraction towards its photodetector disposed  
12 substantially above the point of laser beam incidence on the scanning disc;

13 Figs. 10A2 through 10A4 set forth geometrical optics models of the process of a laser  
14 beam propagating through a holographic facet on the rotating holographic scanning disc shown  
15 in Fig. 10A1, which are used during the disc design process of the present invention to compute  
16 the normalized total out-and-back light diffraction efficiency of each holographic facet to S and  
17 P polarized light when no cross-polarizer is used before the photodetector in the holographic  
18 laser scanning system;

19 Fig. 10B sets forth a set of parameters used to represent the geometrical optics models of  
20 Figs. 10A1 through 10A4;

21 Figs. 10C1 and 10C2 set forth a first set of mathematical expressions (Nos. 1-5, 9, 20, 21)  
22 which describe structural and functional relationships among particular parameters of the  
23 geometrical optics model of Figs. 10A1 through 10A4, and a second set of equations (Nos. 6-8,  
24 10-19) which are used to define (1) the light diffraction efficiency of the i-th holographic  
25 scanning facet to S-polarized outgoing light rays incident on the holographic scanning disc, (2)  
26 the light diffraction efficiency of the i-th holographic scanning facet to P-polarized outgoing  
27 light rays incident on the holographic scanning disc, and (3) the total out-and-back light  
28 diffraction efficiency of the i-th holographic scanning facet to S-polarized outgoing light rays  
29 incident on the holographic disc, each being expressed as a function of the modulation-depth (i.e.  
30 modulation-index) within a fixed thickness gelatin;

31 Fig. 10D1 sets forth a set of graphs plotting, as a function of the disc rotation, prior to  
32 facet optimization, (1) the light diffraction efficiency of the first holographic scanning facet (No.  
33 1) to S-polarized outgoing light rays incident thereto, (2) the light diffraction efficiency of the  
34 first holographic scanning facet to P-polarized outgoing light rays incident thereto, (3) the total  
35 out-and-back light diffraction efficiency of the first holographic scanning facet to S-polarized  
36 outgoing light rays incident, and (4) an intensity of the relative signal (i.e.  $T_{scos\theta_d}$ ), for use in  
37 computing the total out-and-back light diffraction efficiency of the first rotation non-optimized  
38 holographic facet relative to the total out-and-back light diffraction efficiency of the twelfth  
39 rotation non-optimized holographic facet;

40 Fig. 10D2 sets forth a set of graphs plotting, as a function of the disc rotation, after facet  
41 optimization, (1) the light diffraction efficiency of the first holographic scanning facet (No. 1) to  
42 S-polarized outgoing light rays incident thereto, (2) the light diffraction efficiency of the

twentieth holographic scanning facet to P-polarized outgoing light rays incident thereto, (3) the total out-and-back light diffraction efficiency of the twentieth holographic scanning facet to S-polarized outgoing light rays incident, and (4) an intensity of the relative signal (i.e.  $T_s \cos \theta_d$ ), for use in computing the total out-and-back light diffraction efficiency of the first rotation-optimized holographic facet relative to the total out-and-back light diffraction efficiency of the twelfth rotation optimized holographic facet;

Fig. 10E1 sets forth a set of graphs plotting, as a function of the disc rotation, prior to facet optimization, (1) the light diffraction efficiency of the seventh holographic scanning facet (No. 7) to S-polarized outgoing light rays incident thereto, (2) the light diffraction efficiency of the first holographic scanning facet to P-polarized outgoing light rays incident thereto, (3) the total out-and-back light diffraction efficiency of the first holographic scanning facet to S-polarized outgoing light rays incident, and (4) an intensity of the relative signal (i.e.  $T_s \cos \theta_d$ ), for use in computing the total out-and-back light diffraction efficiency of the seventh rotation non-optimized holographic facet relative to the total out-and-back light diffraction efficiency of the seventh rotation non-optimized holographic facet;

Fig. 10E2 sets forth a set of graphs plotting, as a function of the disc rotation, after facet optimization, (1) the light diffraction efficiency of the seventh holographic scanning facet (No. 7) to S-polarized outgoing light rays incident thereto, (2) the light diffraction efficiency of the twentieth holographic scanning facet to P-polarized outgoing light rays incident thereto, (3) the total out-and-back light diffraction efficiency of the twentieth holographic scanning facet to S-polarized outgoing light rays incident, and (4) an intensity of the relative signal (i.e.  $T_s \cos \theta_d$ ), for use in computing the total out-and-back light diffraction efficiency of the seventh rotation non-optimized holographic facet relative to the total out-and-back light diffraction efficiency of the seventh rotation non-optimized holographic facet;

Figs. 10F1 through 10F4, taken together, provide a set of tables setting forth the parameters involved in computation of S and P light diffraction efficiencies of the twelve scanning facets on the holographic scanning disc under design, using the geometrical optics models set forth in Figs. 10A1 through 10A4;

Fig. 10G1 is a geometrical optics model of the Lambertian light scattering and collection process which occurs when a laser scanning beam produced by the system under design reflects from and scatters off a bar code symbol during laser scanning operations, wherein the geometrical optics model is used to calculate the light collection efficiency factor  $E_L$  for use in computing the overall laser scanning beam transmission efficiency schematically depicted by partial light transmission efficiency factors encountered along the outgoing and return optical paths of a laser scanning beam within the holographic scanning system of the present invention;

Fig. 10G2 is a list of parameters employed in the geometrical optics model of Fig. 10G1;

Fig. 10G3 is a set of equations for computing particular parameters specified in the geometrical optics model of Fig. 10G1;

Fig. 11A1 is a table setting forth the results of a Truncation Analysis on the effects of diffraction caused by limiting (i.e. truncating) the spot size of a Gaussian laser beam using an aperture-stop, in order to determine the "effective beam diameter" thereof computed in the S and

P directions at the collimating lens employed in each laser beam production module within the bioptical holographic laser scanning system under design;

Fig. 11A2 is a graphical representation indicating the intensity of the laser beam computed at different radial distances from the laser beam production module under design;

Figs. 11B1 and 11B2, collectively, provide a table setting forth the results of a Gaussian Analysis on laser beam propagation from the laser beam production module under design through an exemplary light focusing facet on the holographic scanning disc under design, in order to determine the diameter of the laser beam computed at different distances from the light focusing facet;

Fig. 11B3 is a graphical representation indicating the 60% intensity diameter of a S-polarized laser beam computed at different distances from the holographic scanning disc under design, for use in determining the depth of focus (DOF) of each laser scanning plane produced by its respective laser beam when scanned by the holographic scanning disc;

Fig. 12A1 is a schematic representation of an exemplary scanning facet having geometric symmetry about the center of its angle of rotation, and specified by an assigned set of eight (x,y,z) coordinate points representative of its vertices;

Fig. 12A2 is a schematic representation of an exemplary scanning facet having geometric symmetry about the center of its angle of rotation, specified by an assigned set of eight (x,y,z) coordinate points representative of its vertices, and providing an equivalent facet geometry for the symmetric scanning facet shown in Fig. 12A1;

Fig. 12B1 is a schematic representation of an exemplary scanning facet having geometric asymmetry about the center of its angle of rotation, and specified by an assigned set of eight (x,y,z) coordinate points representative of its vertices;

Fig. 12B2 is a schematic representation of an exemplary scanning facet having geometric asymmetry about the center of its angle of rotation, specified by an assigned set of eight (x,y,z) coordinate points representative of its vertices, and providing an equivalent facet geometry for the asymmetric scanning facet shown in Fig. 12B1;

Fig. 12C1 is a schematic representation graphically illustrating the laser scanning and light collection processes carried out by a particular scanning facet on the holographic scanning disc, whereby an incident laser beam is (i) diffracted by the first end (i.e. beginning) portion of a scanning facet, (ii) focused to a first point in 3-D space specified by the focal length of the scanning facet and the elevation and skew angles of the diffracted laser beam, (iii) scattered/reflected as it scans its target (e.g. a bar code symbol), and the scattered/reflected light rays, and (iv) collected by the light collecting area of the scanning facet;

Fig. 12C2 is a schematic representation graphically illustrating the laser scanning and light collection processes carried out by a particular scanning facet on the holographic disc, whereby an incident laser beam is (i) diffracted by the second end (i.e. end) portion of a scanning facet, (ii) focused to a second point in 3-D space specified by the focal length of the scanning facet and the elevation and skew angles of the diffracted laser beam, (iii) scattered/reflected as it scans its target (e.g. a bar code symbol), and the scattered/reflected light rays, and (iv) collected by the light collecting area of the scanning facet;



Fig. 12D is a schematic representation graphically illustrating the process of projecting (i) a first parallel set of vectors from an exemplary scanning facet onto the first geometrically-untrimmed planar beam folding mirror associated with a laser scanning station as an incident laser beam is diffracted by the first end portion of the scanning facet as shown in Fig. 12C1, and (ii) a second parallel set of vectors from the scanning facet onto the first geometrically-untrimmed planar beam folding mirror as the incident laser beam is diffracted by the second end portion of the scanning facet as shown in Fig. 12C2, wherein each vector in the first parallel set of vectors emanates from a different assigned vertex on the scanning facet in a direction parallel to the first diffracted laser beam, and each vector in the second parallel set of vectors emanates from a different assigned vertex on the scanning facet in a direction parallel to the second diffracted laser beam, and wherein the first parallel set of vectors collectively define the light collection area of the scanning facet at the first end (i.e. beginning) of the laser scanning plane being generated, the second parallel set of vectors collectively define the light collection area of the scanning facet at the second end (i.e. beginning) of the laser scanning plane being generated, and the points at which these vectors intersect the first geometrically-untrimmed planar beam folding mirror are used to specify the geometrical boundaries that the final (i.e. geometrically-trimmed) planar beam folding mirror should embody for performing light reflection/collection functions during laser scanning beam operations;

Fig. 13A1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 8, 10 and 12, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 8, 10 and 12 projected onto the first non-trimmed planar beam folding mirror in the first mirror group G1 employed in the first laser scanning station ST1;

Fig. 13A2 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 7, 9, and 11, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 7, 9 and 11 projected onto the first non-trimmed planar beam folding mirror in the second mirror group G2 employed in the first laser scanning station ST1;

Fig. 13A3 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 1-4, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 1-4 projected onto the first non-trimmed planar beam folding mirror in the third mirror group G3 employed in the first laser scanning station ST1;

Fig. 13A4 is a graphical plot showing, in the XY plane of the first local coordinate system R1, (i) the projection of the vertices of scanning facet Nos. 8, 10 and 12 onto the first untrimmed planar beam folding mirror in the first mirror group G1 employed at the first laser scanning station ST1, (ii) the projection of the vertices of scanning facet Nos. 7, 9 and 11 onto the first untrimmed planar beam folding mirror in the second mirror group G2 employed at the first laser scanning station ST1, and (iii) the projection of the vertices of scanning facet Nos. 1-4

1 onto the first untrimmed planar beam folding mirror in the third mirror group G3 employed at the  
2 first laser scanning station ST1;

3 Fig. 13A5 is a graphical plot showing, in the XZ plane of the first local coordinate system  
4 R1, (i) the projection of the vertices of scanning facet Nos. 8, 10 and 12 onto the first untrimmed  
5 planar beam folding mirror in the first mirror group G1 employed at the first laser scanning  
6 station ST1, (ii) the projection of the vertices of scanning facet Nos. 7, 9 and 11 onto the first  
7 untrimmed planar beam folding mirror in the second mirror group G2 employed at the first laser  
8 scanning station ST1, and (iii) the projection of the vertices of scanning facet Nos. 1-4 onto the  
9 first untrimmed planar beam folding mirror in the third mirror group G3 employed at the first  
10 laser scanning station ST1;

11 Fig. 13A6 is a graphical plot showing, in the YZ plane of the first local coordinate system  
12 R1, (i) the projection of scanning facet Nos. 8, 10 and 12 onto the first untrimmed planar beam  
13 folding mirror in the first mirror group G1 employed at the first laser scanning station ST1, (ii)  
14 the projection of scanning facet Nos. 7, 9 and 11 onto the first untrimmed planar beam folding  
15 mirror in the second mirror group G2 employed at the first laser scanning station ST1, and (iii)  
16 the projection of scanning facet Nos. 1-4 onto the first untrimmed planar beam folding mirror in  
17 the third mirror group G3 employed at the first laser scanning station ST1;

18 Fig. 13B1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation  
19 and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of  
20 scanning facet Nos. 8, 10 and 12, the middle portion of these scanning facets, and the end (i.e.  
21 second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of  
22 scanning facet Nos. 8, 10 and 12 projected onto the second non-trimmed planar beam folding  
23 mirror in the first mirror group G1 employed in the first laser scanning station ST1;

24 Fig. 13B2 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation  
25 and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of  
26 scanning facet Nos. 7, 9, and 11, the middle portion of these scanning facets, and the end (i.e.  
27 second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of  
28 scanning facet Nos. 7, 9 and 11 projected onto the second non-trimmed planar beam folding  
29 mirror in the second mirror group G2 employed in the first laser scanning station ST1;

30 Fig. 13B3 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation  
31 and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of  
32 scanning facet Nos. 1-4, the middle portion of these scanning facets, and the end (i.e. the second  
33 end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning  
34 facet Nos. 1-4 projected onto the second non-trimmed planar beam folding mirror in the third  
35 mirror group G3 employed in the first laser scanning station ST1;

36 Fig. 13B4 is a graphical plot showing, in the XY plane of the first local coordinate system  
37 R1, (i) the projection of the vertices of scanning facet Nos. 8, 10 and 12 onto the second  
38 untrimmed planar beam folding mirror in the first mirror group G1 employed at the first laser  
39 scanning station ST1, (ii) the projection of the vertices of scanning facet Nos. 7, 9 and 11 onto  
40 the second untrimmed planar beam folding mirror in the second mirror group G2 employed at  
41 the first laser scanning station ST1, and (iii) the projection of the vertices of scanning facet Nos.

1-4 onto the second untrimmed planar beam folding mirror in the third mirror group G3 employed at the first laser scanning station ST1;

Fig. 13B5 is a graphical plot showing, in the XZ plane of the first local coordinate system R1, (i) the projection of the vertices of scanning facet Nos. 8, 10 and 12 onto the second untrimmed planar beam folding mirror in the first mirror group G1 employed at the first laser scanning station ST1, (ii) the projection of the vertices of scanning facet Nos. 7, 9 and 11 onto the second untrimmed planar beam folding mirror in the second mirror group G2 employed at the first laser scanning station ST1, and (iii) the projection of the vertices of scanning facet Nos. 1-4 onto the second untrimmed planar beam folding mirror in the third mirror group G3 employed at the first laser scanning station ST1;

Fig. 13B6 is a graphical plot showing, in the YZ plane of the first local coordinate system R1, (i) the projection of scanning facet Nos. 8, 10 and 12 onto the first untrimmed planar beam folding mirror in the first mirror group G1 employed at the first laser scanning station ST1, (ii) the projection of scanning facet Nos. 7, 9 and 11 onto the first untrimmed planar beam folding mirror in the second mirror group G2 employed at the first laser scanning station ST1, and (iii) the projection of scanning facet Nos. 1-4 onto the second untrimmed planar beam folding mirror in the third mirror group G3 employed at the first laser scanning station ST1;

Fig. 13C1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 8, 10 and 12, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 8, 10 and 12 projected onto the third non-trimmed planar beam folding mirror in the first mirror group G1 employed in the first laser scanning station ST1;

Fig. 13C2 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 7, 9, and 11, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 7, 9 and 11 projected onto the third non-trimmed planar beam folding mirror in the second mirror group G2 employed in the first laser scanning station ST1;

Fig. 13C3 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 1-4, the middle portion of these scanning facets, and the second end (i.e. the end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 1-4 projected onto the third non-trimmed planar beam folding mirror in the third mirror group G3 employed in the first laser scanning station ST1;

Fig. 13C4 is a graphical plot showing, in the XY plane of the first local coordinate system R1, (i) the projection of the vertices of scanning facet Nos. 8, 10 and 12 onto the third untrimmed planar beam folding mirror in the first mirror group G1 employed at the first laser scanning station ST1, (ii) the projection of the vertices of scanning facet Nos. 7, 9 and 11 onto the third untrimmed planar beam folding mirror in the second mirror group G2 employed at the first laser scanning station ST1, and (iii) the projection of the vertices of scanning facet Nos. 1-4 onto the

1 first untrimmed planar beam folding mirror in the third mirror group G3 employed at the first  
2 laser scanning station ST1;

3 Fig. 13C5 is a graphical plot showing, in the XZ plane of the first local coordinate system  
4 R1, (i) the projection of the vertices of scanning facet Nos. 8, 10 and 12 onto the third untrimmed  
5 planar beam folding mirror in the first mirror group G1 employed at the first laser scanning  
6 station ST1, (ii) the projection of the vertices of scanning facet Nos. 7, 9 and 11 onto the third  
7 untrimmed planar beam folding mirror in the second mirror group G2 employed at the first laser  
8 scanning station ST1, and (iii) the projection of the vertices of scanning facet Nos. 1-4 onto the  
9 third untrimmed planar beam folding mirror in the third mirror group G3 employed at the first  
10 laser scanning station ST1;

11 Fig. 13C6 is a graphical plot showing, in the YZ plane of the first local coordinate system  
12 R1, (i) the projection of scanning facet Nos. 8, 10 and 12 onto the third untrimmed planar beam  
13 folding mirror in the first mirror group G1 employed at the first laser scanning station ST1, (ii)  
14 the projection of scanning facet Nos. 7, 9 and 11 onto the third untrimmed planar beam folding  
15 mirror in the second mirror group G2 employed at the first laser scanning station ST1, and (iii)  
16 the projection of scanning facet Nos. 1-4 onto the third untrimmed planar beam folding mirror in  
17 the third mirror group G3 employed at the first laser scanning station ST1;

18 Fig. 13D1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation  
19 and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of  
20 scanning facet Nos. 8, 10 and 12, the middle portion of these scanning facets, and the end (i.e.  
21 the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of  
22 scanning facet Nos. 8, 10 and 12 projected onto the fourth non-trimmed planar beam folding  
23 mirror in the first mirror group G1 employed in the first laser scanning station ST1;

24 Fig. 14A1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation  
25 and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of  
26 scanning facet Nos. 1-6, the middle portion of these scanning facets, and the end (i.e. second  
27 end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning  
28 facet Nos. 1-6 projected onto the first non-trimmed planar beam folding mirror in the first mirror  
29 group G1 employed in the second laser scanning station ST2;

30 Fig. 14B1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation  
31 and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of  
32 scanning facet Nos. 1-6, the middle portion of these scanning facets, and the end (i.e. the second  
33 end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning  
34 facet Nos. 1-6 projected onto the second non-trimmed planar beam folding mirror in the mirror  
35 group G3 employed in the second laser scanning station ST2;

36 Fig. 14C1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation  
37 and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of  
38 scanning facet Nos. 1-6, the middle portion of these scanning facets, and the second end (i.e. the  
39 end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning  
40 facet Nos. 1-6 projected onto the third non-trimmed planar beam folding mirror in the mirror  
41 group G3 employed in the second laser scanning station ST2;

Fig. 14D1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 1-6, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 1-6 projected onto the fourth non-trimmed planar beam folding mirror in the mirror group G3 employed in the second laser scanning station ST2;

Fig. 15A1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 8, 10 and 12, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 8, 10 and 12 projected onto the first non-trimmed planar beam folding mirror in the first mirror group G1 employed in the fourth laser scanning station ST4;

Fig. 15A2 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 7, 9, and 11, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 7, 9 and 11 projected onto the first non-trimmed planar beam folding mirror in the second mirror group G2 employed in the fourth laser scanning station ST4;

Fig. 15A3 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 1-6, the middle portion of these scanning facets, and the second end (i.e. the end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 1-6 projected onto the first non-trimmed planar beam folding mirror in the third mirror group G3 employed in the fourth laser scanning station ST4;

Fig. 15B1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 8, 10 and 12, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 8, 10 and 12 projected onto the second non-trimmed planar beam folding mirror in the first mirror group G1 employed in the fourth laser scanning station ST4;

Fig. 15B2 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 7, 9, and 11, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 7, 9 and 11 projected onto the second non-trimmed planar beam folding mirror in the second mirror group G2 employed in the fourth laser scanning station ST4;

Fig. 15B3 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 1-6, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 1-6 projected onto the second non-trimmed planar beam folding mirror in the third mirror group G3 employed in the fourth laser scanning station ST4;

Fig. 15C1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 8, 10 and 12, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 8, 10 and 12 projected onto the third non-trimmed planar beam folding mirror in the first mirror group G1 employed in the fourth laser scanning station ST4;

Fig. 15C2 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 7, 9, and 11, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 7, 9 and 11 projected onto the third non-trimmed planar beam folding mirror in the second mirror group G2 employed in the fourth laser scanning station ST4;

Fig. 15C3 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 1-6, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 1-6 projected onto the third non-trimmed planar beam folding mirror in the third mirror group G3 employed in the fourth laser scanning station ST4;

Fig. 15D1 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 8, 10 and 12, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 8, 10 and 12 projected onto the fourth non-trimmed planar beam folding mirror in the first mirror group G1 employed in the fourth laser scanning station ST4;

Fig. 15D2 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 7, 9, and 11, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 7, 9 and 11 projected onto the fourth non-trimmed planar beam folding mirror in the second mirror group G2 employed in the fourth laser scanning station ST4;

Fig. 15D3 is a spreadsheet table listing (i) the (x,y,x) coordinates specifying the elevation and skew angles of the diffracted laser beams produced at the start (i.e. first end) portion of scanning facet Nos. 1-6, the middle portion of these scanning facets, and the end (i.e. the second end) portion of the scanning facets, and (ii) the (x,y,z) coordinates of the vertices of scanning facet Nos. 1-6 projected onto the fourth non-trimmed planar beam folding mirror in the third mirror group G3 employed in the fourth laser scanning station ST4;

Figs. 16A, 16B and 16C provide a flow chart describing a method of designing a light collection and detection subsystem for a bioptical holographic scanner according to the principles of the present invention;

Fig. 17A is an elevated end view of the bioptical holographic laser scanning system of the illustrative embodiment, showing that, at each laser scanning station, the photodetector is disposed above the point of incidence on the holographic scanning disc, whereas the parabolic

1 light focusing mirror is disposed beneath the holographic scanning disc, in order to reduce the  
2 height dimension of the bottom portion of the scanner housing;

3 Fig. 17B is a 3-D wire-frame type geometrical optics model of the parabolic mirror,  
4 photodetector and scanning disc assembly associated with each laser scanning station in the  
5 holographic scanning system of the present invention under design;

6 Fig. 17C is a ray optics diagram showing the paths of the innermost and outermost light  
7 rays collected by a holographic scanning facet on the scanning disc associated with the light  
8 detection subsystem of the present invention depicted in Fig. 17A; and

9 Fig. 18 is a schematic representation of an alternative embodiment of the holographic  
10 laser scanning system of the present invention, wherein only a bottom scanning window is  
11 provided in a system having only a bottom portion.

12  
13  
14 DETAILED DESCRIPTION OF THE ILLUSTRATIVE  
15 EMBODIMENTS OF THE PRESENT INVENTION  
16

17 Referring to the figures in the accompanying Drawings, the various illustrative  
18 embodiments of the bioptical holographic laser scanner of the present invention will be described  
19 in great detail.

20 In the illustrative embodiments, the apparatus of the present invention is realized in the  
21 form of an automatic code symbol reading system having a high-speed bioptical holographic  
22 laser scanning mechanism as well as a scan data processor for decode processing scan data  
23 signals produced thereby. However, for the sake of convenience of expression, the term  
24 "bioptical holographic laser scanner" shall be used hereinafter to denote the bar code symbol  
25 reading system which employs the bioptical holographic laser scanning mechanism of the  
26 present invention.

27 As shown in Fig. 1A, the bioptical holographic laser scanner of the first illustrative  
28 embodiment of the present invention 1 has a compact housing 2 having a first housing portion  
29 4A, and a second housing portion 4B which projects from one end of the first housing portion in  
30 an orthogonal manner. When the holographic laser scanner 1 is installed within a counter-top  
31 surface, as shown in Fig. 1B1 and 1B2, the first housing portion 4A oriented horizontally,  
32 whereas the second housing portion 4B is oriented vertically with respect to the POS station.  
33 Thus throughout the Specification and Claims hereof, the terms first housing portion and  
34 horizontally-disposed housing portion may be used interchangeably but refer to the same  
35 structure; likewise, the terms the terms second housing portion and vertically-disposed housing  
36 portion may be used interchangeably but refer to the same structure.

37 In the illustrative embodiment, the total height of the scanner housing is 8.73 inches, with  
38 width and length dimensions of 10.90 and 14.86 inches, respectively, to provide a total internal  
39 housing volume ("scanner volume")  $V_{\text{housing}}$  of about 1624.3 cubic inches with a scanner housing  
40 depth of 3.41 inches. As will be described in greater detail below, the total three-dimensional  
41 scanning volume produced by this ultra-compact housing is about 432 cubic inches with a  
42 scanning depth of field of about 6.0 inches measured from the bottom scanning window 16 and

1 about 8.0 inches measured from the side scanning window 18. Importantly, the resolution of the  
2 bar code symbol that the scanning pattern of the illustrative embodiment can resolve at any  
3 location within the specified three-dimensional laser scanning volume  $V_{\text{scanning}}$  is on the order of  
4 about 0.006 inches minimum element width. It is understood, however, this scanning resolution  
5 may be greater or lesser depending on the particular embodiment of the present invention.

6 Note that in the illustrative embodiment, the depth of the first housing portion 4A (which  
7 is disposed under the counter in a POS retail application) is less than 5 inches, and preferably  
8 less than 3.5 inches. Moreover, the volume of the scanner housing is less than 1650 cubic  
9 inches, and the 3-D scanning volume produced by the scanning system is greater than 400 cubic  
10 inches. Such a design reduces the depth of the scanner housing, which is a key benefit in a space  
11 constrained environment such as in POS retail applications.

12 In the illustrative embodiment, the base of the first housing portion 4A is recessed (with  
13 respect to the top of the first housing portion 4A) as shown in Fig. 1A1 and 1A2.

14 The bioptical holographic laser scanning bar code symbol reading system of the present  
15 invention 1 shown in Fig. 1A can be used in a diverse variety of bar code symbol scanning  
16 applications. As shown in Fig. 1B1, the bioptical holographic laser scanner 1 can be installed  
17 within the countertop of a point-of-sale (POS) station 26, having a computer-based cash register  
18 20, a weigh-scale 22 mounted within the counter adjacent the laser scanner, and an automated  
19 transaction terminal (ATM) supported upon a courtesy stand in a conventional manner.  
20 Similarly, as shown in Fig. 1B2, the bioptical holographic laser scanner 1 can be mounted on  
21 weigh-scale 22, and the scanner/weigh-scale combination installed within the countertop of a  
22 point-of-sale (POS) station 26 having a computer-based cash register 20 and an automated  
23 transaction terminal (ATM) supported upon a courtesy stand in a conventional manner. In this  
24 configuration, items (such as fruit or other produce) that need to be weighed are placed on the  
25 first housing portion 4A of the scanner 1 where they are weighed by the weigh-scale 22 disposed  
26 beneath the scanner 1.

27 Alternatively, as shown in Fig. 1C, the bioptical holographic laser scanner can be  
28 installed above a conveyor belt structure as part of a manually-assisted parcel sorting operation  
29 being carried out, for example, during inventory control and management operations.

30 As shown in Figs. 1D1, 1E, 2A1, 2B, 2B2 and 2C1, the bioptical holographic scanning  
31 system of the illustrative embodiment comprises a holographic scanning disc 30 mounted on an  
32 optical bench 32; first, second, third and fourth laser scanning stations indicated by ST1, ST2,  
33 ST3 and ST4, respectively, and symmetrically arranged about the holographic laser scanning  
34 station at different angular locations. As will be described in greater detail hereinafter, each laser  
35 scanning generates a laser scanning beam that is directed through a different, yet fixed point of  
36 incidence on laser scanning disc 30. As shown in Fig. 2B1, the point of incidences associated  
37 with the second and fourth laser scanning stations ST2 and ST4 are aligned with a (central)  
38 longitudinal reference axis LRA disposed within the central plane of the scanning disc and  
39 bisecting both the bottom and vertical housing portions of the holographic laser scanning system.  
40 As shown in Fig 2B1, the first and third laser scanning stations ST1 and ST3 are disposed on  
41 opposite sides of the longitudinal reference axis, and are aligned with a transverse reference axis



1 TRA , also disposed within the central plane of the scanning disc, and passing through the points  
2 of incidence associated with the first and third laser scanning stations ST3 and ST4, as shown.

3 As will be described in greater detail hereinafter, the position, geometry and orientation  
4 of each of the subcomponents of each laser scanning station are locally defined with respect to a  
5 hybrid Cartesian/Polar coordinate reference system symbolically embedded within the  
6 holographic scanning disc. Thus, four locally-defined (*hybrid Cartesian/Polar*) coordinate  
7 reference systems  $R_{local\ 1}$ ,  $R_{local\ 2}$ ,  $R_{local\ 3}$  and  $R_{local\ 4}$  are used to specify the position, geometry  
8 and orientation of each of the subcomponents of the first, second, third and fourth laser scanning  
9 stations ST1, ST2, ST3, and ST4, respectively. However, as will be described in detail  
10 hereinafter, each of these coordinate measurements eventually must be translated back to a  
11 globally-defined coordinate reference system  $R_{global}$  symbolically embedded within the  
12 holographic scanning disc of the system. As shown in Fig. 2A1, the global coordinate reference  
13 system  $R_{global}$  is symbolically embedded within holographic scanning system as follows: the x  
14 and y axes of the global coordinate reference system extend within the central plane of the  
15 holographic scanning disc, such that the x axis is aligned with the transverse reference axis TRA  
16 passing through the point of incidences associated with the first and third laser scanning stations  
17 ST3 and ST4, the y axis is aligned with the longitudinal reference axis LRA passing through the  
18 point of incidences associated with the second and fourth laser scanning stations ST2 and ST4,  
19 while the z axis of the global coordinate reference system is aligned with the axis of rotation of  
20 the holographic scanning disc.

21 With the global coordinate reference system symbolically embedded within the  
22 holographic scanning system, as defined hereinabove, each of the four locally defined coordinate  
23 reference frames  $R_{local\ 1}$ ,  $R_{local\ 2}$ ,  $R_{local\ 3}$  and  $R_{local\ 4}$  are defined as follows: the first local  
24 coordinate reference system  $R_{local\ 1}$  is aligned with the global coordinate reference system  $R_{global}$ ;  
25 the second local coordinate reference system  $R_{local\ 2}$  is rotated 90 degrees counter-clockwise in  
26 the X-Y plane of the global coordinate reference system  $R_{global}$ , so that its x axis of  $R_{local\ 2}$  is  
27 aligned with the point of incidence associated with the second laser scanning station ST2 ; the  
28 third local coordinate reference system  $R_{local\ 3}$  is rotated 180 degrees counter-clockwise in the X-  
29 Y plane of the global coordinate reference system  $R_{global}$ , so that the x axis of  $R_{local\ 3}$  is aligned  
30 with the point of incidence associated with the third laser scanning station ST3; and the fourth  
31 local coordinate reference system  $R_{local\ 4}$  is rotated 270 degrees counter-clockwise in the X-Y  
32 plane of the global coordinate reference system  $R_{global}$ , so that the x axis of  $R_{local\ 4}$  is aligned with  
33 the point of incidence associated with the fourth laser scanning station ST4. Coordinate values  
34 of points specified in any one of these local coordinate reference systems using vectors  
35 referenced therefrom can be converted into corresponding coordinate values referenced with  
36 respect to the global coordinate reference system  $R_{global}$  using homogeneous transformations  
37 known in the art 3-D geometrical modeling art.

38 The holographic scanning disc 30 employed in the system hereof comprises two glass  
39 plates 32A and 32B, between which are supported a plurality of specially designed holographic  
40 optical elements (HOEs), referred to hereinafter as "holographic scanning facets" or  
41 "holographic facets". In the illustrative embodiments, twelve holographic scanning facets are  
42 supported on the scanning disc. Each holographic facet 34 is preferably realized as a volume

1 transmission-type light diffraction hologram having a slanted fringe structure having variations  
2 in spatial frequency to provide a characteristic focal length  $f_i$ . The light diffraction efficiency of  
3 such volume light diffraction holograms, as a function of incidence angle  $A_i$ , modulation depth  
4  $\Delta n_i$ , or recording media losses, is described in great detail in the celebrated paper entitled  
5 "Coupled Wave Theory for Thick Hologram Gratings" by Herwig Kogelnik, published in The  
6 Bell System Technical Journal (BSTJ), Volume.8, Number 9, at Pages 2909-2947, in November  
7 1969, incorporated herein by reference in its entirety.

8 In a conventional manner, the glass support plates 32A and 32B forming part of the  
9 holographic scanning disc hereof are mounted to a support hub, as shown in Figs. 1D1, and 2A2.  
10 In turn, the support hub 2 is mounted to the shaft of a high-speed, electric motor 40. For  
11 purposes of simplicity of description, when describing the laser scanning stations of the present  
12 invention, reference will be made to the first laser scanning station denoted as ST1. While the  
13 beam folding mirror arrangement employed in laser scanning stations ST1, ST3 and ST4 are  
14 quite different, as will be described in great detail hereinafter, the beam folding mirror  
15 arrangement of the third laser scanning station ST3 is similar to the beam folding mirror  
16 arrangement employed in laser scanning station ST1, except that the location of these mirror  
17 arrangements about the transverse reference axis TRA are reversed. Despite such differences,  
18 the laser scanning stations ST2, ST3 and ST4 have substantially similar structure, and operate in  
19 substantially the same manner as the first laser scanning station ST1. Thus, when describing the  
20 components which each of the laser scanning stations have in common, reference will be made to  
21 the first laser station, for purpose of illustration and compact description.

22 As best shown in Fig. 3A1, the holographic facets on holographic scanning disc 30 are  
23 arranged on the surface thereof in a manner which utilizes substantially all of the light collecting  
24 surface area provided between the outer radius of the scanning disc,  $r_{outer}$ , and the inner radius  
25 thereof,  $r_{inner}$ . In the illustrative embodiment, twelve (12) holographic scanning facets are used in  
26 conjunction with the four independent laser beam sources provided by the four laser scanning  
27 stations of the system, so as to project from the bottom and side scanning windows of the system,  
28 an omni-directional laser scanning pattern consisting of 50 laser scanning planes cyclically  
29 generated at a rate in excess of 1000 times per second. It is understood, however, this number  
30 will vary from embodiment to embodiment of the present invention and thus shall not form a  
31 limitation thereof.

32 In the illustrative embodiment of the present invention, there are three different types of  
33 facets on the holographic scanning disc hereof. These facet types are based on (i) beam  
34 elevation angle characteristics of the facet, and (ii) skew angle characteristics thereof,  
35 schematically defined in Figs. 3A2 and 3A3, respectively. As shown in the table of Fig. 3A4, the  
36 first class of facets have High Elevation (HE) angle characteristics and Left (i.e. positive) Skew  
37 (LS) angle characteristics; the second class of facets have High Elevation (HE) angle  
38 characteristics and Right (i.e. negative) Skew (RS) angle characteristics; and the third class of  
39 facets have Low Elevation (LE) angle characteristics and no (i.e. zero) Skew (LS) angle  
40 characteristics. As shown in Figs. 3A2 and 3A3, skew angle characteristics are referenced by  
41 counter-clockwise rotation within the local coordinate reference system of interest. Thus, left  
42 (i.e. positive) skew angle characteristics are indicated when the plane, within which the outgoing

1 laser beam is diffracted, deflects towards to left side of the XZ plane as the scanning facets  
2 sweeps across the point of incidence of the associated laser scanning station, whereas right (i.e.  
3 negative) skew angle characteristics are indicated when he plane, within which the outgoing laser  
4 beam is diffracted, deflects towards to right side of the XZ plane as the scanning facets sweeps  
5 across the point of incidence of the associated laser scanning station. No (i.e. zero) skew angle  
6 characteristics are indicated when the plane, within which the outgoing laser beam is diffracted,  
7 is deflected towards neither the left or right side of the XZ plane as the scanning facets sweeps  
8 across the point of incidence of the associated laser scanning station, but rather remains centrally  
9 disposed about the XZ plane. As will become apparent hereinafter, the use of holographic  
10 scanning facets having such diverse elevation and skew characteristics enables the design and  
11 construction of a bioptical holographic laser scanning system employing multiple laser scanning  
12 stations, each having a plurality of beam folding mirrors that are compactly arranged within a  
13 minimized region of volumetric space, required in space-constricted POS-type scanning  
14 applications.

15 Laser beams passing through scanning facets having High Elevation (HE) angle  
16 characteristics and Left (i.e. positive) Skew (LS) angle characteristics are deflected towards the  
17 beam folding mirrors arranged on the left side of hosting laser scanning station, at a high  
18 elevation angle (or low diffraction angle by definition). Laser beams passing through scanning  
19 facets having High Elevation (HE) angle characteristics and Right (i.e. negative) Skew (RS)  
20 angle characteristics are deflected towards the beam folding mirrors arranged on the right side of  
21 hosting laser scanning station, at a high elevation angle (or low diffraction angle by definition).  
22 Laser beams passing through scanning facets having Low Elevation (LE) angle characteristics  
23 and No Skew (LS) angle characteristics are not deflected towards either side of hosting laser  
24 scanning station, at a low elevation angle (or high diffraction angle by definition), but instead  
25 remain centered about the point of incidence at the laser scanning station.

26 As schematically illustrated in Fig. 3A1, each facet on the holographic scanning disc 30  
27 is assigned a unique facet number. As indicated in the table of Fig. 3A4, scanning facets  
28 assigned numbers 7, 9 and 11 in the illustrative design are classified into a first facet group (i.e.  
29 class) indicated by G1, as each scanning facet in this first facet group has both High Elevation  
30 (HE) angle characteristics and Left ( i.e. negative) Skew (LS) angle characteristics as indicated in  
31 the spreadsheet disc design parameter table of Figs. 3G1 and 3G2. Facets assigned numbers 8,  
32 10 and 12 are classified into a second facet group indicated by G2, as each scanning facet in this  
33 second facet group has both High Elevation (HE) angle characteristics and Right Skew (RS)  
34 angle characteristics, as indicated in the spreadsheet disc design parameter table of Figs. 3G1 and  
35 3G2. Facets assigned numbers 1-6 are classified into the third facet group, as each scanning  
36 facet in this third facet group has both Low Elevation (LE) angle characteristics and Left Skew  
37 (LS) angle characteristics, as indicated in the spreadsheet disc design parameter table of Figs.  
38 3G1 and 3G2. By virtue of such characteristics, the scanning facets in each of these three  
39 different facet groups produces an outgoing laser beam that is diffracted along a different  
40 direction of skew, and therefore, is designed to cooperate with a different group of laser beam  
41 folding mirrors in order to generate particular components of the complex omnidirectional laser

1 scanning pattern of the present invention. Such features of the bioptical holographic scanning  
2 system of the present invention will be illustrated in great detail hereinafter.

3 In addition, the holographic scanning disc 30 preferably includes scanning facets with  
4 symmetrical LS and RS angle characteristics. For example, as illustrated in Fig. 3A4 and 3G2,  
5 facets 7, 9 and 11 have LS angle characteristics (+28 degrees) that are symmetrical with respect  
6 to the RS angle characteristics (-28 degrees) of facets 8, 10 and 12, respectively. Such features  
7 enable different laser scanning stations to produce substantially similar scanning patterns. Figs.  
8 5B4 and 5L3 illustrate this feature. More specifically, Fig. 5B4 illustrates the scanning pattern  
9 produced by facets 7, 9 and 11 in cooperation with laser scanning station ST1. Fig. 5L3  
10 illustrates the scanning pattern produced by facets 8, 10 and 12 in cooperation with laser scanning  
11 station ST3. Note that these two scanning patterns are substantially similar as shown.

12 As best shown in Figs. 1D1, 1E, 2B2, 2C1, 2K, 2N, and 2O, the first laser scanning  
13 station (ST1) comprises: a first laser beam production module 41A mounted on the optical bench  
14 42 of the system, preferably outside the outer periphery of the holographic scanning disc 30, as  
15 shown in Fig. 2A2 and 2B2; a first laser beam directing mirror 43A, disposed beneath the edge  
16 of the scanning disc, below the first point of incidence associated with the first scanning station  
17 ST1, for directing the laser beam output from the first laser beam production module 41A,  
18 through the first point of incidence at a fixed angle of incidence which, as indicated in the  
19 spreadsheet of Fig. 3F, is substantially equal for each laser scanning station in the system; three  
20 groups of laser beam folding mirrors, MG1@ST1, MG2@ST1 and MG3@ST1 which are  
21 arranged about the first point of incidence at the first scanning station ST1, and cooperate with  
22 the three groups of scanning facets G1, G2 and G3 on the scanning disc, respectively, so as to  
23 generate and project different groups of laser scanning planes through the bottom scanning  
24 window 16, as graphically illustrated in Figs. 5B1 through 5H5, and vectorally specified in Figs.  
25 6A1 through 6C5; a first light collecting/focusing mirror structure (e.g. parabolic light collecting  
26 mirror or parabolic surface emulating volume reflection hologram) 70A disposed beneath  
27 holographic scanning disc 30 adjacent the first laser beam directing mirror 43A and first point of  
28 incidence at scanning station ST1; a first photodetector 45A disposed substantially above the  
29 first point of incidence at scanning station ST1 at a predetermined (i.e. minimized) height above  
30 the holographic scanning disc 30; and a first set of analog and digital signal processing boards 50  
31 and 55, associated with the first laser scanning station ST1, and mounted within the compact  
32 scanner housing, for processing analog and digital scan data signals as described in detail in  
33 Applicants' US Patent Application Serial No. 08/949,915 filed October 14, 1997, and  
34 incorporated herein by reference, incorporated herein by reference in its entirety.

35 For purposes of illustration and conciseness of description, each laser beam folding  
36 mirror in each mirror group arranged at each laser scanning station ST1, ST2, ST3 and ST4, is  
37 assigned a unique mirror identification code (i.e. indicator) throughout the drawings hereof.  
38 Each mirror identification code conforms to the syntactical structure  $M_{i,j,k}$ , wherein: index i  
39 represents the scanning station number (e.g. i=1 for ST1); index j represents the mirror group  
40 number (e.g. j=1 for mirrors which cooperate with scanning facets in group G1); and index k  
41 represents the mirror number in the mirror group assigned by the sequential order that the  
42 outgoing laser beam reflects off the mirrors during the laser scanning plane generation process

(e.g.  $k=1$  for mirrors which cause an outgoing laser beam to undergo its first reflection after diffracting through a scanning facet).

Referring to Figs. 2K, 2N, 2O and 3B and using the mirror identification conventions set forth above, the laser beam folding mirrors employed at the first scanning station ST1 can be conveniently indexed as follows: mirror group MG1@ST1, containing facets that generate left skewed outgoing laser beams, has two beam folding mirrors indicated by  $M_{1,1,1}$ , and  $M_{1,1,2}$  in Figs. 5B1 through 5C5, and 6A1 through 6A4; mirror group MG2@ST1, containing facets that generate right skewed outgoing laser beams, has three beam folding mirrors indicated by  $M_{1,2,1}$ ,  $M_{1,2,2}$  and  $M_{1,2,3}$  in Figs. 5B1 through 5H5, and 6D1 through 6E5; and mirror group MG3@ST1, containing facets that do not generate skewed outgoing laser beams, has two beam folding mirrors indicated by  $M_{1,3,1}$ , and  $M_{1,3,2}$  in Figs. 5F1 through 5G5, and 6C1 through 6C5.

The position and orientation of each beam folding mirror employed at scanning station ST1 relative to the first locally-defined coordinate reference system  $R_{local\ 1}$  is specified by a set of position vectors pointing from the from the origin of this local coordinate reference system to the vertices of each such beam folding mirror element (i.e. light reflective surface patch) which has been optimized in terms of occupying a minimal volume within the scanner housing without compromising the performance of its beam folding function. The x,y,z coordinates of these vertex-specifying vectors are set forth in the spreadsheet table of Figs. 3B, organized according to the three mirror groups MG1@ST1, MG2@ST1 and MG3@ST1 employed at laser scanning station ST1. Notably, the first vertex of each facet in these mirror groups is repeated in the table of Fig. 3B, to traverse a closed path in 3-D space, specifying the perimetrical boundaries of these optimally-trimmed beam folding mirrors employed in the scanning system of the illustrative embodiment.

As shown in Fig. 3B, the mirrors in each mirror group of scanning station ST1 are arranged in the order that the beam folding mirror performs its beam folding (i.e. light reflection) function upon the outgoing diffracted laser beam produced by a scanning facet associated with a facet group corresponding to the mirror group. Notably, at scanning station ST1, two light reflection operations are performed by the mirror groups MG1@ST1 and MG3@ST1 upon the outgoing diffracted laser beams, whereas three light reflection operations are performed by mirror group MG2@ST1 upon the outgoing diffracted laser beams. Also, certain beam reflecting mirrors (e.g.  $M_{1,1,1}$  and  $M_{1,1,2}$ ) have six vertices, while some mirrors have four vertices (e.g.  $M_{1,3,2}$  and  $M_{1,1,2}$ ), and yet other mirrors (e.g.  $M_{1,1,2}$ ) have five vertices. As will be described in greater detail hereinafter, the exact number of vertices of each beam folding mirror will depend on the laser scanning plane being generated by the outgoing laser beam, the geometrical characteristics of the overall 3-D scanning pattern to be generated from the holographic scanning system in the particular scanning application at hand, and physical constraints within the scanner housing. Also, while the coordinate values for the vertices of each beam folding mirror specify the surface area, position and orientation of each mirror employed in the first laser scanning station ST1, it is understood that other mirror surface areas, positions and orientations can and may be used to realize other embodiments of the first laser scanning station ST1 in accordance with the principles of the present invention taught herein.

As best shown in Figs. 1D1, 1E, 2B2, 2C1 and 2L, the second laser scanning station (ST2) comprises: a second laser beam production module 41B mounted on the optical bench 42 of the system, preferably outside the outer periphery of the holographic scanning disc 30, as shown in Fig. 2A2 and 2B2; a second laser beam directing mirror 43B, disposed beneath the edge of the scanning disc, below the second point of incidence associated with the second scanning station ST2, for directing the laser beam output from the first laser beam production module 41B, through the first point of incidence at a fixed angle of incidence; one group of laser beam folding mirrors, MG3@ST2, which are arranged about the second point of incidence at the second scanning station ST2, and cooperate with the corresponding group of scanning facets G3 on the scanning disc so as to generate and project different groups of laser scanning planes through the bottom scanning window 16, as graphically illustrated in Figs. 5I1 through 5J5, and vectorally specified in Figs. 6D1 through 6D7; a second light collecting/focusing mirror structure (e.g. parabolic light collecting mirror or parabolic surface emulating volume-type hologram) 70B disposed beneath holographic scanning disc 30 adjacent the second laser beam directing mirror 43B and the second point of incidence at scanning station ST2; a second photodetector 45B disposed substantially above the second point of incidence at scanning station ST2 at a predetermined (i.e. minimized) height above the holographic scanning disc 30; and a second set of analog and digital signal processing boards 50B and 55B, associated with the second laser scanning station ST2, and mounted within the compact scanner housing, for processing analog and digital scan data signals as described in detail in Applicants' US Patent Application Serial No. 08/949,915 filed October 14, 1997, and incorporated herein by reference, incorporated herein by reference in its entirety.

Referring to Figs. 2L and 3C and using the mirror identification conventions disclosed above, the laser beam folding mirrors employed at the second scanning station ST2 can be conveniently indexed as follows: mirror group MG3@ST2, containing facets that do not generate skewed outgoing laser beams, has two beam folding mirrors indicated by  $M_{1,3,1}$ , and  $M_{1,3,2}$  shown in Figs. 5I1 through 5J5, and 6D1 through 6D7.

The position and orientation of each beam folding mirror employed at the second scanning station ST2 relative to the second locally-defined coordinate reference system  $R_{local\ 2}$  is specified by a set of position vectors pointing from the from the origin of this local coordinate reference system to the vertices of each such beam folding mirror element (i.e. light reflective surface patch) which has been optimized in terms of occupying a minimal volume within the scanner housing without compromising the performance of its beam folding function. The x,y,z coordinates of these vertex-specifying vectors are set forth in the spreadsheet table of Figs. 3C, organized according to the three mirror groups MG1@ST2, MG2@ST2 and MG3@ST2 employed at laser scanning station ST2. Notably, the first vertex of each facet in these mirror groups is repeated in the table of Fig. 3C, to traverse a closed path in 3-D space, specifying the perimetrical boundaries of these optimally-trimmed beam folding mirrors employed in the scanning system of the illustrative embodiment.

As shown in Fig. 3C, the mirrors in each mirror group of scanning station ST2 are arranged in the order that the beam folding mirror performs its beam folding (i.e. light reflection) function upon the outgoing diffracted laser beam produced by a scanning facets associated with a

1 facet group corresponding to the mirror group. Notably, at scanning station ST2, two light  
2 reflection operations are performed by the mirror group MG3@ST2 upon the outgoing  
3 diffracted laser beams. Also, while beam reflecting mirror M<sub>2,3,1</sub> has four vertices, mirrors  
4 M<sub>2,3,1A</sub> and M<sub>2,3,1B</sub> have five vertices. As will be described in greater detail hereinafter, the exact  
5 number of vertices of each beam folding mirror at scanning station ST2 will depend on the laser  
6 scanning plane being generated by the outgoing laser beam, the geometrical characteristics of the  
7 overall 3-D scanning pattern to be generated from the holographic scanning system in the  
8 particular scanning application at hand, and physical constraints within the scanner housing.  
9 Also, while the coordinate values for the vertices of each beam folding mirror specify the surface  
10 area, position and orientation of each mirror employed in the second laser scanning station ST2,  
11 it is understood that other mirror surface areas, positions and orientations can and may be used to  
12 realize other embodiments of the second laser scanning station ST2 in accordance with the  
13 principles of the present invention taught herein.

14 As best shown in Figs. 1D1, 1E, 2B2, 2C1, 2M, 2N and 2O, the third laser scanning  
15 station (ST2) comprises: a third laser beam production module 41C mounted on the optical  
16 bench 42 of the system, preferably outside the outer periphery of the holographic scanning disc  
17 30, as shown in Fig. 2A2 and 2B2; a third laser beam directing mirror 43C, disposed beneath the  
18 edge of the scanning disc, below the third point of incidence associated with the third scanning  
19 station ST3, for directing the laser beam output from the third laser beam production module  
20 41C, through the third point of incidence at a fixed angle of incidence; three groups of laser  
21 beam folding mirrors, MG1@ST3, MG2@ST3 and MG3@ST3 which are arranged about the  
22 third point of incidence at the third scanning station ST3, and cooperate with the three groups of  
23 scanning facets MG1@ST3, MG2@ST3 and MG3@ST3 on the scanning disc, respectively, so  
24 as to generate and project different groups of laser scanning planes through the bottom scanning  
25 window 16, as graphically illustrated in Figs. 5K1 through 5R5, and vectorally specified in Figs.  
26 6E1 through 6G5; a third light collecting/focusing mirror structure (e.g. parabolic light collecting  
27 mirror or parabolic surface emulating volume reflection hologram) 70C disposed beneath  
28 holographic scanning disc 30 adjacent the third laser beam directing mirror 43C and the third  
29 point of incidence at scanning station ST3; a third photodetector 45C disposed substantially  
30 above the third point of incidence at scanning station ST3 at a predetermined (i.e. minimized)  
31 height above the holographic scanning disc 30; and a third set of analog and digital signal  
32 processing boards 50C and 55C, associated with the third laser scanning station ST3, and  
33 mounted within the compact scanner housing, for processing analog and digital scan data signals  
34 as described in detail in Applicants' US Patent Application Serial No. 08/949,915 filed October  
35 14, 1997, and incorporated herein by reference, incorporated herein by reference in its entirety.

36 Referring to Figs. 2M and 3D and using the mirror identification conventions set forth  
37 above, the laser beam folding mirrors employed at the third scanning station ST3 can be  
38 conveniently indexed as follows: mirror group MG1@ST3, containing facets that generate left  
39 (i.e. positive) skewed outgoing laser beams, has three beam folding mirrors indicated by M<sub>3,1,1</sub>,  
40 M<sub>3,1,2</sub> and M<sub>3,1,3</sub> shown in Figs. 5M1 through 5N5, and Figs. 6E1 through 6G5; mirror group  
41 MG2@ST3, containing facets that generate right (i.e. negative) skewed outgoing laser beams,  
42 has two beam folding mirrors indicated by M<sub>3,3,1</sub>, and M<sub>3,2,2</sub> shown in Figs. 5K1 through 5L5,

1 and Figs. 6F1 through 6F4; and mirror group MG3@ST3, containing facets that do not generate  
2 skewed outgoing laser beams, has two beam folding mirrors indicated by  $M_{3,3,1}$ , and  $M_{3,3,2}$   
3 shown in Figs. 5O1 through 5P5, and Figs. 6G1 through 6G5.

4 The position and orientation of each beam folding mirror employed at scanning station  
5 ST3 relative to the third locally-defined coordinate reference system  $R_{\text{local } 3}$  is specified by a set  
6 of position vectors pointing from the from the origin of this local coordinate reference system to  
7 the vertices of each such beam folding mirror element (i.e. light reflective surface patch) which  
8 has been optimized in terms of occupying a minimal volume within the scanner housing without  
9 compromising the performance of its beam folding function. The x,y,z coordinates of these  
10 vertex-specifying vectors are set forth in the spreadsheet table of Figs. 3D, organized according  
11 to the three mirror groups MG1@ST3, MG2@ST3 and MG3@ST3 employed at laser scanning  
12 station ST3. Notably, the first vertex of each facet in these mirror groups is repeated in the table  
13 of Fig. 3D, to traverse a closed path in 3-D space, specifying the perimetrical boundaries of these  
14 optimally-trimmed beam folding mirrors employed in the scanning system of the illustrative  
15 embodiment.

16 As shown in Fig. 3D, the mirrors in each mirror group of scanning station ST3 are  
17 arranged in the order that the beam folding mirror performs its beam folding (i.e. light reflection)  
18 function upon the outgoing diffracted laser beam produced by a scanning facet associated with a  
19 facet group corresponding to the mirror group. Notably, at scanning station ST3, two light  
20 reflection operations are performed by the mirror groups MG2@ST3 and MG3@ST3 upon the  
21 outgoing diffracted laser beams, whereas three light reflection operations are performed by  
22 mirror group MG1@ST3 upon the outgoing diffracted laser beams. Also, certain beam  
23 reflecting mirrors (e.g.  $M_{3,2,1}$  and  $M_{3,2,2}$ ) have six vertices, while some mirrors have four vertices  
24 (e.g.  $M_{3,1,2}$  and  $M_{3,3,2}$ ), and yet other mirrors (e.g.  $M_{3,1,3}$ ) have five vertices. As will be described  
25 in greater detail hereinafter, the exact number of vertices of each beam folding mirror will  
26 depend on the laser scanning plane being generated by the outgoing laser beam, the geometrical  
27 characteristics of the overall 3-D scanning pattern to be generated from the holographic scanning  
28 system in the particular scanning application at hand, and physical constraints within the scanner  
29 housing. Also, while the coordinate values for the vertices of each beam folding mirror specify  
30 the surface area, position and orientation of each mirror employed in the third laser scanning  
31 station ST3, it is understood that other mirror surface areas, positions and orientations can and  
32 may be used to realize other embodiments of the third laser scanning station ST3 in accordance  
33 with the principles of the present invention taught herein.

34 As best shown in Figs. 1D1, 1E, 2B2, 2C1, 2N, 2P and 2Q, the fourth laser scanning  
35 station (ST4) comprises: a fourth laser beam production module 41D mounted on the optical  
36 bench 42 of the system, preferably outside the outer periphery of the holographic scanning disc  
37 30, as shown in Fig. 2A2 and 2B2; a fourth laser beam directing mirror 43D, disposed beneath  
38 the edge of the scanning disc, below the fourth point of incidence associated with the fourth  
39 scanning station ST4, for directing the laser beam output from the fourth laser beam production  
40 module 41D, through the fourth point of incidence at a fixed angle of incidence; three groups of  
41 laser beam folding mirrors, MG1@ST4, MG2@ST4 and MG3@ST4 which are arranged about  
42 the fourth point of incidence at the fourth scanning station ST4, and cooperate with the three



groups of scanning facets G1, G2 and G3 on the scanning disc, respectively, so as to generate and project different groups of laser scanning planes through the side bottom scanning window 18, as graphically illustrated in Figs. 5U1 through 5Z4, and vectorally specified in Figs. 6H1 through 6J7; a fourth light collecting/focusing mirror structure (e.g. parabolic light collecting mirror or parabolic surface emulating volume reflection hologram) 700 disposed beneath holographic scanning disc 30 adjacent the fourth laser beam directing mirror 43D and the fourth point of incidence at scanning station ST4; a fourth photodetector 45D disposed substantially above the fourth point of incidence at scanning station ST4 at a predetermined (i.e. minimized) height above the holographic scanning disc 30; and a fourth set of analog and digital signal processing boards 50D and 55D, associated with the fourth laser scanning station ST4, and mounted within the compact scanner housing, for processing analog and digital scan data signals as described in detail in Applicants' US Patent Application Serial No. 08/949,915 filed October 14, 1997, and incorporated herein by reference, incorporated herein by reference in its entirety.

Referring to Figs. 2N, 2P, 2Q, and 3E and using the mirror identification conventions set forth above, the laser beam folding mirrors employed at the fourth scanning station ST4 can be conveniently indexed as follows: mirror group MG1@ST4, containing facets that generate left (i.e. positive) skewed outgoing laser beams, has two beam folding mirrors indicated by  $M_{4,1,1}$  and  $M_{4,1,2}$  shown in Figs. 5U1 through 5V5, and Figs. 6H1 through 6H4; mirror group MG2@ST4, containing facets that generate right (i.e. negative) skewed outgoing laser beams, has two beam folding mirrors indicated by  $M_{4,2,1}$  and  $M_{4,2,2}$  shown in Figs. 5U1 through 5V5, and Figs. 6I1 through 6I4; and mirror group MG3@ST4, containing facets that do not generate skewed outgoing laser beams, has two (i.e. a pair of split-type) beam folding mirrors indicated by  $M_{4,3,1A}$  and  $M_{4,3,1B}$  shown in Figs. 5W1 through 5V5, and Figs. 6J1 through 6J7.

The position and orientation of each beam folding mirror employed at scanning station ST4 relative to the fourth locally-defined coordinate reference system  $R_{local\ 4}$  is specified by a set of position vectors pointing from the origin of this local coordinate reference system to the vertices of each such beam folding mirror element (i.e. light reflective surface patch) which has been optimized in terms of occupying a minimal volume within the scanner housing without compromising the performance of its beam folding function. The x,y,z coordinates of these vertex-specifying vectors are set forth in the spreadsheet table of Figs. 3E, organized according to the three mirror groups MG1@ST4, MG2@ST4 and MG3@ST4 employed at laser scanning station ST4. Notably, the first vertex of each facet in these mirror groups is repeated in the table of Fig. 3E, to traverse a closed path in 3-D space, specifying the perimetrical boundaries of these optimally-trimmed beam folding mirrors employed in the scanning system of the illustrative embodiment.

As shown in Fig. 3E, the mirrors in each mirror group of scanning station ST4 are arranged in the order that the beam folding mirror performs its beam folding (i.e. light reflection) function upon the outgoing diffracted laser beam produced by a scanning facet associated with a facet group corresponding to the mirror group. Notably, at scanning station ST4, two light reflection operations are performed by the mirror groups MG1@ST4 and MG2@ST4 upon the outgoing diffracted laser beams, whereas one light reflection operation is performed by mirror group MG3@ST4 upon the outgoing diffracted laser beams. Notably, while all mirrors in the

1 mirror groups of scanning station have four vertices, it is understood that in alternative  
2 embodiments of the present invention, the beam folding mirrors in such mirror groups may have  
3 more or less than four vertices, depending on the laser scanning planes being generated by the  
4 outgoing laser beams, the geometrical characteristics of the overall 3-D scanning pattern to be  
5 generated from the holographic scanning system in the particular scanning application at hand,  
6 and physical constraints within the scanner housing. Also, while the coordinate values for the  
7 vertices of each beam folding mirror specify the surface area, position and orientation of each  
8 mirror employed in the fourth laser scanning station ST4, it is understood that other mirror  
9 surface areas, positions and orientations can and may be used to realize other embodiments of the  
10 fourth laser scanning station ST4 in accordance with the principles of the present invention  
11 taught herein.

12 In the illustrative embodiment of the present invention, certain of the laser beam folding  
13 mirrors associated with scanning stations ST1 and ST3, and all of the beam folding mirrors  
14 associated with scanning station ST4 are physically supported using a first mirror support  
15 platform, formed with the scanner housing. All of the beam folding mirrors associated with the  
16 second laser scanning station ST2, and certain of beam folding mirrors associated with laser  
17 scanning stations ST1 are physically supported using a second mirror support platform  
18 associated with optical bench 42 of the scanning system. Preferably, these mirror mounting  
19 support structures, as well as the components of the scanning housing are made from a high-  
20 impact plastic using injection molding techniques well known in the art. The vertices of the laser  
21 beam folding mirrors used at each scanning station can be used to create molds for making such  
22 mirror support structures.

23 During operation of the bioptical laser scanning system hereof, each laser beam  
24 production module 41A, 41B, 41C and 41D cooperates with the holographic scanning disc 30  
25 and produces from its internal visible laser diode(VLD) 153, a laser beam having desired beam  
26 cross-sectional characteristics (e.g. the beam aspect ratio of an ellipse or circle) and being  
27 essentially free of astigmatism and beam-dispersion that is otherwise associated with a laser  
28 beam directly transmitted from a VLD through a prior art rotating holographic scanning facet  
29 during laser beam scanning operations. When an incident laser beam from the VLD passes  
30 through a particular holographic scanning facet at the point of incidence of the laser scanning  
31 station of the present invention, it is diffracted in a prespecified "outgoing" direction (i.e. at an  
32 angle of diffraction  $B_i$ ) determined by the skew angle  $\phi_{skew}$  and elevation angle  $\theta_{elevation}$   
33 determined during the holographic disc design process of the present invention. The function of  
34 the multiple groups of laser beam folding mirrors associated with each laser scanning station is  
35 to change (i.e. fold) the direction of the outgoing diffracted laser beam from its outgoing  
36 direction off the scanning disc, into the direction required to generate its corresponding laser  
37 scanning plane in front of the bottom and side scanning window 16 and 18. The actual laser  
38 scanning planes produced by the laser scanning stations of the system are geometrically specified  
39 in Figs. 5A1 through 5Z4, and vectorally specified in Figs. 6A1 through 6J7. Notably, when a  
40 produced laser scanning plane is intersected by a planar surface (e.g. associated with an object  
41 bearing a bar code symbol), a linear scanline is projected on the intersected surface. The angular

1 dimensions of each resulting scanning plane are determined by the Scan Angle,  $\theta_{Si}$  associated  
2 with the geometry of the scanning facet, and the Scan Angle Multiplication Factor,  $M_i$  associated  
3 therewith, which will be discussed in greater detail hereinafter.

4 When a bar code symbol is scanned by any one of the laser scanning planes projected  
5 from the bottom or side scanning windows of the system, the incident laser light scanned across  
6 the object is intensity modulated by the absorptive properties of the scanned object and scattered  
7 according to Lambert's Law (for diffuse reflective surfaces). A portion of this laser light is  
8 reflected back along the outgoing ray (optical) path, off the same group of beam folding mirrors  
9 employed during the corresponding laser beam generation process, and thereafter passes through  
10 the same holographic scanning facet that generated the corresponding scanning plane only  
11  $T_{\text{transit}} = 2f/c$  seconds before, where  $c$  is the speed of light. As the reflected laser light passes  
12 through the holographic scanning facet on its return path towards the parabolic mirror structure  
13 disposed beneath the holographic scanning disc, the incoming light rays enter the holographic  
14 scanning facet close to the Bragg angle thereof (i.e.  $B_i$ ) and thus (once again) are strongly  
15 diffracted towards the parabolic mirror along its optical axis. The parabolic mirror associated  
16 with each laser scanning station, in turn, focuses these collected light rays and redirects the same  
17 through the holographic scanning facet at angles sufficiently far off the Bragg angle (i.e.  $A_i$ ) so  
18 that they are transmitted therethrough towards the photodetector disposed directly above the  
19 point of incidence at the laser scanning station with minimal losses due to internal diffraction  
20 within the holographic facet. A novel method of designing the light  
21 collection/focusing/detection subsystem of the present invention will be described in great detail  
22 hereinafter.

23 As will be described in greater detail hereinafter, the geometry of each holographic facet  
24 has been designed so that (1) each of the twelve holographic facets supported thereon has  
25 substantially the same (i.e. equal) Lambertian light collecting efficiency, independent of its focal  
26 length, and (2) the collective surface area of all of the holographic facets occupies (i.e. uses) all  
27 of the available light collecting surface area between the outer radius and inner radius of the  
28 scanning disc. The advantage of this aspect of the present invention is that optical-based scan  
29 data signals with maximum signal-to-noise (SNR) ratio are produced and collected at the  
30 photodetector of each laser scanning station in the system. This, of course, implies higher  
31 performance and higher quality scan data signals for signal processing purposes.

32 As shown in Fig. 3A1, each holographic facet on the surface of the scanning disc is  
33 specified by a set of geometrical parameters, a set of optical parameters, and a set of holographic  
34 recording parameters. The geometrical parameters define various physical characteristics of the  
35 facet in issue, such as the location of the facet on the disc specified by its preassigned facet  
36 number (e.g.  $n=1, 2, 3, \dots$ , or 12), its light collecting surface Area<sub>i</sub> (designed to exhibit a high  
37 diffraction efficiency to incoming light rays on Bragg), the Angle of the facet  $\theta_{\text{rot}i}$ , the adjusted  
38 Rotation Angle of the facet  $\theta'_{\text{rot}i}$  actual scan angle of the facet  $\theta_{\text{Sweep}i}$  (accounting for beam  
39 diameter  $d_{\text{beam}}$  and interfaced gaps  $d_{\text{gap}}$ ), and the surface boundaries SB<sub>i</sub> occupied by the  
40 holographic facet on the scanning disc, which typically will be irregular in shape by virtue of the  
41 optimized light collecting surface area of the holographic disc). The optical parameters

1 associated with each holographic facet include the wavelength  $\lambda$  at which the object beam is  
2 designed to be reconstructed, the angle of incidence of the holographic facet  $A_i$ , the angle of  
3 diffraction thereof  $B_i$ , its scan angle multiplication factor  $M_i$ , the focal length  $f_i$  of the facet, etc.  
4 Unlike the other parameters associated with each facet, the recording parameters define: the  
5 thickness of the recording medium  $T$  (e.g. dichromate gelatin or Dupont photopolymer) used  
6 during the recording of the holographic facet; the average bulk index of refraction of the  
7 recording medium; and the modulation depth (i.e. modulation-index)  $\Delta n_i$  associated with fringe  
8 structure formed in the recording medium. Collectively, these parameters shall be referred to as  
9 "construction parameters" as these parameters are required to construct the holographic facet  
10 with which they are associated.

11 In the bioptical holographic laser scanning system of the present invention, the principal  
12 function of each holographic facet on the scanning disc is to deflect an incident laser beam along  
13 a particular path in 3-D space in order to generate a corresponding scanning plane within the 3-D  
14 laser scanning volume produced by the laser scanning system hereof. Collectively, the complex  
15 of laser scanning planes produced by the plurality of holographic facets in cooperation with the  
16 four laser beam production modules ST1, ST2, ST3, and ST4 creates an omni-directional scanning  
17 pattern within the highly-defined 3-D scanning volume of the scanning system between the space  
18 occupied by the bottom and side scanning windows of the system.

19 In the bioptical holographic laser scanning system of the present invention, multiple  
20 facets of the holographic scanning disc can be designed such that multiple incident laser beams  
21 are simultaneously focused to overlapping regions in the 3-D scanning volume at varying focal  
22 distances (preferably, less than 2 inches or less difference in focal distance). Such features  
23 provide a larger spot in the same vicinity as a smaller spot, which extends the overall depth of  
24 field of the bioptical holographic laser scanner system while reducing paper noise.

25 As shown in the timing diagram of Fig. 6K, the bioptical holographic laser scanner of the  
26 illustrative embodiment cyclically generates a complex omni-directional 3-D laser scanning  
27 pattern from both the bottom and side scanning windows 16 and 18 thereof. This complex omni-  
28 directional scanning pattern is graphically illustrated in Figs. 5A1 through 5A5, and the scanning  
29 plane components of this pattern are graphically illustrated in Figs. 5A6 through 5Z4. The 3-D  
30 laser scanning pattern of the illustrative embodiment consists of 50 different laser scanning  
31 planes, having different depths of focus, which cooperate in order to generate a plurality of pairs  
32 of quasi-orthogonal laser scanning patterns within the 3-D scanning volume of the system,  
33 thereby enabling true omnidirectional scanning of bar code symbols having minimum bar  
34 elements on the order of about 0.006 inches or less. Greater details of the laser scanning pattern  
35 of the present invention will be described hereinbelow.

36 In the bioptical holographic laser scanning system of the present invention, the laser light  
37 source (e.g., VLD) of the laser beam production module(s) can be deactivated (e.g., turned off)  
38 when the scan line produced therefrom is no longer passing through the bottom or side window.  
39 This eliminates unwanted internal scattering of the laser light in the system housing and extends  
40 the life of the laser light source.

As shown in Figs. 2E through 2E3 and 2F1 through 2H3, the four laser production modules 41A, 41B, 41C and 41D are mounted on a base plate (i.e. optical bench) 42 in Fig. 1G, about the axis of rotation of the shaft of electric motor 41, at the angular locations specified in Figs. 2B1 and 2B2, detailed above. As shown in Figs. 2G1 through 2G3, each laser beam production module comprises: a visible laser diode (VLD) 153 and an aspheric collimating lens (L1) 81 supported within the bore of a housing 82 mounted upon the optical bench 42 of the module housing; a multi-function light diffractive grating 83 having a fixed spatial frequency and disposed at incident angle relative to the outgoing laser beam collimated from lens 81 for changing properties of the incident laser beam so that the aspect-ratio thereof is controlled, beam dispersion is minimized upon the laser beam exiting the holographic scanning disc; a beam folding mirror 84 supported at the edge of housing for directing the output laser beam through the scanning disc at the point of incidence, at the angle of incidence; and, possibly, a photodetector 84 supported within a housing 82 and disposed along the optical axis of the VLD 81 for detecting the zeroeth diffraction order as the incident laser beam is transmitted through the multifunction light diffractive grating 83, and producing an electrical signal indicative of the detected intensity. Details for designing the multi-function light diffractive grating and configuring the laser scanning beam module of the illustrative embodiment is described in great detail in Applicants' prior US Patent Application Serial No. 08/949,915 filed October 14, 1997, and incorporated herein by reference, incorporated herein by reference in its entirety.

In the illustrative embodiment describe above wherein the laser scanning station ST4 produces scanning planes that are directed through the vertical window 18 of the system, the aspheric collimating lens (L1) 81 of the laser production module 41D for the laser scanning station ST4 is designed to increase the focus distance of these scanning planes directed through the vertical window 18 beyond the focus distance of the scanning planes that are directed through the horizontal window 16 of the system (produced by the laser scanning stations ST1, ST2 and ST3). Such a design allows for the same facets of the holographic disc to be used in producing the scanning planes that are directed through both the vertical window 18 and the horizontal window 16.

In each laser scanning station (ST1, ST2, ST3 and ST4) of the illustrative embodiment, the laser beam production module serves several important functions. The module produces a circularized laser beam that is directed at the point of incidence, located at  $r_o$ , on the rotating scanning disk, at the prespecified angle of incidence  $\theta_i$  (i.e.  $90^\circ - A_i$ ), which, in the illustrative embodiment, is precisely the same for all facets thereon. Also, the module produces a laser beam that is free of VLD-related astigmatism, and exhibits minimum dispersion when diffracted by the scanning disk, as taught by Applicants in US Patent Application Serial No. 08/949,915 filed October 14, 1997, and incorporated herein by reference.

As shown in Figs. 2H1 and 2H2, each laser beam directing module 41A, 41B, 41C and 41D, cooperating with laser beam directing modules 43A, 43B, 43C and 43D, respectively, comprises an optical bench 90 which is stationarily mounted upon the optical bench of the scanning system, as shown in Figs. 1E and 2A2. As shown in Figs. 2H1 and 2H2, the optical bench 90 supports a first planar mirror 91 which reflects the laser beam output from its associated laser beam production module at about a 90 degree angle, onto a second planar mirror

1 92 also supported by the optical bench. As shown, the second planar mirror 92 is disposed at an  
2 angle relative to the central plane of the scanning disc to that the beam reflecting off the second  
3 planar mirror 92 is directed onto the point of incidence of the associated scanning station at the  
4 predetermined angle of incidence.

5 As shown in Figs. 2I1 through 2J2, scan data photodetectors 45A and 45C associated  
6 with laser scanning stations ST1 and ST3 are mounted substantially above the first and third  
7 point of incidences, whereas scan data photodetectors 45B and 45D associated with laser  
8 scanning stations ST2 and ST4 are mounted substantially above the second and fourth point of  
9 incidences so that these devices do not block or otherwise interfere with the returning (i.e.  
10 incoming) laser light rays reflecting off light reflective surfaces (e.g. product surfaces, bar code  
11 symbols, etc) during laser scanning and light collecting operations. In practice, each  
12 photodetector 45A, 45B, 45C and 45D is supported in its respective position by a photodetector  
13 support frame or like structure which is stationarily mounted to the optical bench 42 by way one  
14 or more support elements (not shown for purposes of clarity). The electrical analog scan data  
15 signal produced from each photodetector is processed in a conventional manner by its analog  
16 scan data signal processing board which can be supported upon photodetector support frame, or  
17 by other suitable support mechanisms known in the art. Notably, the height of the photodetector  
18 support structure, referenced to the base plate (i.e. optical bench) 42, will be chosen to be less  
19 than the maximum height of the base/bottom portion of the scanner housing.

20 As best shown in Fig. 2I1 and 2J2, the parabolic light collecting mirror structure 70A  
21 (70B, 70C, 70D) associated with each laser scanning station is disposed beneath the holographic  
22 scanning disc, about the x axis of the locally embedded coordinate system of the laser scanning  
23 station. While certainly not apparent, precise placement of the parabolic light collecting element  
24 (e.g. mirror) relative to the holographic facets on the scanning disc is a critical requirement for  
25 effective light detection by the photodetector associated with each laser scanning station.  
26 Placement of the photodetector 45A at the focal point of the parabolic light focusing mirror 70A  
27 alone is not sufficient for optimal light detection in the light detection subsystem of the present  
28 invention. Careful analysis must be accorded to the light diffraction efficiency of the facets on  
29 the holographic scanning disc and to the polarization state(s) of collected and focused light rays  
30 being transmitted therethrough for detection. As will become more apparent hereinafter, the  
31 purpose of such light diffraction efficiency analysis ensures the realization of two important  
32 conditions, namely: (i) that substantially all of the incoming light rays reflected off an object  
33 (e.g. bar code symbol) and passing through the holographic facet (producing the corresponding  
34 instant scanning beam) are collected by the parabolic light collecting mirror; and (ii) that all of  
35 the light rays collected by the parabolic light collecting mirror are focused through the same  
36 holographic facet onto the photodetector associated with the station, with minimal loss  
37 associated with light diffraction and refractive scattering within the holographic facet.

38 In another embodiment of the present invention, the scan data photodetector (45A, 45B,  
39 45C and 45D) for each laser scanning station is mounted along the x axis in the locally  
40 embedded coordinate system of the laser scanning station directly above the edge of the  
41 holographic scanning disc (or possibly outside the outer periphery of the holographic scanning  
42 disc). Moreover, the corresponding parabolic light collecting mirror structure (70A, 70B, 70C,

1 or 70D) for each laser scanning station is disposed beneath the holographic scanning disc, about  
2 the x axis of the locally embedded coordinate system of the laser scanning station and is  
3 designed to ensure the realization of two important conditions, namely: (i) that substantially all  
4 of the incoming light rays reflected off an object (e.g. bar code symbol) and passing through the  
5 holographic facet (producing the corresponding instant scanning beam) are collected by the  
6 parabolic light collecting mirror structure (70A, 70B, 70C, or 70D); and (ii) that all of the light  
7 rays collected by the parabolic light collecting mirror structure (70A, 70B, 70C, or 70D) are  
8 focused onto the corresponding scan data photodetector (45A, 45B, 45C and 45D). Such a  
9 design reduces the height of the parabolic light collecting mirror structures (70A, 70B, 70C, and  
10 70D), thereby allowing for reduction in depth of the scanner housing, which is a key benefit in a  
11 space constrained environment such as in POS retail applications.

12 In another embodiment of the present invention, the scan data photodetector (45A, 45B,  
13 45C or 45D) for one or more of the laser scanning stations may be disposed behind one of the  
14 beam folding mirrors. In this case, a small hole (or notch) may be cut in this beam folding  
15 mirror(s) to allow return light collected by the corresponding parabolic light collecting mirror  
16 structure (70A, 70B, 70C, or 70D), which is disposed beneath the holographic scanning disc, to  
17 reach the scan data photodetector (45A, 45B, 45C and 45D).

18 Preferably, the size, shape and orientation of the scan data collecting photodetector (45A,  
19 45B, 45C and 45D) for each laser scanning station is designed so that the lateral shift of the  
20 reflected beam image across the light sensitive surface of the photodetector, as a scanned item  
21 moves through the depth of field region of the scanning station, results in a relatively uniform  
22 light level reaching the light sensitive surface of the photodetector.

23 In addition, a light cone disposed immediately adjacent to one or more of the scan data  
24 collecting photodetectors (45A, 45B, 45C and 45D) may be used to collect light directed thereto  
25 by the parabolic light collecting mirror structures (70A, 70B, 70C, and 70D) and funnel such  
26 light to the light collecting surface(s) of the photodetector(s).

27 In addition, one or more light pipes may be used to funnel light from a light collection  
28 element (for example, a parabolic light collecting mirror) in the return optical path for one or  
29 more of the laser scanning stations to the light collecting surface(s) of the scan data collecting  
30 photodetector(s) (45A, 45B, 45C and 45D).

31 Moreover, the optical surface of the parabolic light collecting mirror structures (70A,  
32 70B, 70C, and 70D) for the laser scanning stations ST1, ST2, ST3 and ST4, respectively, is  
33 preferably shaped as a truncated ellipse. Such an optical surface may be physically formed from  
34 pie-shaped sectors whose three corners are truncated.

35 As illustrated in Fig. 2I2, a light blocking element 51, which is supported by legs (two  
36 shown as 52A and 52B), may be positioned above the scanning disk 30. The light blocking  
37 element 51 serves two primary purposes. First, it blocks the zero-order beams produced from the  
38 scanning disc 30 (which correspond to the primary beams produced by the laser beam production  
39 modules 47A, 47B, 47C and 47D for the laser scanning stations ST1, ST2, ST3 and ST4,  
40 respectively, that are incident on the scanning disc 30) so that these zero-order beams do not pass  
41 through the bottom window 16. Importantly, these zero-order beams are static beams and would,  
42 therefor, violate laser safety standards were it not blocked. The second function is to block

1 ambient light which comes into the bottom window 16 (including light entering the bottom  
2 window 16 along the exact opposite direction of the outgoing zero-order beams) from reaching  
3 the photodetectors (45A, 45B, 45C and 45D) for the laser scanning stations ST1, ST2, ST3 and  
4 ST4, respectively. If it were not blocked, this ambient light would, in some amount, pass  
5 through the scanning disc 30, reflect off the parabolic light collecting mirror structures (70A,  
6 70B, 70C, and 70D) and be directed to the photodetectors (45A, 45B, 45C and 45D), which  
7 would add unwanted noise to the signal generated therein.

8 As shown in Figs. 2A and 2B1, the four digital scan data signal processing boards 55A,  
9 55B, 55C and 55D are arranged in such a manner within the scanner housing to receive and  
10 provide for processing the analog scan data signals produced from analog scan data signal  
11 processing boards 50A, 50B, 50C, and 50D respectively. Each of the analog signal processing  
12 boards 50A, 50B, 50C and 50D, with its scan data photodetector mounted thereto, can be  
13 mounted above the corresponding laser beam directing mirror module 43A, 43B, 43C and 43D,  
14 set back slightly in a radial direction along the x axis of the locally embedded coordinate  
15 reference system. In practice, each analog scan data signal can be made very small and narrow to  
16 occupy the available space provided in such "return ray free" locations within the scanner  
17 housing. Digital scan data signal processing boards 55A, 55B, 55C and 55D can be mounted  
18 virtually anywhere within the side portion of the scanner housing which does not cause  
19 interference with outgoing and incoming (i.e. return) laser light rays. A central processing board  
20 60 can also be mounted within the vertical housing portion of the scanner housing, for processing  
21 signals produced from the digital scan data signal processing boards. A conventional power  
22 supply board can be mounted upon the base plate (i.e. optical bench) 42 of the system, preferably  
23 within one of the corners of the system. The function of the digital scan data signal processing  
24 boards, the central processing board, and the power supply board will be described in greater  
25 detail in connection with the functional system diagram of Fig. 4. As shown, electrical cables  
26 are used to conduct electrical signals from each analog scan data signal processing board to its  
27 associated digital scan data signal processing board, and from each digital scan data signal  
28 processing board to the central processing board. Regulated power supply voltages are provided  
29 to the central signal processing board 60 by way of an electrical harness (not shown), for  
30 distribution to the various electrical and electro-optical devices requiring electrical power within  
31 the holographic laser scanner. In a conventional manner, electrical power from a standard 120  
32 Volt, 60 HZ, power supply is provided to the power supply board by way of flexible electrical  
33 wiring (not shown). Symbol character data produced from the central processing board is  
34 transmitted over a serial data transmission cable connected to a serial output (i.e. standard  
35 RS232) communications jack installed through a wall in the scanner housing. This data can be  
36 transmitted to any host device by way of a serial (or parallel) data communications cable, RF  
37 signal transceiver, or other communication mechanism known in the art.

38 As shown in Figs. 1A, the bottom and side scanning windows 16 and 18 have light  
39 transmission apertures of substantially planar extent. Bottom light transmission aperture is  
40 substantially parallel to the holographic scanning disc rotatably supported upon the shaft of  
41 electric motor 41, whereas the side light transmission aperture is substantially perpendicular  
42 thereto. In order to seal off the optical components of the scanning system from dust, moisture



1 and the like, laser scanning windows 16 and 18, preferably fabricated from a high impact plastic  
2 material, are installed over their corresponding light transmission apertures using a rubber gasket  
3 and conventional mounting techniques. In the illustrative embodiment, each laser scanning  
4 window 16 and 18 has spectrally-selective light transmission characteristics which, in  
5 conjunction with a spectrally-selective filters 16A, 16B, 16C, 16D installed before each  
6 photodetector within the housing, forms a narrow-band spectral filtering subsystem that performs  
7 two different functions. The first function of the narrow-band spectral filtering subsystem is to  
8 transmit only the optical wavelengths in the red region of the visible spectrum in order to impart  
9 a reddish color or semi-transparent character to the laser scanning window. This makes the  
10 internal optical components less visible and thus remarkably improves the external appearance of  
11 the holographic laser scanning system. This feature also makes the holographic laser scanner  
12 less intimidating to customers at point-of-sale (POS) stations where it may be used. The second  
13 function of the narrow-band spectral filtering subsystem is to transmit to the photodetector for  
14 detection, only the narrow band of spectral components comprising the outgoing laser beam  
15 produced by the associated laser beam production module. Details regarding this optical filtering  
16 subsystem are disclosed in copending Application Serial No. 08/439,224, entitled "Laser Bar  
17 Code Symbol Scanner Employing Optical Filtering With Narrow Band-Pass Characteristics and  
18 Spatially Separated Optical Filter Elements" filed on May 11, 1995, which is incorporated herein  
19 by reference in its entirety.

20 When using multiple laser beam sources in any holographic laser scanning system, the  
21 problem of "cross-talk" among the neighboring light detection subsystems typically arises and  
22 must be adequately resolved. The cause of the cross-talk problem is well known. It is due to the  
23 fact that the spectral components of one laser beam are detected by a neighboring photodetector.  
24 While certainly not apparent, the holographic scanning disc of the present invention has been  
25 designed so that light rays produced from one laser beam (e.g.  $j=1$ ) and reflected off a scanned  
26 code symbol anywhere within the laser scanning volume  $V_{\text{scanning}}$  will fall incident upon the light  
27 collecting region of the scanning disc associated with a neighboring light detection subsystem in  
28 an off-Bragg condition. Consequently, the signal level of "neighboring" incoming scan data  
29 signals are virtually undetectable by each photodetector in the holographic laser scanner of the  
30 present invention. The optical characteristics of the scanning facets on the scanning disc which  
31 makes this feature possible will be described in greater detail hereinafter during the description  
32 of the scanning disc design process hereof.

33 As best shown in Fig. 3A1, the holographic scanning disc of the present invention is  
34 unlike any other prior art laser scanning disc in three important respects. Firstly, virtually all of  
35 the utilizable surface area of the scanning disc, defined between the outer edge of the support  
36 hub 40 and the outer edge of the scanning disc, is occupied by the collective surface area of all  
37 twenty holographic scanning facets that have been laid out over this defined region. Secondly,  
38 each holographic scanning facet has substantially the same Lambertian light collection efficiency  
39 as all other scanning facets. Unlike conventional laser scanning discs, the geometry of each  
40 holographic facet on the scanning disc of the present invention is apparently irregular, arbitrary  
41 and perhaps even fanciful to the eyes of onlookers. The fact is, however, that this is not the case.  
42 As taught in Applicants' U.S. Patent Application Serial No. 08/949,915 filed October 14, 1997,

1 and incorporated herein by reference, the scanning disc design process employed herein  
2 comprises two major stages: a first, "analytical modeling stage" during which particular optical  
3 and geometrical parameters are determined for each holographic facet within a complex set of  
4 scanning system constraints; and a second, "holographic facet layout stage", during which the  
5 scanning disc designer lays out each holographic facet on the support disc so that virtually all of  
6 the available surface area thereon is utilized by the resulting layout. While the disc design  
7 method allows certain geometrical parameters associated with each designed holographic facet to  
8 be selected on the basis of discretion and judgement of the disc designer (preferably using a  
9 computer-aided (CAD) tool) during the holographic facet layout stage, certain geometrical  
10 parameters, however, such as the total surface area of each facet  $Area_i$ , its Scan Sweep Rotation  
11 (or Sweep Angle  $\theta'_{rot}$ ) and its inner radius  $r_i$  are determined during the analytical modeling stage  
12 by the geometrical structure (e.g. its scanline length, focal plane, and relative position in the scan  
13 pattern) associated with the corresponding laser scanline  $P(i,j)$  produced by the holographic facet  
14 within a particular focal plane of the prespecified laser scanning pattern. Consequently,  
15 particular parameters determined during the analytical modeling stage of the design process  
16 operate as constraints upon the disc designer during the facet layout stage of the process. Thus,  
17 the holographic facets realized on the scanning disc of the present invention have particular  
18 geometrical characteristics that are directly determined by geometrical properties of the laser  
19 scanning pattern produced therefrom, as well as the optical properties associated with the laser  
20 beam and the holographic facets realized on the scanning disc.

21 As shown in the system diagram of Figs. 4A through 4C, the holographic laser scanning  
22 system of the present invention comprises a number of system components, many of which are  
23 realized on boards that have been hereinbefore described. For sake of simplicity, it will be best  
24 to describe these system components by describing the components realized on each of the  
25 above-described boards, and thereafter describe the interfaces and interaction therebetween.

26 In the illustrative embodiment, each analog scan data signal processing board 50A, 50B,  
27 50C and 50D has the following components mounted thereon: an associated photodetector 45A  
28 (45B, 45C, 45D) (e.g. a silicon photocell) for detection of analog scan data signals (as  
29 described); an analog signal processing circuit 50A (50B, 50C, 50D) for processing detected  
30 analog scan data signals; a 0-th diffraction order signal detector 36A (36B, 36C, 36D) for  
31 detecting the low-level, 0-th diffraction order signal produced from each holographic facet on the  
32 rotating scanning disc during scanner operation; and associated signal processing circuitry 37A  
33 (37B, 37C, 37D) for detecting a prespecified pulse in the optical signal produced by the 0-th  
34 diffraction order signal detector and generating a synchronizing signal  $S(t)$  containing a periodic  
35 pulse pattern. As will be described below in greater detail, the function of the synchronizing  
36 signal  $S(t)$  is to indicate when a particular holographic facet (e.g. Facet No.  $i=1$ ) produces its 0-th  
37 order optical signal, for purposes of linking detected scan data signals with the particular  
38 holographic facets that generated them during the scanning process.

39 In the illustrative embodiment, each photodetector 45A, 45B, 45C and 45D is realized as  
40 an opto-electronic device and each analog signal processing (e.g. preamplification and A/D  
41 conversion) circuit 35A (35B, 35C, 35D) aboard the analog signal processing board is realized as  
42 an Application Specific Integrated Circuit (ASIC) chip. These chips are suitably mounted onto a

1 small printed circuit (PC) board, along with electrical connectors which allow for interfacing  
2 with other boards within the scanner housing. With all of its components mounted thereon, each  
3 PC board is suitably mounted within the scanner housing.

4 In a conventional manner, the optical scan data signal  $D_0$  focused onto the photodetector  
5 45A (45B, 45C or 45D) during laser scanning operations is produced by light rays associated  
6 with a diffracted laser beam being scanned across a light reflective surface (e.g. the bars and  
7 spaces of a bar code symbol) and scattering thereof, whereupon the polarization state distribution  
8 of the scattered light rays is typically altered when the scanned surface exhibits diffuse reflective  
9 characteristics. Thereafter, a portion of the scattered light rays are reflected along the same  
10 outgoing light ray paths toward the holographic facet which produced the scanned laser beam.  
11 These reflected light rays are collected by the scanning facet and ultimately focused onto the  
12 photodetector of the associated light detection subsystem by its parabolic light reflecting mirror  
13 disposed beneath the scanning disc. The function of each photodetector is to detect variations in  
14 the amplitude (i.e. intensity) of optical scan data signal  $D_0$ , and produce in response thereto an  
15 electrical analog scan data signal  $D_1$  which corresponds to such intensity variations. When a  
16 photodetector with suitable light sensitivity characteristics is used, the amplitude variations of  
17 electrical analog scan data signal  $D_1$  will linearly correspond to light reflection characteristics of  
18 the scanned surface (e.g. the scanned bar code symbol). The function of the analog signal  
19 processing circuitry is to band-pass filter and preamplify the electrical analog scan data signal  
20  $D_1$ , in order to improve the SNR of the output signal.

21 In the illustrative embodiment, each digital scan data signal processing board 55A (55B,  
22 55C, 55D) is constructed the same. On each of these signal processing boards, programmable  
23 digitizing circuit 38A (38B, 38C, 38D) is realized as a second ASIC chip. Also, a programmed  
24 decode computer 39A (39B, 39C, 39D) is realized as a microprocessor and associated program  
25 and data storage memory and system buses, for carrying out symbol decoding operations. In the  
26 illustrative embodiment, the ASIC chips, the microprocessor, its associated memory and systems  
27 buses are all mounted on a single printed circuit (PC) board, using suitable electrical connectors,  
28 in a manner well known in the art.

29 The function of the A/D conversion circuit is to perform a simple thresholding function in  
30 order to convert the electrical analog scan data signal  $D_1$  into a corresponding digital scan data  
31 signal  $D_2$  having first and second (i.e. binary) signal levels which correspond to the bars and  
32 spaces of the bar code symbol being scanned. In practice, the digital scan data signal  $D_2$  appears  
33 as a pulse-width modulated type signal as the first and second signal levels thereof vary in  
34 proportion to the width of bars and spaces in the scanned bar code symbol.

35 The function of the programmable digitizing circuit is to convert the digital scan data  
36 signal  $D_2$ , associated with each scanned bar code symbol, into a corresponding sequence of  
37 digital words (i.e. a sequence of digital count values)  $D_3$ . Notably, in the digital word sequence  
38  $D_3$ , each digital word represents the time length associated with each first or second signal level  
39 in the corresponding digital scan data signal  $D_2$ . Preferably, these digital count values are in a  
40 suitable digital format for use in carrying out various symbol decoding operations which, like the  
41 scanning pattern and volume of the present invention, will be determined primarily by the  
42 particular scanning application at hand. Reference is made to U.S. Patent No. 5,343,027 to

1 Knowles, incorporated herein by reference, as it provides technical details regarding the design  
2 and construction of microelectronic digitizing circuits suitable for use in the holographic laser  
3 scanner of the present invention.

4 In bar code symbol scanning applications, the function of the programmed decode  
5 computer is to receive each digital word sequence  $D_3$  produced from the digitizing circuit, and  
6 subject it to one or more bar code symbol decoding algorithms in order to determine which bar  
7 code symbol is indicated (i.e. represented) by the digital word sequence  $D_3$ , originally derived  
8 from corresponding scan data signal  $D_1$  detected by the photodetector associated with the decode  
9 computer. In more general scanning applications, the function of the programmed decode  
10 computer is to receive each digital word sequence  $D_3$  produced from the digitizing circuit, and  
11 subject it to one or more pattern recognition algorithms (e.g. character recognition algorithms) in  
12 order to determine which pattern is indicated by the digital word sequence  $D_3$ . In bar code  
13 symbol reading applications, in which scanned code symbols can be any one of a number of  
14 symbologies, a bar code symbol decoding algorithm with auto-discrimination capabilities can be  
15 used in a manner known in the art.

16 As shown in Figs. 4A through 4C, the central processing board 60 comprises a number of  
17 components mounted on a small PC board, namely: a programmed microprocessor 61 with a  
18 system bus and associated program and data storage memory, for controlling the system  
19 operation of the holographic laser scanner and performing other auxiliary functions; first, second,  
20 third and forth serial data channels 62A, 62B, 62C and 62D, for receiving serial data input from  
21 the programmable decode computers and RF receiver/base unit 64; an input/output (I/O)  
22 interface circuit 65 for interfacing with and transmitting symbol character data and other  
23 information to host computer system 68 (e.g. central computer, cash register, etc.); and a user-  
24 interface circuit 65 for providing drive signals to an audio-transducer 67 and LED-based visual  
25 indicators used to signal successful symbol reading operations to users and the like. In the  
26 illustrative embodiment, each serial data channel is realized as an RS232 port, although it is  
27 understood that other structures may be used to realize the function performed thereby. The  
28 programmed control computer 61 also produces motor control signals, and laser control signals  
29 during system operation. These control signals are received as input by a power supply circuit  
30 69 realized on the power supply PC board, identified hereinabove. Other input signals to the  
31 power supply circuit 69 include a 120 Volt, 60 Hz line voltage signal from a standard power  
32 distribution circuit. On the basis of the received input signals, the power supply circuit produces  
33 as output, (1) laser source enable signals to drive VLDs 153A, 153B, 153C, and 153D,  
34 respectively, and (2) motor enable signals in order to drive the scanning disc motor 41.

35 In the illustrative embodiment, RF base unit 64 is realized on a very small PC board  
36 mounted on the base plate 42 within the scanner housing. Preferably, RF base unit 64 is  
37 constructed according to the teachings of copending U.S. Application Serial No. 08/292,237 filed  
38 August 17, 1995, also incorporated herein by reference. The function of the base unit is to  
39 receive data-packet modulated carrier signals transmitted from a remotely situated bar code  
40 symbol reader, data collection unit, or other device capable of transmitting data packet  
41 modulated carrier signals of the type described in said Application Serial No. 08/292,237, supra.

1 In some holographic scanning applications, where omni-directional scanning cannot be  
2 ensured at all regions within a prespecified scanning volume, it may be useful to use scan data  
3 produced either (i) from the same laser scanning plane reproduced many times over a very short  
4 time duration while the code symbol is being scanned therethrough, or (ii) from several different  
5 scanning planes spatially contiguous within a prespecified portion of the scanning volume. In  
6 the first instance, if the bar code symbol is moved through a partial region of the scanning  
7 volume, a number of partial scan data signal fragments associated with the moved bar code  
8 symbol can be acquired by a particular scanning plane being cyclically generated over an ultra-  
9 short period of time (e.g. 1-3 milliseconds), thereby providing sufficient scan data to read the bar  
10 code symbol. In the second instance, if the bar code symbol is within the scanning volume, a  
11 number of partial scan data signal fragments associated with the bar code symbol can be  
12 acquired by several different scanning planes being simultaneously generated by the three laser  
13 scanning stations of the system hereof, thereby providing sufficient scan data to read the bar code  
14 symbol, that is, provided such scan data can be identified and collectively gathered at a particular  
15 decode processor for symbol decoding operations.

16 In order to allow the bioptical holographic scanner of the present invention to use symbol  
17 decoding algorithms that operate upon partial scan data signal fragments, as described above, the  
18 0-th order signal detector and its associated processing circuitry are used to produce a periodic  
19 signal  $X(t)$ , as discussed briefly above. As the periodic signal  $X(t)$  is generated by the 0-th order  
20 of the incident laser beam passing through the outer radial portion of each holographic facet on  
21 the rotating scanning disc, this signal will include a pulse at the occurrence of each holographic  
22 facet interface. However, in order to uniquely identify a particular facet for reference purposes, a  
23 "gap" of prespecified width  $d_{gap}$ , as shown in Fig. 3A1, is formed between two prespecified  
24 facets (i.e.  $i=1$  and 6) at the radial distance through which the incident laser beam passes. Thus,  
25 in addition to the periodic inter-facet pulses, the periodic signal  $X(t)$  also includes a  
26 "synchronizing pulse" produced by the prespecified "gap" which is detectable every  $T=2\pi/\omega$   
27 [seconds], where  $\omega$  is the constant angular velocity of the holographic scanning disc maintained  
28 by the scanning disc motor and associated driver control circuitry. Thus, while the function of  
29 the 0-th order light detector is to detect the 0-th diffractive order of the incident laser beam, the  
30 function of its associated signal processing circuitry is to (1) detect the periodic occurrence of the  
31 "synchronizing pulse" in the periodic signal  $X(t)$  and (2) simultaneously generate a periodic  
32 synchronizing signal  $S(t)$  containing only the periodic synchronizing pulse stream. The  
33 construction of such pulse detection and signal generation circuitry is well known within the  
34 ordinary skill of those in the art.

35 As each synchronizing pulse in the synchronizing signal  $S(t)$  is synchronous with the  
36 "reference" holographic facet on the scanning disc, the decode processor (i.e. computer) (39A,  
37 39B, 39C, 39D) provided with this periodic signal can readily "link up" or relate, on a real-time  
38 basis, (1) each analog scan data signal  $D_i$  it receives with (2) the particular holographic facet on  
39 the scanning disc that generated the analog scan data signal. To perform such signal-to-facet  
40 relating operations, the decode computer is provided with information regarding the order in  
41 which the holographic facets are arranged on the scanning disc. Such facet order information

1 can be represented as a sequence of facet numbers (e.g.  $i = 1, 6, 3, 9, 7, 4, 8, 11, 5, 12, 2, 10, 1$ )  
2 stored within the associated memory of each decode processor. By producing both a scan data  
3 signal and a synchronizing signal  $S(t)$  as described above, the holographic scanner of the present  
4 invention can readily carry out a diverse repertoire of symbol decoding processes which use  
5 partial scan data signal fragments during the symbol reading process. The advantages of this  
6 feature of the system will become apparent hereinafter.

7 In code symbol reading applications where partial scan data signal fragments are used to  
8 decode scanned code symbols, the synchronizing signal  $S(t)$  described above can be used to  
9 identify a set of digital word sequences  $D_3$ , (i.e.  $\{D_s\}$ ), associated with a set of time-sequentially  
10 generated laser scanning beams produced by a particular holographic facet on the scanning disc.  
11 In such applications, each set of digital word sequences can be used to decode a partially scanned  
12 code symbol and produce symbol character data representative of the scanned code symbol. In  
13 code symbol reading applications where complete scan data signals are used to decode scanned  
14 code symbols, the synchronizing signal  $S(t)$  described above need not be used, as the digital  
15 word sequence  $D_3$  corresponding to the completely scanned bar code symbol is sufficient to  
16 carry out symbol decoding operations using conventional symbol decoding algorithms known in  
17 the art.

18 Referring to Figs. 5A1 through 5Z4, the omnidirectional laser scanning pattern generated  
19 by the bioptical holographic scanner hereof is illustrated in greater detail.

20 In Figs. 5A1 through 5A4, all of the laser scanning planes that are projected through the  
21 bottom and side scanning windows during the course of a complete revolution of the holographic  
22 scanning disc are shown simultaneously. It is understood, however, that at any instant in time,  
23 only four scanning planes (i.e. scanlines) are being simultaneously generated, but that during a  
24 complete revolution of the holographic scanning disc, all 50 scanning planes are generated from  
25 four scanning stations of the system. The order in which each scanning plane is produced during  
26 a single revolution of the scanning disc is described by the schematic representation shown in  
27 Fig. 6K. Notably, as shown in Fig. 6K, different angular portions of different scanning facets are  
28 used at different laser scanning stations in order to generate laser scanning planes that produce  
29 laser scan lines of particular lengths at particular depths of focus and spatial regions in the 3-D  
30 scanning volume of the system. For example, as shown in Fig. 6K, at the laser scanning station  
31 ST1, only a small angular portions of scanning facet Nos. 8, 10, and 12 are used to generate laser  
32 scanning planes from the bottom scanning window using mirror groups MG2@ST1, whereas  
33 substantially greater angular portions of scanning facet Nos. 7, 9 and 11 are employed to  
34 generate laser scanning planes from the bottom scanning window using mirror groups  
35 MG1@ST1, and almost the entire angular extent of scanning facet Nos. 1, 2, 3 and 4 are used to  
36 generate laser scanning planes from the bottom scanning window using mirror groups  
37 MG3@ST1. At scanning station ST4, substantially the entire angular extent of scanning facet  
38 Nos. 1, 2, 3 and 4 are used to generate laser scanning planes from the side scanning window  
39 using mirror groups MG3@ST4.

40 In order to more fully appreciate complexity and capabilities associated with the  
41 omnidirectional laser scanning pattern of the present invention, it will be helpful to describe the  
42 structure of such subcomponents, as well as the manner in which such subcomponents are

1 generated by particular holographic facets on the rotating scanning disc passing through  
2 particular laser scanning stations. Also, it will be helpful to show how, when such  
3 subcomponents of the laser scanning pattern are spatially combined within the space occupied  
4 between the bottom and side scanning windows, pairs of quasi-orthogonal scanning planes are  
5 produced therewithin to form the complete omnidirectional scanning pattern during each  
6 complete revolution of the holographic scanning disc.

7 As shown in Figs. 5B1 through C5, when scanning facets (Nos. 7, 9 and 11) having high  
8 elevation angle characteristics and left (i.e. positive) skew angle characteristics pass through the  
9 first laser scanning station (ST1), these scanning facets sequentially generate laser scanning  
10 beams that reflect off the first group of beam folding mirrors (MG1@ST1) associated therewith  
11 during system operation, and project substantially vertically-disposed laser scanning planes  
12 through the bottom scanning window for reading horizontally-oriented (i.e. ladder-type) bar code  
13 symbols.

14 As shown in Figs. 5D1 through 5E5, when scanning facets (Nos. 8, 10 and 12) having  
15 high elevation angle characteristics and right (i.e. negative) skew angle characteristics pass  
16 through the first laser scanning station (ST1), these scanning facets sequentially generate laser  
17 scanning beams that reflect off the second group of beam folding mirrors (MG2@ST1)  
18 associated therewith during system operation, and project substantially vertically-disposed laser  
19 scanning planes through the bottom scanning window for reading horizontally-oriented (i.e.  
20 ladder-type) bar code symbols.

21 As shown in Figs. 5F1 through 5G5, when scanning facets (Nos. 1 through 4) having low  
22 elevation angle characteristics and no (i.e. zero) skew angle characteristics pass through the first  
23 laser scanning station (ST1), these scanning facets sequentially generate laser scanning beams  
24 that reflect off the third group of beam folding mirrors (MG3@ST1) associated therewith during  
25 system operation, and project substantially horizontally-disposed laser scanning planes through  
26 the bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code  
27 symbols.

28 As shown in Figs. 5H1 through 5H10, when scanning facets (Nos. 1-4 and 7-12) pass  
29 through the first laser scanning station (ST1), they sequentially generate laser scanning beams  
30 that reflect off the first, second and third groups of beam folding mirrors (MG1@ST1,  
31 MG2@ST1 and MG3@ST1) associated therewith during system operation, and project both  
32 substantially horizontally and vertically disposed laser scanning planes through the bottom  
33 scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
34 horizontally-oriented (i.e. ladder type) bar code symbols, respectively.

35 As shown in Figs. 5K1 through 5L5, when scanning facets (Nos. 8, 10 and 12) having  
36 high elevation angle characteristics and right (i.e. negative) skew angle characteristics pass  
37 through the third laser scanning station (ST3), these scanning facets sequentially generate laser  
38 scanning beams that reflect off the first group of beam folding mirrors (MG1@ST3) associated  
39 therewith during system operation, and project substantially vertically disposed laser scanning  
40 planes through the bottom scanning window for reading horizontally-oriented (i.e. ladder type)  
41 bar code symbols.

1 As shown in Figs. 5M1 through 5N5, when scanning facets (Nos. 7, 9 and 11) having  
2 high elevation angle characteristics and left (i.e. positive) skew angle characteristics pass through  
3 the third laser scanning station (ST3), these scanning facets sequentially generate laser scanning  
4 beams that reflect off the second group of beam folding mirrors (MG2@ST3) associated  
5 therewith during system operation, and project substantially vertically disposed laser scanning  
6 planes through the bottom scanning window for reading horizontally-oriented (i.e. ladder type)  
7 bar code symbols.

8 As shown in Figs. 5O1 through 5P5, when scanning facets (Nos. 1-4) having low  
9 elevation angle characteristics and no (i.e. zero) skew angle characteristics pass through the third  
10 laser scanning station (ST3), these scanning facets sequentially generate laser scanning beams  
11 that reflect off the third group of beam folding mirrors (MG3@ST3) associated therewith, and  
12 project substantially horizontally disposed laser scanning planes through the bottom scanning  
13 window for reading vertically-oriented (i.e. picket-fence type) bar code symbols during system  
14 operation.

15 As shown in Figs. 5Q1 through 5R5, when scanning facets (Nos. 1-4 and 7-12) pass  
16 through the third laser scanning station (ST3), these scanning facets sequentially generate laser  
17 scanning beams that reflect off the first, second and third groups of beam folding mirrors  
18 (MG1@ST3, MG2@ST3 and MG3@ST3) associated therewith during system operation, an  
19 project both substantially horizontally and vertically disposed laser scanning planes through the  
20 bottom scanning window for reading vertically-oriented (i.e. picket-fence type) bar code symbols  
21 and horizontally-oriented (i.e. ladder type) bar code symbols, respectively.

22 As shown in Figs. 5S1 through 5T5, when scanning facets (Nos. 1-12) pass through the  
23 first, second and third laser scanning stations (ST3, ST2 and ST3), these scanning facets  
24 sequentially generate laser scanning beams that reflect off the groups of beam folding mirrors  
25 (MG1@ST1, MG2@ST1, MG3@ST1, MG3@ST2, (MG1@ST3, MG2@ST3 and MG3@ST3)  
26 associated therewith during system operation, and project both substantially horizontally and  
27 vertically disposed laser scanning planes through the bottom scanning window for reading  
28 vertically-oriented (i.e. picket-fence type) bar code symbols and horizontally-oriented (i.e. ladder  
29 type) bar code symbols, respectively.

30 As shown in Figs. 5U1 through 5V5, when scanning facets (Nos. 7-12) pass through the  
31 fourth laser scanning station (ST4), these scanning facets sequentially generate laser scanning  
32 beams that reflect off the groups of beam folding mirrors (MG1@ST4 and MG2@ST4)  
33 associated therewith during system operation, and project substantially vertically disposed laser  
34 scanning planes through the side scanning window for reading horizontally-oriented (i.e. ladder  
35 type) bar code symbols.

36 As shown in Figs. 5W1 through 5X5, when scanning facets (Nos. 1-6) pass through the  
37 fourth laser scanning station (ST4), these scanning facets sequentially generate laser scanning  
38 beams that reflect off the third group of beam folding mirrors (MG3@ST4) associated therewith  
39 during system operation, and project substantially horizontally disposed laser scanning planes  
40 through the side scanning window for reading vertically-oriented (i.e. picket-fence type) bar code  
41 symbols.



1 As shown in Figs. 5Y1 through 5Z4, when scanning facets (Nos. 1-12) pass through the  
2 fourth laser scanning station (ST4), these scanning facets sequentially generate laser scanning  
3 beams that reflect off the first, second and third groups of beam folding mirrors (MG1@ST4,  
4 MG2@ST4 and MG3@ST4) associated therewith during system operation, and project both  
5 substantially horizontally and vertically disposed laser scanning planes through the side scanning  
6 window for reading vertically-oriented (i.e. picket-fence type) bar code symbols and  
7 horizontally-oriented (i.e. ladder type) bar code symbols, respectively.

8 The time sequential order in which each laser scanning plane is cyclically generated from  
9 the bioptical holographic laser scanning system of the illustrative embodiment described above,  
10 is shown in the schematic "facet versus timing" diagram of Fig. 6K.

11  
12 DESIGNING A BIOPTICAL HOLOGRAPHIC LASER SCANNING SYSTEM  
13 ACCORDING TO THE METHOD OF THE PRESENT INVENTION  
14

15  
16 The basic design method disclosed in US Patent No. 08/949,915 filed October 14, 1997,  
17 now U.S. Letters Patent No. 6,158,659, incorporated herein by reference, can be used to design  
18 the bioptical laser scanning system of the present invention. However, a recursive design method  
19 described hereinbelow with reference to Figs. 7A through 7R is typically a more preferred  
20 method when the laser scanning pattern to be generated from the system is complex, as in the  
21 case of a high-performance bioptical POS laser scanner, as disclosed herein.

22 Referring to Figs. 7A through 7R, the major steps involved in practicing the holographic  
23 scanner design method hereof will now be described in great detail. Notably, the terms  
24 "holographic scanner design method" and "scanner design method" are employed herein to  
25 describe the overall process used to design all of the subsystems of the holographic laser scanner  
26 including, but not limited to, the holographic scanning disc, the beam folding mirror array, the  
27 light collecting and detecting subsystem, the laser beam production modules, as well as the  
28 scanner housing within which such subsystems are compactly contained. Thus, the holographic  
29 scanner design method hereof comprises a collection of subsystem design methods and processes  
30 which interact with each other to provide a composite method. In general, there are numerous  
31 embodiments of the holographic scanner design method of the present invention. Factors which  
32 influence the design of the scanning disc and light detection subsystem include, for example, the  
33 polarization state of the incident laser beam used during scanning operations, as well as the  
34 polarization state of the laser light rays collected, focused and detected by the light collecting and  
35 detecting subsystem used during light collecting and detecting operations.

36 In the illustrative embodiments of the present invention, the scanner design methods  
37 hereof are carried out on a computer-aided design (CAD) workstation which can be realized  
38 using a computer system, such as the Macintosh 8500/120 computer system. In the illustrative  
39 embodiment, the CAD-workstation supports a 3-D geometrical database for storing and  
40 retrieving information representative of 3-D models of the holographic scanning apparatus and  
41 processes under design; as well as a relational database for storing and retrieving information  
42 representative of geometrical and analytical models holographic laser scanning apparatus and

processes under design. In addition, the CAD workstation includes a diverse array of computer programs which, when executed, provide a number of important design and analysis tools. Such design and analysis tools include, but are not limited to: 3-D geometrical modeling tools (e.g. AUTOCAD geometrical modeling software, by AutoDesk, Inc. for creating and modifying 3-D geometrical models of virtually every aspect of the holographic laser scanning apparatus and processes under design; robust mathematical modeling tools (e.g. MATHCAD 3.1 for Macintosh by MathSoft, Inc. of Cambridge, Massachusetts) for creating, modifying and analyzing mathematical models of the holographic scanning apparatus and processes under design; and spreadsheet modeling tools (e.g. EXCEL by Microsoft Corporation, or LOTUS by Lotus Development Corporation) for creating, modifying and analyzing spreadsheet-type analytical models of the holographic scanning apparatus and processes under design. For purposes of simplicity of expression, the above-described CAD workstation and all of its tools shall be collectively referred to as the "Holographic Scanner Design (HSD) workstation" of the present invention. Where necessary or otherwise appropriate, the functionalities and tools of the HSD workstation will be elaborated in greater detail hereinafter.

As indicated in Fig. 7A, step A1 of the scanner design method involves geometrically specifying the volumetric (e.g. physical) dimensions of the scanner housing of a holographic laser scanner to be designed. In the illustrative embodiment, the laser scanner is a holographic bioptical laser scanning system having a pair of vertically and horizontally arranged scanning windows formed therein. Such geometric specifications include the position and size of a pair of vertically and horizontally arranged scanning windows formed therein, from which a complex omni-directional laser scanning pattern is to be generated and projected therefrom.

As indicated in Fig. 7A, step A2 of the scanner design method involves creating a 3-D Solid Geometry Model of the optical bench of the scanner and the scanner housing supported thereupon. The 3-D solid geometry model can be created on a computer workstation (e.g. O<sub>2</sub> workstation from Silicon Graphics, Inc.) running a 3-D solid geometry program (e.g. Designer from Alias-Wavefront, Inc. of Toronto, Canada) or any other suitably programmed computer system equipped with 3-D solid modeling software (e.g. CADKEY 3-D solid modeling software from CADKEY Corporation of Marlborough, Massachusetts).

As indicated in Fig. 7A, step A3 of the scanner design method involves producing a geometrical specification of the generalized 3-D structure of the laser scanning pattern and scanning volume to be generated from such scanning windows. Such geometrical specifications include scanning performance parameters (e.g. the volumetric dimensions of the laser scanning pattern, laser beam spot size of the laser scanning planes projected therewithin), as well as the focal zones of the scanning pattern required to read a predetermined set of bar code symbol structures). Preferably, such geometrical specifications will involve the creation of a 3-D solid geometry model of the composite laser scanning pattern to be generated from the holographic laser scanning system under design. In the illustrative embodiment, a 3-D geometrical model of the composite laser scanning pattern is schematically depicted in Figs. 5A1 through 5V4. While it is not necessary to develop the model in such detail, it will be helpful to create sufficient structure for each of the laser scanning planes to be generated from the laser scanning platform under design. In general, the better the specification of the desired laser scanning pattern, the

1 easier it will be for the designer to determine if he or she is on course with regards to the system  
2 design process. It is understood, however, that in some instances, it may be desirable to employ a  
3 generalized laser scanning specification and allow a great deal of flexibility during the later  
4 stages of the design process. Naturally, the resolution of the bar code symbols to be read will  
5 determine the largest cross sectional dimension that each scan line can be in order to resolve the  
6 bar code symbol. Thus, it will be necessary to provide a proper specification of the maximum  
7 cross-sectional diameter of the scanned laser beams within the specified scanning volume.

8 As indicated in Fig. 7B, step B1 of the scanner design method involves selecting an  
9 architecture for a holographic laser scanning platform to be designed and realized upon the  
10 optical bench within the specified scanner housing. In the illustrative embodiment, the  
11 holographic laser scanning platform is that schematically depicted in Figs. 2A through 2K2. As  
12 shown therein, the selected scanning platform generally comprises: a plurality of laser scanning  
13 stations arranged about a holographic scanning disc having a plurality of left-skewed holographic  
14 scanning facets with both high and low elevation diffraction angles and a plurality of right-  
15 skewed holographic scanning facets with both high and low elevation diffraction angles. As  
16 described hereinabove, each laser scanning station (i.e. ST1, ST2, and ST3) comprises: a laser  
17 beam production module (LBPM); a first plurality of laser beam folding mirrors for folding laser  
18 beams diffracted from the plurality of left-skewed holographic scanning facets; a second  
19 plurality of laser beam folding mirrors for folding laser beams diffracted from the plurality of  
20 right-skewed holographic scanning facets; a laser light collection and detection subsystem  
21 having a parabolic (or elliptical) light focusing mirror disposed beneath the holographic scanning  
22 disc and a photodetector disposed about the holographic scanning disc; a scan data signal  
23 processing board for processing the analog scan data signals produced from the photodetector  
24 and producing digital character data; and a decode processing board for processing digital scan  
25 data and producing symbol character data. In the illustrative embodiment, the holographic laser  
26 scanning platform for the bioptic holographic laser scanner comprises: a holographic scanning  
27 disc having twelve (12) holographic optical elements (HOEs) or facets and three laser scanning  
28 stations. Three of the laser beam scanning stations are arranged about the holographic scanning  
29 disc for generating the first, second and third partial laser scanning patterns from the bottom  
30 scanning window. The fourth laser scanning station is mounted within the vertical portion of the  
31 scanner housing, and employs a set of beam folding mirrors to project the fourth partial laser  
32 scanning pattern out the vertical scanning window and above the bottom scanning window. Each  
33 of these subcomponents have been described in great detail hereinabove.

34 As indicated in Fig. 7B, step B2 of the scanner design method involves creating a 3-D  
35 Solid Geometry Model for each laser scanning station in the Holographic Scanning System. In  
36 the illustrative embodiment, this step of the design procedure can be carried out using the 3-D  
37 solid modeling system to create a parameterized 3-D solid model for each such laser scanning  
38 station.

39 As indicated in Fig. 7B, step B3 of the scanner design method involves using a 3-D solid  
40 modeling system to integrate the 3-D solid geometry models of the scanner housing, optical  
41 bench, holographic scanning disc, and laser scanning stations, thereby forming a composite 3-D  
42 solid geometrical model for the bioptic holographic laser scanning system under design.

1 As indicated in Fig. 7B, step B4 of the scanner design method involves symbolically  
2 embedding the first locally-defined hybrid Cartesian/Polar Coordinate System  $R_{local\ 1}$  within the  
3 composite 3-D solid geometry model of the holographic laser scanning system, as shown in Fig.  
4 2A1. The function of local coordinate reference system is to enable the specification of the  
5 propagation of laser beams generated from the laser beam production module of Laser Scanning  
6 Station No. 1 through the facets on the holographic scanning disc, and off the beam folding  
7 mirrors associated with the Laser Scanning Station, through the Bottom Scanning Window  
8 formed in the Scanner Housing.

9 As indicated in Fig. 7C, step B5 of the scanner design method involves symbolically  
10 embedding a second locally-defined hybrid Cartesian/Polar Coordinate System  $R_{local\ 2}$  within the  
11 composite 3-D solid geometry model of the Holographic Laser Scanning System, as shown in  
12 Fig. 2A1. The function of local coordinate reference system is to enable the specification of the  
13 propagation of laser beams generated from the laser beam production module of Laser Scanning  
14 Station No. 2 through the facets on the holographic scanning disc, and off the beam folding  
15 mirrors associated with the Laser Scanning Station, through the Bottom Scanning Window  
16 formed in the Scanner Housing.

17 As indicated in Fig. 7C, step B6 of the scanner design method involves symbolically  
18 embedding a third locally-defined hybrid Cartesian/Polar Coordinate System  $R_{local\ 3}$  within the  
19 composite 3-D solid geometry model of the Holographic Laser Scanning System, as shown in  
20 Fig. 2A1. The function of local coordinate reference system is to enable the specification of the  
21 propagation of laser beams generated from the laser beam production module of Laser Scanning  
22 Station No. 3 through the facets on the holographic scanning disc, and off the beam folding  
23 mirrors associated with the Laser Scanning Station, through the Bottom Scanning Window  
24 formed in the Scanner Housing.

25 As indicated in Fig. 7C, step B7 of the scanner design method involves symbolically  
26 embedding a fourth locally-defined hybrid Cartesian/Polar Coordinate System  $R_{local\ 3}$  within the  
27 composite 3-D solid geometry model of the Holographic Laser Scanning System, as shown in  
28 Fig. 2A1. The function of local coordinate reference system is to enable the specification of the  
29 propagation of laser beams generated from the laser beam production module of Laser Scanning  
30 Station No. 4 through the facets on the holographic scanning disc, and off the beam folding  
31 mirrors associated with the Laser Scanning Station, through the Bottom Scanning Window  
32 formed in the Scanner Housing.

33 As indicated in Fig. 7D, step B8 of the scanner design method involves symbolically  
34 embedding a globally-defined hybrid Cartesian/Polar Coordinate System  $R_{global}$  within the 3-D  
35 solid geometry model of the Holographic Laser Scanning System, as shown in Fig. 2A1. The  
36 function of this global coordinate reference system is to enable the specification of the  
37 propagation of laser beams generated from Laser Scanning Station Nos. 1, 2, 3 and 4 relative to  
38 the globally-based coordinate system  $R_{global}$ .

39 As indicated in Fig. 7D, step CA1 of the scanner design method involves creating, for  
40 each scanning facet passing through each Laser Scanning Station in the Holographic Scanning  
41 System, an analytical-based light diffraction model of the laser beam as it propagates from its  
42 laser beam production module (LBPM), towards and through each scanning facet on the

1 holographic scanning disc in the system, as the scanning disc rotates about its axis of rotation.  
2 This analytical-based light diffraction model is also known as a laser scanning beam production  
3 model, and is set forth in Figs. 8A through 8E. Preferably, this laser beam production model is  
4 created using spread-sheet based modeling tools which enable the embodying all of the  
5 analytical relationships defined in Figs. 8A through 8E.

6 As indicated in Fig. 7D, step C1B of the scanner design method involves converting the  
7 analytical-based diffraction models created in Step C1A into corresponding vector-based light  
8 diffraction models of the laser beam diffraction processes, illustrated in Figs. 8F1 through 8F5.  
9 The purpose of converting each analytical-based diffraction model to a vector-based light  
10 diffraction model is that it facilitates the computation of the x,y,z coordinates of outgoing  
11 diffracted laser beams. The use of a spreadsheet type program to perform such vector-based  
12 modeling facilitates the updating and sequential generation of outgoing diffracted laser beams  
13 along the start, middle and end of each scanning facet, as well as the convenient management  
14 and display of such coordinate data during the system design process. The function of the  
15 vector-based light diffraction model is to model the laser scanning plane generation processes  
16 carried out at each scanning station and generate the x,y,z components of each diffracted laser  
17 beam towards its point of focus as each scanning facet rotates through the incident laser beam  
18 which is maintained at a substantially constant incident angle thereto. These x,y,z components  
19 are stored in a Summary Table and describe the coordinates of each laser scanning plane  
20 generated from the system as the scanning disc rotates about its axis during each complete  
21 revolution.

22 In the illustrative embodiment, the vector-based light diffraction model for each scanning  
23 facet is schematically illustrated in Figs. 8F1, 8F2, 8F3, 8F4 and 8F5. As shown in these figures,  
24 the incoming laser beam (i.e. incident) to scanning disk at angle A, is defined by a Reference  
25 vector (i.e. unit input vector) R which is the same for all scanning facets on the disc. Each  
26 outgoing diffracted laser beam is defined by an Object vector O, specified by (i) a point source  
27 located at the diffraction focal length (focus) of the scanning facet, (ii) the elevation angle (angle  
28 B) of the scanning facet, and (iii) the skew angle thereof, as shown in Fig. 8B.

29 As each incident laser beam is generated by a collimated light source (passing through  
30 the disc at angle A), the Reference beam  $R_p$  for any point p on the scanning disk is the same, i.e.  
31  $R_p=R$ . The Object beam emanating from any point p on the scanning facet shall be designated as  
32  $O_p=O-D$ , where D is the vector from the center point of the scanning disc annulus to an arbitrary  
33 point p on the scanning facet. Notably, vector D in the above expression is not explicitly shown  
34 in the vector model of Figs. 8F1 and 8F2, but is figured into the calculations employed therein.

35 Each outgoing diffracted laser beam (i.e. exiting ray) is calculated when the arbitrary  
36 point p on the scanning facet is rotated over the incoming laser beam. The rotation causes a new  
37 orientation for vector  $R_p$  in the local co-ordinate system which shall be designated as  $R_p'$ . This  
38 new value is stored within the spreadsheet modeling program. Likewise the object ray O is  
39 rotated and the new value with respect to the locale co-ordinate system is calculated and stored in  
40 the spreadsheet modeling program. The exiting diffracted laser beam, or object ray, is calculated  
41 (i.e. as a unit output vector) using the grating equation:  
42

$$O_p' = R - R_p' + O'$$

described in detail in "Handbook of Optical Holography" by H.J. Caulfield, Academic Press pp. 575-576, except that different notation has been used herein, and some simplifications have been made.

In Fig. 8F3, a schematic diagram is shown illustrating how the z component of the diffracted object ray (at point p) is calculated by the spreadsheet modeling program. In Fig. 8F4, a schematic diagram is shown illustrating how the x and y components of the diffracted object ray (at point p) are calculated by the spreadsheet modeling program, and that the object vector  $O_p$  is composed by combining the x,y,z components thereof, as expressed in detail in Fig. 8F5.

As each facet is rotated through the incident laser beam, the x,y,z components of the computed Object ray (i.e. exiting diffracted laser beam) are stored in a Summary Table maintained by the spreadsheet program. The purpose of the Summary table is to organize the data calculated above for ready access by other programs during the design process. The Summary Table consists of a column of facet numbers and the associated unit output vectors for the middle, start and end of scanning lines expressed in x, y, z Cartesian format. These vectors are simply copied from the locations where they were calculated.

The vector-based light diffraction models as described above are used to model the laser scanning plane generation processes carried out at each scanning station and generate the x,y,z components of each diffracted laser beam towards its point of focus as each scanning facet rotates through the incident laser beam which is maintained at a substantially constant incident angle thereto as will now be described in detail.

As indicated in Fig. 7E, step C1C of the scanner design method involves assigning, to each scanning facet moving through each of the Laser Scanning Stations in the system, initial (or updated) values to the following scanning facet parameters: the input angle  $A_i$ , the elevation angle  $B_i$ , the skew angle  $\theta_{skewi}$ , the scan angle  $\theta_{rofi}$ , the (diffraction) focal length  $f_i$  of the facet, and the beam diameter at the point of incidence of the laser beam on the scanning disc, required to generate the desired laser scanning planes from the system under design.

As indicated in Fig. 7E, step C2A of the design method involves creating a geometrical optics model, for each scanning facet on the scanning disc, by computing the equalized facet area  $A_i$  for each facet which ensures equalized light collection therefrom. In the illustrative embodiment, this procedure uses polarization-dependent light diffraction efficiency analysis, Lambertian light collection analysis etc. in order to determine the area for each facet that ensures that the same amount of light is collected by the corresponding photodetector. The input parameters for the analytical model used to perform such calculations are: the focal length of each facet; the skew angle of the facet; the elevation angle of each facet; the incidence angle of each facet; the inner radius of the scanning disc; the outer radius of the scanning disc; and the total number of facets on the scanning disc. Notably, as the facet area is not a parameter in the diffraction-based model, this step need only be carried out when the diffraction angles, focal lengths and scanning patterns are attained by a particular configuration.

As indicated in Fig. 7E, step C2B of the design method involves numerically evaluating, for each scanning facet on the scanning disc, the relative light diffraction factor  $H_i$  and the

modulation depth  $\Delta n_i$  required to achieve the same, and then store these values in the spreadsheet program.

Fig. 10A2 defines the facet design parameters that pertain to the optimization of the facet areas on the disc. The incidence plane contains the incident beam and the normal to the disc. The incidence angle,  $\theta_i$  and angle A are measured in the incidence plane. The diffraction plane contains the diffracted beam and the normal to the disc. The diffraction angle,  $\theta_d$ , and angle B are measured in the diffraction plane. The angle between these two planes is defined as the skew angle,  $\phi_{skew}$ .

Additional parameters used in the determination of the facet areas are defined in Fig. 10A3. The top view of the holographic disc shows the orientation of the grating structure at an angle  $\theta_{Ro}$  away from being perpendicular to the incidence plane. Section A-A in Fig. 10A4 shows a view of the parallel Bragg surfaces within the holographic medium of the scanning disc. Notably, section A-A shows a relatively large gelatin thickness simply for clarity. The angles in that figure drawing are denoted by a prime (') since those angles, as seen from the A-A perspective, are projections of the actual angles into the plane of A-A from either the incidence or diffraction plane. Fig. 10B lists the definitions of the parameters indicated in Figs 10A2 and 10A3, along with some additional parameters used in determining the diffraction efficiency of the facets. All of these parameters are used in determining the relative efficiency factors,  $H_i$ , of the facets, and thereby the relative facet areas.

In determining the design facet efficiencies the following parameters are given: incidence angle, diffraction angle, skew angle, facet angular width (defined previously as  $\theta_{ROT}$ ), average bulk refractive index of the holographic medium, S-polarization losses, and P-polarization losses. The effective gelatin thickness is also chosen ahead of time, with the intent of it being as thin as possible while still being able to modulate the refractive index far enough to achieve high diffraction efficiency. The reason for desiring a thin film is that efficiency varies more with disc rotation when the film is thicker (i.e. a result of Bragg sensitivity being greater when the film is thicker). As uniform efficiency is desired, a film as thin as possible is therefor also desired. However, the thinner the film, the higher the index modulation,  $n_1$ , must be in order to maximize the design efficiency, and there are limits on how high the modulation can go. Also, if the film is too thin, the efficiency of the third pass of the light through the disc from the light collector mirror to the photodetector will be reduced. Bearing these considerations in mind, a suitable effective film thickness is chosen.

Determining the design facet efficiencies involves applying a numerical solving algorithm to a complex non-linear formula. That formula is governed by the equations in Figs. 10C1 through 10C3. The input constants of the formula are given above, the variables of the formula are the index modulation and the Bragg plane tilts, and the output of the formula relates Equations (19) & (22) to a solution goal. For ease of computation, and production, it is more convenient to use the maximum efficiency incidence angle,  $\phi_{imax}$ , that results from the Bragg plane tilt as the variable, rather than the Bragg plane tilt itself. This angle is not to be confused with the design incidence angle at which the laser beam strikes the disc when in use. The goal is achieved by allowing the numerical solver to vary the variables of the formula until Equation

(22) is satisfied and Equation (19) is maximized for all facets. Equation (19) is the total diffraction efficiency of a given facet. Equation (22) is an expression which dictates the most uniform *relative signal collection* within a given facet.

Signal, as it is being referred to here, is the total amount of light being collected at any instant by a given facet. The variation in the amount of light collected as the disc rotates is referred to as the relative signal. It is normalized to some arbitrary amount, and is therefore unitless. The relative signal is directly proportional to the total facet efficiency,  $T_s$ , and to the facet area projected in the direction of the diffracted beam. Both of these values are functions of disc rotation. Furthermore, the projected facet area can be expressed as the product of some constant with the cosine of the diffraction angle. As a result, the relative signal can be expressed as the product of the total facet efficiency with the cosine of the diffraction angle.

Specific solutions of Equation (22) are graphically depicted in Figs. 10D1 and 10D2 for facets 1 and 12 respectively. The plots in these figures show the variation of (diffraction) efficiency with disc rotation. The rotation angles are measured from the center of the given facet (zero on the abscissa), at which point the facet (i.e. grating) has an orientation angle of  $\theta_{Ro}$  (nominal angle). It can be seen from Fig. 10D1 that as the incident laser beam approaches a more positive rotation angle, the efficiencies tend to rise. This is due to the maximum efficiency incidence angle being optimized to a value less than the working incidence angle. This effect offsets the fact that as we rotate in that direction the facet area appears smaller and smaller. The result is that the relative signal produced at the left extreme facet position ( $\theta_R = \theta_{Ro} - \theta_{ROTi}$ ) is equal to the relative signal produced at the right extreme facet position ( $\theta_R = \theta_{Ro} + \theta_{ROTi}$ ), and thereby Equation (22) is satisfied.

Using the facet design techniques described above, it is now possible to design and construct holographic scanning discs having facets with skew angle characteristics, wherein the incident Bragg angle of each facet is optimized so that the total light collection efficiency thereof exhibits maximal uniformity with respect to facet rotation. In summary, this technique involves varying the diffraction efficiency function of each facet (dependent on facet rotation angle) by (i) varying the Bragg Angle of the facet until (ii) the product of the diffraction efficiency function and the collection aperture function is observed to exhibit maximum uniformity with respect to facet rotation angle.

As a result of this aspect of the present invention, it is now possible to design and manufacture holographic scanning discs (i) having minimal diffraction efficiency variation with respect to disc rotation, as shown in Fig. 10D2 and 10E2, and therefore (ii) capable of generating laser scanning beams having more uniform performance characteristics.

As indicated in Fig. 7E, step C2C of the design method involves numerically evaluating, for each i-th scanning facet, the relative light collection efficiency  $\xi_i$  thereof. This step involves using Equation No. 7 set forth in the table of Fig. 8E.

As indicated in Fig. 7E, step C2D of the design method involves numerically evaluating, for each i-th scanning facet, the total light collection area  $A_i$  thereof, using substantially all of the surface area available on the scanning disc. This step involves using Equation No. 8 set forth in the table of Fig. 8E.



1 As indicated in Fig. 7F, step C2E of the design method involves determining, for  
2 each i-th scanning facet, the minimal value for the inner radius  $r$ , which allows the desired  
3 housing height using a reiterative computational procedure described in detail in US Patent No.  
4 08/949,915 filed October 14, 1997, now U.S. Letters Patent No. 6,158,659, incorporated herein  
5 by reference.

6 As indicated in Fig. 7F, step C2F of the design method involves verifying that  
7 geometrical parameters obtained for each i-th scanning facet above allow the facets to be  
8 physically laid out on the available surface area upon the scanning disc. Techniques for carrying  
9 out this step of the method are disclosed in US Patent No. 08/949,915 filed October 14, 1997,  
10 now U.S. Letters Patent No. 6,158,659.

11 As indicated in Fig. 7F, step C2G of the design method involves confirming that light  
12 transmission efficiencies along the outgoing and relative optical paths produce sufficient power  
13 levels at photodetection. This step of the method is carried out using the spreadsheet information  
14 table set forth in Fig. 9.

15 As indicated in Fig. 7F, step C3A of the design method involves using the facet  
16 parameters computed in step C2A to compute a set of Construction Parameters for each facet on  
17 the scanning disc. This step of the method is described in detail in US Patent No. 08/949,915  
18 filed October 14, 1997, now U.S. Letters Patent No. 6,158,659.

19 As indicated in Fig. 7F, step C3B of the design method involves using the set of  
20 Construction Parameters computed in step C3A to construct a Construction Vector and thereafter  
21 install the Construction Vector into the Vector-Based Light Diffraction Model created in Step  
22 C1B for each of the facets on the scanning disc.

23 As indicated in Fig. 7G, step C4A of the design method involves specifying the depth of  
24 focus (DOF) and the minimum beam spot size (i.e. cross-sectional diameter) of the laser  
25 scanning planes to be generated from each facet on the scanning disc at each of the laser  
26 scanning stations. In practice, this step involves considering the assumed (i.e. initial value)  
27 focal length of the facet (i.e. its optical power), and then based on this specification, specifying  
28 the effective beam diameter (i.e. at the  $1/e^2$  power point along the laser beam) that the scanned  
29 laser beam must have in the S and P polarization directions at the collimating lens L of the laser  
30 beam production module (LBPM) in each Laser Scanning Station so that the desired depth of  
31 focus and laser beam cross-sectional characteristics are attained throughout the scanning volume  
32 by the resulting laser scanning plane.

33 As illustrated in Fig. 11A1, a spreadsheet-type laser beam truncation analysis program is  
34 used to obtain the following measures: (1) the effective beam diameter (i.e.  $1/e^2$  diameter) in the  
35 S and P polarization directions at the collimating lens within the laser beam production module  
36 (LBPM) under design; and (2) light intensity loss characteristics. The fixed input parameters to  
37 this program are VLD output wavelength  $\lambda_{VLD}$ ,  $\theta_s$ , and  $\theta_p$ ; and the variable input parameters are  
38 lens parameters such as, for example, focal length (mm), numerical aperture, clear aperture, etc.  
39 The output from this program is the effective beam diameter  $d_e$  in the S and P directions at the  
40 lens, and the light intensity loss ( $1/e^2$ ).

41 Given the laser and lens parameters, the spreadsheet truncation analysis program  
42 calculates the effect of truncation on the laser beam. The final result of the program is an

1 “effective diameter” which is an equivalent  $1/e$ -squared diameter that will produce the same spot  
2 at the focal point as the actual truncated laser beam. This is also the beam diameter that will be  
3 inserted into the main scanner disc design spreadsheet program. The actual number linked to the  
4 main scanner disc design spreadsheet program will be a rounded number. It will usually be  
5 rounded up to 0.1 to allow for tolerances. Fig. 11A2 sets forth a graphical plot of data produced  
6 by the truncation analysis spreadsheet program when numerically integrating the diffraction  
7 equation  $A(z)$ , as described in Fig. 11A1.

8 A Gaussian Analysis spreadsheet program, as shown in Figs. 11B1 and 11B2, is then  
9 used to measure the amount of light intensity lost by virtue of truncation and propagation along  
10 the outgoing optical paths of the system. In the illustrative embodiment, the Gaussian Beam  
11 Analysis spreadsheet program has the following input parameters: wavelength of VLD, effective  
12 beam diameter at scanning disc  $d_e$  (linked from the Truncation Analysis spreadsheet program),  
13 and assumed focal length of the holographic facet(s); the output from the program is the  
14 minimum beam spot size at light intensity loss ( $1/e^2$ ) of the outgoing laser beam, and depth of  
15 field for each group of holographic facets.

16  
17 As indicated in Fig. 7G, step C4B of the design method involves using the results from  
18 Step C4A above and initial facet parameters, to specify the focal length and numerical aperture  
19 of the VLD lens in the Refraction-Based Model of the Laser Beam Production Modules (used in  
20 the Holographic Scanning System) so as to produce laser scanning planes having the DOF and  
21 minimum beam spot size characteristics specified in Step C4A.

#### 22 23 Steps Involving The Design Of Laser Scanning Station No. 1

24  
25 As indicated in Fig. 7H, step C5 of the design method involves assigning, for each  
26 scanning facet passing through Laser Scanning Station No. 1, (initial or updated) coordinate  
27 values for the position and orientation of each beam folding mirror employed in the Laser  
28 Scanning Station No. 1, and using such coordinate values, constructing a Vector-Based  
29 Reflection Model of the propagation of the laser beam diffracted from the scanning facet towards  
30 and off the laser beam folding mirrors in the Laser Scanning Station so as to enable the  
31 geometrical modeling of laser scanning plane generation processes during each revolution of the  
32 holographic scanning disc about its axis of rotation.

33 As indicated in Fig. 7H, step C6A of the design method involves, for each scanning facet  
34 passing through Laser Scanning Station No. 1, integrating the Vector-Based Diffraction Model  
35 created in Step C2A and the Vector-Based Reflection Model created in STEP C5 so as to create  
36 a Vector-Based Geometric Optics Model of the laser scanning plane process generated from the  
37 scanning facet as it is passed through Laser Scanning Station No. 1.

38 As indicated in Fig. 7H, step C6B of the design method involves importing the Vector-  
39 Based Geometric Optics Model created during Step C6A, into the 3-D Solid Geometry Model of  
40 the Holographic Scanning System created during Step B3 in order to enable the 3-D Solid  
41 Geometry Model of the Holographic Scanning System to generate, relative to the global

coordinate reference system rglobal, geometrical models of the laser scanning planes produced during each revolution of the holographic scanning disc.

As indicated in Fig. 7I, step C7 of the design method involves using the Vector-Based Geometric Optics Models embodied within the 3-D Solid Geometry Model of the Holographic Scanning System to graphically plot the partial laser scanning pattern resulting from laser scanning beam production processes supported upon Laser Scanning Station No. 1.

As indicated in Fig. 7I, step C8 of the design method involves determining whether the parameters in the vector-based geometric optics model are optimally set so that the laser scan planes produced from laser scanning station 1 converge towards the desired laser scanning planes to be generated therefrom. If the designer determines that the laser scanning planes produced from laser scanning station ST1 have not yet converged towards the desired laser scanning planes to be generated therefrom, then the design process proceeds to step C9 in Fig. 7H, at which point the designer may, as necessary, modify the position of the beam folding mirrors employed in Laser Scanning Station ST1, and/or modify the facet parameters on the scanning disc as deemed necessary to achieve correspondence therebetween or to achieve an otherwise desired laser scanning pattern. Thereafter, the design process returns to Step C5, where updated coordinate values are reassigned to the position and orientation of each beam folding mirror, and vector-based reflection models are modified based on such modified coordinate values. During each recursive loop from Steps (i.e. Blocks) C5 through C8, Truncation Analysis and Gaussian Beam Analysis used in Steps C4 and C5 can be re-performed in connection with Laser Scanning Station ST1, in order to re-specify the VLD lens in Geometrical Optics Model of each LBPM, and determine the depth of field and resolution parameters for each scanning plane generated from the holographic scanning disc.

If the designer determines at Step C8 that the laser scanning planes produced from laser scanning station ST1 have converged towards the desired laser scanning planes to be generated therefrom, then the design process proceeds to Block C10 in Fig. 7I, at which point (Step twenty-four), the designer optimizes the physical dimensions of each beam folding mirror in laser scanning station ST1. After a number of recursive loops, the parameters in the Vector-Based Geometric Optics Model will be optimally set so that the laser scanning planes produced from Laser Scanning Station No. 1 converge towards the desired Laser Scanning Planes to be generated therefrom, and each beam folding mirror has been truncated to a minimal set of dimensions.

In the illustrative embodiment, Step C10 is generally carried out by projecting the light collection geometry of each scanning facet (preferably specified by a set of vectors as shown in Fig. 12D) onto the first outgoing beam folding mirror (and each successive beam folding mirror) in the group of beam folding mirrors involved in the generation of each scanning plane from the Laser Scanning Station ST1, and then analyzing such geometrical projections on each given beam folding mirror to find the geometrical boundaries that covers the geometrical projections for the given beam folding mirror. The given beam folding mirror is trimmed such that its outer periphery corresponds to such geometrical boundaries, thereby minimized surface dimensions of the given beam folding mirror while maximum number of return light rays collected by the beam folding mirror. This geometrical projection process will be described below with reference to

1 Figs. 12A1 through 13D1, for the case addressing Scanning Stations No. 1, in particular. Figs.  
2 12A-12D and 14A1-14D1, address Scanning Station No. 2, whereas Figs. 12A-12D and 15A1-  
3 15D3, address Scanning Station No. 4.

4 In general, the first step of the facet trimming method involves specifying: the vertices  
5 of each facet on the disc using a set of vectors defined relative to the first local coordinate  
6 reference system  $R_{local\ 1}$ ; and the vertices of each beam folding mirror (associated with a  
7 particular scanning plane generation process) using a second set of vectors also defined relative  
8 to the local coordinate reference system. Thereafter, the surface area of each facet is  
9 consecutively projected onto each beam folding mirror in its respective mirror group in order to  
10 determine if each mirror is large enough to collect the return laser light rays from the scanned bar  
11 code. This step can be carried out using geometrical projection techniques well known in the  
12 mathematical arts. Afterwards, geometrical projections onto the surfaces of each beam folding  
13 mirror are analyzed with a view towards modifying (i.e. trimming) the dimensions of each such  
14 mirror so that the maximum number of return light rays are collected using beam folding mirrors  
15 having minimized surface dimensions.

#### 16 Steps Involving The Design Of Laser Scanning Station No. 2

17  
18  
19 As indicated in Fig. 7J, step D1 of the design method involves, for each scanning facet  
20 passing through Laser Scanning Station No. 2, assigning (initial or updated) coordinate values  
21 for the position and orientation of each beam folding mirror employed in the Laser Scanning  
22 Station No. 2, and using such coordinate values, construct a Vector-Based Reflection Model of  
23 the propagation of the laser beam diffracted from the scanning facet towards and off the laser  
24 beam folding mirrors in the Laser Scanning Station so as to enable the geometrical modeling of  
25 laser scanning plane generation processes during each revolution of the holographic scanning  
26 disc about its axis of rotation.

27  
28 As indicated in Fig. D2A, step D2A of the design method involves, for each scanning  
29 facet passing through Laser Scanning Station No. 2, integrating the Vector-Based Diffraction  
30 Model created in Step CA2 and the Vector-Based Reflection Model created in step D1 so as to  
31 create a Vector-Based Geometric Optics Model of the laser scanning plane process generated  
32 from the scanning facet as it is passed through Laser Scanning Station No. 2.

33 As indicated in Fig. 7K, step D2B of the design method involves importing the Vector-  
34 Based Geometric Optics Model created during step D2A into the 3-D Solid Geometry Model of  
35 the Holographic Scanning System created during Step B3 in order to enable the 3-D Solid  
36 Geometry Model of the Holographic Scanning System to generate, relative to the global  
37 coordinate reference system, geometrical models of the laser scanning planes produced during  
38 each revolution of the holographic scanning disc

39 As indicated in Fig. 7K, step D3 of the design method involves using the Vector-Based  
40 Geometric Optics Models embodied within the 3-D Solid Geometry Model of the Holographic  
41 Scanning System to graphically plot the partial laser scanning pattern resulting from laser  
42 scanning beam production processes supported upon Laser Scanning Station No. 2.

As indicated in Fig. 7L, step D4 of the design method involves determining whether the parameters in the vector-based geometric optics model are optimally set so that the laser scan planes produced from laser scanning station 2 converge towards the desired laser scanning planes to be generated therefrom. If the designer determines that the laser scanning planes produced from laser scanning station ST2 have not yet converged towards the desired laser scanning planes to be generated therefrom, then the design process proceeds to step D5 in Fig. 7L, at which point (Step thirtieth), the designer may, as necessary, modify the position of the beam folding mirrors employed in Laser Scanning Station ST2, and/or modify the facet parameters on the scanning disc as deemed necessary to achieve correspondence therebetween or to achieve an otherwise desired laser scanning pattern. Thereafter, the design process returns to step D1, where updated coordinate values are reassigned to the position and orientation of each beam folding mirror, and vector-based reflection models are modified based on such modified coordinate values. During each recursive loop from steps D1 through D4, Truncation Analysis and Gaussian Beam Analysis used in Steps C4 and C5 can be re-performed in connection with Laser Scanning Station ST2, in order to re-specify the VLD lens in Geometrical Optics Model of each LBPM, and determine the depth of field and resolution parameters for each scanning plane generated from the holographic scanning disc. If the designer determines that the laser scanning planes produced from laser scanning station ST2 have converged towards the desired laser scanning planes to be generated therefrom, then the design process proceeds to Step D6 in Fig. 7K, at which point (Step thirty-one), the designer optimizes the physical dimensions of each beam folding mirror in laser scanning station ST2. After a number of recursive loops, the parameters in the Vector-Based Geometric Optics Model will be optimally set so that the laser scanning planes produced from Laser Scanning Station ST2 converge towards the desired laser scanning planes to be generated therefrom.

As indicated in Fig. 7L, step D5 of the design method involves modifying, as necessary, the position of the beam folding mirrors employed in Laser Scanning Station No. 2, and/or modifying the facet parameters to achieve correspondence therebetween or to achieve an otherwise desired laser scanning pattern.

As indicated in Fig. 7L, step D6 of the design method involves optimizing the physical dimensions of each beam folding mirror employed in Laser Scanning Station No. 2 by projecting the geometry of each scanning facet onto each beam folding mirror involved in the generation of each scanning plane from the Laser Scanning Station. A more detailed description of this step is described above with respect to step C10 of Fig. 7H.

### Steps Involving The Design Of Laser Scanning Station No. 3

As indicated in Fig. 7M, step E1 of the design method involves, for each scanning facet passing through Laser Scanning Station No. 3, assigning (initial or updated) coordinate values for the position and orientation of each beam folding mirror employed in the Laser Scanning Station No. 3, and using such coordinate values, construct a Vector-Based Reflection Model of the propagation of the laser beam diffracted from the scanning facet towards and off the laser beam folding mirrors in the Laser Scanning Station so as to enable the geometrical modeling of

laser scanning plane generation processes during each revolution of the holographic scanning disc about its axis of rotation.

As indicated in Fig. 7M, step E2A of the design method involves, for each scanning facet passing through Laser Scanning Station No. 3, integrating the Vector-Based Diffraction Model created in Step C2A and the Vector-Based Reflection Model created in step E1 above so as to create a Vector-Based Geometric Optics Model of the laser scanning plane process generated from the scanning facet as it is passed through Laser Scanning Station No. 3.

As indicated in Fig. 7M, step E2B of the design method involves importing the Vector-Based Geometric Optics Model created during Step E2A into the 3-D Solid Geometry Model of the Holographic Scanning System created during Step B3 in order to enable the 3-D Solid Geometry Model of the Holographic Scanning System to generate, relative to the global coordinate reference system, geometrical models of the laser scanning planes produced during each revolution of the holographic scanning disc.

As indicated in Fig. 7N, step E3 of the design method involves using the Vector-Based Geometric Optics Models embodied within the 3-D Solid Geometry Model of the Holographic Scanning System, to graphically plot the partial laser scanning pattern resulting from laser scanning beam production processes supported upon Laser Scanning Station No. 3.

As indicated in Fig. 7N, step E4 of the design method involves determining whether the parameters in the vector-based geometric optics model have been optimally set so that the laser scan planes produced from Laser Scanning Station No. 3 converge towards the desired laser scanning planes to be generated therefrom. If the designer determines that the laser scanning planes produced from laser scanning station ST3 have not yet converged towards the desired laser scanning planes to be generated therefrom, then the design process proceeds to Step E5 in Fig. 7M, at which point, the designer may, as necessary, modify the position of the beam folding mirrors employed in Laser Scanning Station ST3, and/or modify the facet parameters on the scanning disc as deemed necessary to achieve correspondence therebetween or to achieve an otherwise desired laser scanning pattern. Thereafter, the design process returns to Step E1, where updated coordinate values are reassigned to the position and orientation of each beam folding mirror, and vector-based reflection models are modified based on such modified coordinate values.

During each recursive loop from Steps E1 through E4, Truncation Analysis and Gaussian Beam Analysis used in Steps C4 and C5 can be reperformed in connection with Laser Scanning Station ST3, in order to respecify the VLD lens in Geometrical Optics Model of each LBPM, and determine the depth of field and resolution parameters for each scanning plane generated from the holographic scanning disc. If the designer determines that the laser scanning planes produced from laser scanning station ST3 have converged towards the desired laser scanning planes to be generated therefrom, then the design process proceeds to Step E6 in Fig. 7N, at which point the designer optimizes the physical dimensions of each beam folding mirror in laser scanning station ST3. After a number of recursive loops, the parameters in the Vector-Based Geometric Optics Model will be optimally set so that the laser scanning planes produced from Laser Scanning Station ST3 converge towards the desired laser scanning planes to be generated therefrom.

1 As indicated in Fig. 7N, step E5 of the design method involves modifying, as necessary,  
2 the position of the beam folding mirrors employed in Laser Scanning Station No. 3, and/or  
3 modify the facet parameters to achieve correspondence therebetween or to achieve an otherwise  
4 desired laser scanning pattern.

5 As indicated in Fig. 7N, step E6 of the design method involves optimizing the physical  
6 dimensions of each beam folding mirror employed in Laser Scanning Station No. 3 by projecting  
7 the geometry of each scanning facet onto each beam folding mirror involved in the generation of  
8 each scanning plane from the Laser Scanning Station. A more detailed description of this step is  
9 described above with respect to step C10 if Fig. 7H.

#### 11 Steps Involving The Design Of Laser Scanning Station No. 4

12  
13 As indicated in Fig. 7O, step F1 of the design method involves, for each scanning facet  
14 passing through Laser Scanning Station No. 4, assigning (initial or updated) coordinate values  
15 for the position and orientation of each beam folding mirror employed in the Laser Scanning  
16 Station No. 4, and using such coordinate values, construct a Vector-Based Reflection Model of  
17 the propagation of the laser beam diffracted from the scanning facet towards and off the laser  
18 beam folding mirrors in the Laser Scanning Station so as to enable the geometrical modeling of  
19 laser scanning plane generation processes during each revolution of the holographic scanning  
20 disc about its axis of rotation.

21 As indicated in Fig. 7O, step F2B of the design method involves importing the Vector-  
22 Based Geometric Optics Model created during Step F2A into the 3-D Solid Geometry Model of  
23 the Holographic Scanning System created during Step B3 in order to enable the 3-D Solid  
24 Geometry Model of the Holographic Scanning System to generate, relative to the global  
25 coordinate reference system, geometrical models of the laser scanning planes produced during  
26 each revolution of the holographic scanning disc.

27 As indicated in Fig. 7P, step F3 of the design method involves using the Vector-Based  
28 Geometric Optics Models embodied within the 3-D Solid Geometry Model of the Holographic  
29 Scanning System to graphically plot the partial laser scanning pattern resulting from laser  
30 scanning beam production processes supported upon Laser Scanning Station No. 4.

31 As indicated in Fig. 7P, step F4 of the design method involves determining whether the  
32 parameters in the vector-based geometric optics model are optimally set so that the laser scan  
33 planes produced from laser scanning station 4 converge towards the desired laser scanning  
34 planes to be generated therefrom.

35 As indicated in Fig. 7P, step F5 of the design method involves modifying, as necessary,  
36 the position of the beam folding mirrors employed in Laser Scanning Station No. 4, and/or  
37 modify the facet parameters to achieve correspondence therebetween or to achieve an otherwise  
38 desired laser scanning pattern.

39 As indicated in Fig. 7P, step F6 of the design method involves optimizing the physical  
40 dimensions of each beam folding mirror employed in Laser Scanning Station No. 4 by projecting  
41 the geometry of each scanning facet onto each beam folding mirror involved in the generation of

each scanning plane from the Laser Scanning Station. A more detailed description of this step is described above with respect to step C10 if Fig. 7H.

#### Steps Involving The Design Of The Holographic Laser Scanning Disc And The Laser Scanning Stations

As indicated in Fig. 7Q, step G of the design method involves laying out holographic scanning facets on the holographic scanning disc using the computed equalized areas for each facet, and any facet ordering imposed for satisfaction of a predetermined constraint.

As indicated in Fig. 7Q, step H1 of the design method involves designing the multi-function light diffractive grating employed within the laser beam production module of each Laser Scanning Station in the Holographic Scanning System. The input parameters are the angle of incidence of the facets, the average angle of diffraction of the facets, wavelength; the output parameters are the construction parameters required to make multi-function plate and dispersion plots for the laser beam production module and scanning disc.

As indicated in Fig. 7Q, step H2 of the design method involves using a spreadsheet program to perform Astigmatism Analysis on the resulting design of the Laser Beam Production Module. The inputs to the spreadsheet program are multi-function plate parameters; whereas the output parameters are convergence/divergence plots of laser beams produced from the multi-function plate.

As indicated in Fig. 7Q, step H3 of the design method involves using a spreadsheet program to perform Dispersion Analysis on the resulting design for each Laser Beam Production Module and holographic scanning disc. The inputs to the spreadsheet program are multi-function plate parameters, average facet parameters; whereas the output parameters are dispersion plots of scanning facets.

As indicated in Fig. 7R, step I1 of the design method involves, for each Laser Scanning Station, using a spreadsheet program to design the light collection mirror disposed beneath the holographic scanning disc in relation to the specified location of the photodetector associated therewith. This process involves using the specifications for the holographic scanning disc, scanner housing, beam folding mirrors and resulting laser scanning pattern. The input parameters to the spreadsheet program are the maximum distance above the scanning disc (i.e. box height), the angle of incidence of the laser beam on the scanning disc, focal length of the light collection mirror, collection width of the worst case scanning facet, and scan angle of facet; whereas the output parameters are surface specifications of the light collecting surface.

As indicated in Fig. 7R, step I2 of the design method involves using a spreadsheet program to perform Off-Bragg Analysis on focused light rays being directed from the light collection mirror through the holographic scanning disc, towards the photodetector within Laser Scanning Station. The input parameters to the spreadsheet program are the extreme Bragg angles and Bragg sensitivity curve; whereas the output parameters are percentage of light loss due to diffraction through scanning facet. If light loss is too great, then respond by changing position of photodetector and/or change angle of incidence A.



1 As indicated in Fig. 7R, step I3 of the design method involves using a spreadsheet  
2 program to determine the minimum area of the photodetector employed within the light  
3 collection and photodetection subsystem in each Laser Scanning Station. This procedural step  
4 solves the problem of the beam diameter increasing in size at the photodetector in response to  
5 increased axial motion in the image plane. The input parameters to the spreadsheet program are  
6 the extreme angles of left, right, in and out beams off the light collection mirror to the  
7 photodetector (i.e. cone of rays from light collection mirror to photodetector), the distance from  
8 the light collection mirror to the photodetector, focal length of light collection mirror, and depth  
9 of field at target; whereas the output parameters are the surface area of the photodetector. If at  
10 any stage of the design process, the worst case geometry gets worse, then the detector area  
11 design step and light collection mirror (size and shape) design step are repeated.

12 Below is a procedure for minimizing the detector area in the bioptical laser scanner of the  
13 present invention: (1) Insert all key parameters into a light collection mirror/detector-size  
14 spreadsheet; (2) Key parameters are: (a) assumed height of detector above disk (this will be  
15 modified by the spreadsheet design process), (b) assumed distance from disk rotation axis (also  
16 modified by the spreadsheet design process), (c) angle of incidence of the VLD beam at the disk,  
17 (d) angle of diffraction, (e) radius of disk, (f) minimum inner radius of facets, (g) maximum  
18 outer radius of facets, (h) divergence of incident VLD beam at disk, (j) diffraction focal length of  
19 facet (waist location), and (k) desired depth of field; (3) the spreadsheet design program is run  
20 with the above parameters; (4) the detector area is one of the output parameters provided by the  
21 spreadsheet; (5) If the detector area is larger than desired, one, or both, of the two main assumed  
22 input parameters, (a) and (b) is (are) adjusted until a desired detector size is achieved.

23 Parameter (a) employed in the above procedure is generally fixed by other requirements,  
24 such as the height of the scanner box and the need to avoid obstructing the outgoing and return  
25 beam paths. Decreasing the distance from the axis of rotation (parameter b) will decrease the size  
26 of the photodetector. However, decreasing this distance will also increase the depth of the light  
27 collection mirror below the disk. So an optimum value may have to be selected. This optimum  
28 value is often a "best compromise" between depth of the light detecting mirror and size of the  
29 photodetector. The spreadsheet will provide the necessary information for making that selection.  
30 The light collection mirror/photodetector-size spreadsheet is simply an application of the  
31 geometric and trigonometric equations associated with the light collection mirror/detector  
32 geometry.

33 As indicated in Fig. 7R, step J of the design method involves using the finalized models  
34 in order to construct the holographic scanning disc, and components employed within the  
35 Holographic Scanning System

36 As indicated in Fig. 7R, step K of the design method involves assembling the constructed  
37 components to produce the Holographic Scanning System.

### 38 Modifications To Illustrative Embodiments of Present Invention

39  
40  
41 The illustrative embodiments of the holographic laser scanning system of the present  
42 invention as described above may be modified in various ways using the design method set forth

1 herein. For example, more or less groups of beam folding mirrors can be added to each laser  
2 scanning station within the system. Also more or less laser scanning stations might be employed  
3 within the system. Also, more or less facets (or groups of facets) and corresponding groups of  
4 light bending mirrors may be added. Also, the scan pattern produced from the bottom and side  
5 windows can be altered. Also, the dimensions of the scanner housing and the optical subsystem  
6 housed therein can be altered. Such modifications might be practiced in order to provide an  
7 omnidirectional laser scanning pattern having scanning performance characteristics optimized  
8 for a specialized scanning application.

9 While the scanning disc of the illustrative embodiment employed facets having low  
10 elevation angle characteristics and no (i.e. zero) skew angle characteristics, it is understood that  
11 it might be desirable in particular applications to use scanning facets having low elevation angle  
12 characteristics and left and/or right skew angle characteristics to as to enable a compact scanner  
13 design in a particular application.

14 While the various embodiments of the holographic laser scanner hereof have been  
15 described in connection with linear (1-D) bar code symbol scanning applications, it should be  
16 clear, however, that the scanning apparatus and methods of the present invention are equally  
17 suited for scanning 2-D bar code symbols, as well as alphanumeric characters (e.g. textual  
18 information) in optical character recognition (OCR) applications, as well as scanning graphical  
19 images in graphical scanning arts.

20 Several modifications to the illustrative embodiments have been described above. It is  
21 understood, however, that various other modifications to the illustrative embodiment of the  
22 present invention will readily occur to persons with ordinary skill in the art. All such  
23 modifications and variations are deemed to be within the scope and spirit of the present invention  
24 as defined by the accompanying Claims to Invention.